QNAP

QNAP TS-1232PXU-RP-4G NAS Rack (2U) Annapurna Labs AL324 4 GB DDR4 72 TB HDD QNAP Turbo System Black

Brand : QNAP **Product code:** TS-1232PXU-RP-4G/72TB-IWP

Product name: TS-1232PXU-RP-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing
- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning
- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of Google G Suite and Microsoft 365
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks
- Expand the application potential of the TS-1232PXU-RP by installing a compatible PCle card
- Increase the storage capacity of the TS-1232PXU-RP with QNAP TR RAID expansion enclosures or TL IBOD

12x 3.5", 4GB DDR4, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 2x 250W PSU, 89x482x534 mm



| Character and | | D. ciam | |
|---|---|---|--|
| Storage | | Design | |
| Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration | Serial ATA II, Serial ATA III 2.5,3.5" ✓ 0, 1, 5, 6, 10, JBOD ✓ | Cooling type * Product colour Number of fans Fan diameter LED indicators | Active Black 2 fan(s) 7 cm HDD, LAN, Status |
| Online RAID expansion | 1 | Performance | |
| RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported | | Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level | NAS Small & Medium Business Cloud, iSCSI LUN 32.2 dB |
| Installed storage drive type * Supported storage drive types * Bad block scan | HDD HDD & SSD ✓ | Snapshot Web-based management Security algorithms | ✓ ✓ 256-bit AES, FIPS 140-2, HTTPS, |
| Processor | | Access Control List (ACL) | SSH, SSL/TLS ✓ |
| Processor manufacturer * | Annapurna Labs | Reset button | 1 |
| Processor family * | Annapurna Labs | On/off switch | √ |
| Processor model * | AL324 | Built-in FTP server | ✓ |
| Processor frequency * Processor cores | 1.7 GHz 4 | Browser supported | Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+, Google Chrome |
| Memory | | System log | √ |
| Internal memory * | 4 GB | Hot spare | ✓ |
| Internal memory type | DDR4 | S.M.A.R.T. support | ✓ |
| Maximum RAM supported | 16 GB | Share folder | CIFS/SMB |
| Memory slots | 1 | Universal Plug and Play (UPnP) | √ |
| Memory form factor Flash memory | UDIMM 512 MB | USB copy function | ✓ |
| Network | JIZ MD | Software | |
| | , | Operating system installed * | QNAP Turbo System |
| Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported | 100,1000,2500,10000 Mbit/s | Operating system version Windows operating systems supported | 4.4.3 Windows 10, Windows 7, Windows 8 |
| (max) | 10000 Mbit/s | Linux operating systems supported | ✓ |
| DHCP client | ✓ | | |
| DHCP server | 1 | | |
| Jumbo frames support | ✓ | | |

| Network | | Software | |
|---|----------------------------------|--|--|
| iSCSI support | 1 | Sortware | Mac OS X 10.10 Yosemite. Mac OS X |
| Wake-on-LAN ready Supported network protocols Link aggregation | PPTP, L2TP/IPSec, OpenVPN, QBelt | Mac operating systems supported | 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina |
| Load balancing system WLAN adapter supported | 4 | Server operating systems supported | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows |
| Ports & interfaces | | | Server 2019 |
| USB port * | ✓ | Power | |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports * | 4 2 SFP+ 2 | Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) AC input voltage | Built-in 250 W 2 83.57 W 100 - 240 V |
| Design | | Fan voltage | 12 V |
| Chassis type * | Rack (2U) | Weight & dimensions | |
| | | Width * Depth * Height * Weight | 482 mm 534 mm 89 mm 11.3 kg |
| | | Packaging content | |
| | | Cables included Number of screws | AC, LAN (RJ-45) 84 |
| | | Operational conditions | |
| | | Operating temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C 5 - 95% |

