QNAP

QNAP DS723+ NAS Desktop Ethernet LAN Black R1600

Brand: QNAP **Product code**: DS723+/24TB-REDPLUS

Product name: DS723+

AMD Ryzen R1600, 2 GB DDR4 ECC, 20.7 dB, 65 W, 100 - 240 V QNAP DS723+. Total installed storage capacity: 24 TB, Installed storage drive type: HDD, Supported storage drive types: HDD & SSD. Processor family: AMD Ryzen, Processor manufacturer: AMD, Processor model: R1600. Internal memory: 2 GB, Internal memory type: DDR4, Maximum RAM supported: 32 GB. Ethernet LAN data rates: 10,100,1000 Mbit/s, Ethernet LAN data rate supported (max): 10000 Mbit/s, Supported network protocols: SMB1 (CIFS), SMB2, SMB3, NFSv3, NFSv4, NFSv4.1, NFS Kerberized sessions, iSCSI, HTTP, HTTPs, FTP,.... Chassis type: Desktop, Cooling type: Active, Product colour: Black





| Storage | | Design | |
|---|---|--------------------------------------|---|
| <u> </u> | | - | |
| Storage drive interface * | Serial ATA | Product colour | Black |
| Storage drive sizes supported | 2.5,3.5,M.2 | Number of fans | 1 fan(s) |
| Number of M.2 (M & B) slots | 2 | Fan diameter | 9.2 cm |
| RAID support * | ✓ | Drive bay locking | ✓ |
| RAID levels | 0, 1, 5, 6, 10, JBOD | LED indicators | Power, Status |
| Online RAID migration | ✓ | Cable lock slot | ✓ |
| Online RAID expansion | ✓ | Cable lock slot type | Kensington |
| Hot-swap drive bays | ✓ | Performance | |
| Supported file systems | BTRFS, Fat, HFS+, NTFS, exFAT, ext3, ext4 | Type * | NAS |
| Storage drives installed * | ✓ | Device class * | Home & Home Office |
| Total installed storage capacity * | 24 TB | Backup function * | ✓ |
| Number of storage drives installed * | 2 | Backup features | Cloud, iSCSI LUN |
| Number of storage drives supported | 2 | Multilingual support | ✓ |
| * | 2 | Number of users | 2048 user(s) |
| Installed storage drive type * | HDD | Noise level | 20.7 dB |
| Supported storage drive types * | HDD & SSD | Share folder access right management | ✓ |
| Processor | | Security algorithms | AES, SSH, HTTPS, SSL/TLS |
| Processor manufacturer * | AMD | Access Control List (ACL) | ✓ |
| Processor family * | AMD Ryzen | Reset button | ✓ |
| Processor model * | R1600 | On/off switch | ✓ |
| Processor frequency * | 2.6 GHz | Built-in FTP server | ✓ |
| Processor boost frequency Processor cores | 3.1 GHz 2 | Browser supported | Google Chrome, Firefox, Microsoft Edge, Safari |
| Processor threads | 4 | System log | ✓ |
| Number of processors supported | 1 | Share folder | 512 |
| Memory | | Software | |
| Internal memory type | DDR4 | Operating system installed * | DiskStation Manager |
| Maximum RAM supported Memory slots | 32 GB 2 | Server operating systems supported | Windows Server 2016, Windows Server 2019 |
| Internal memory * | 2 GB | Power | |
| Memory form factor | SO-DIMM | Power supply location | External |
| | | to to A | • |

| Memory | | Power | |
|---|---|-------------------------------------|---|
| ECC | ✓ | Power supply unit (PSU) capacity | 65 W |
| Network | | Power consumption (typical) | 21.07 W |
| Ethernet LAN * | ✓ | Power consumption (HDD standby) | 8.62 W |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | AC input voltage AC input frequency | 100 - 240 V 50 - 60 Hz |
| Ethernet LAN data rate supported (max) | 10000 Mbit/s | Weight & dimensions | 30 - 00 112 |
| iSCSI support | ✓ | Width * | 106 mm |
| Wake-on-LAN ready | ✓ | Depth * | 223 mm |
| | SMB1 (CIFS), SMB2, SMB3, NFSv3, NFSv4, NFSv4.1, NFS Kerberized sessions, iSCSI, HTTP, HTTPs, FTP, | Height * | 166 mm |
| Supported network protocols | | Packaging content | |
| Link aggregation | SNMP, LDAP, CalDAV | External power adapter | ✓ |
| Load balancing system | , | Cables included | AC, LAN (RJ-45) |
| Ports & interfaces | • | Power cables quantity | 1 |
| | | Technical details | |
| USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A | ✓ | Sustainability compliance | ✓ |
| ports quantity | 1 | Sustainability certificates | CCC, CE, Federal Communications Commission (FCC), RoHS, UKCA |
| eSATA ports quantity Ethernet LAN (RJ-45) ports * | 1 2 | Compliance certificates | CCC, CE, Federal Communications Commission (FCC), RoHS, UKCA |
| Concurrent connections PCI Express x2 (Gen 3.x) slots | 500 1 | Operational conditions | |
| | - | Operating temperature (T-T) | 0 - 40 °C |
| Design | 5 1. | Operating relative humidity (H-H) | 8 - 80% |
| Chassis type * | Desktop | Storage temperature (T-T) | -20 - 60 °C |
| Cooling type * | Active | Storage relative humidity (H-H) | 5 - 95% |
| | | Operating altitude | 0 - 5000 m |
| | | Certificates | |
| | | Certification | BSMI, VCCI, RCM, EAC, KC |

