QNAP


Brand: QNAP

QNAP TS-h1887XU-RP NAS Rack (2U) Intel Xeon E E-2334 16 GB DDR4 264 TB QuTS hero Black, White

Product code: TS-H1887XU-RP-E2334-16G/264TB-

Product name: TS-h1887XU-RP

Copper ethernet cabling technology 10GBASE-T





Intel Xeon E-2334, 16 GB ECC DDR4, 5GB Flash, 12 x 3.5" + 6 x 2.5", RJ-45, USB 3.2 Gen 2, 2U, 13 kg QNAP TS-h1887XU-RP. Type: NAS. Chassis type: Rack (2U). Device class: Large Enterprise Business. Processor family: Intel Xeon E, Processor model: E-2334, Processor frequency: 3.4 GHz. Internal memory: 16 GB, Internal memory type: DDR4. Total installed storage capacity: 264 TB. Operating system installed: QuTS hero



| Storage | | Performance | |
|--|--|---|---|
| Storage Storage drive interface * Supported storage drive interfaces Storage drive sizes supported System drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Supported file systems Storage drives installed * Total installed storage capacity * | Serial ATA Serial ATA 2.5,3.5" 3.5" ✓ 1, 5, 6, 10, 50, 60, JBOD ✓ ✓ FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 ✓ 264 TB | Performance Backup function * Backup features Multilingual support Number of users Snapshot Management protocols Web-based management Share folder access right management Security algorithms Access Control List (ACL) Reset button On/off switch | Cloud, iSCSI LUN 16000 user(s) SMB/CIFS, AFP, NFS HTTPS, SNMPv2, SNMPv3, SSH |
| Number of storage drives supported * Supported storage drive types * Disk roaming | 18 HDD & SSD ✓ | Built-in FTP server Browser supported | Apple Safari (latest version), Google Chrome (latest version), Microsoft Edge (latest version), Mozilla Firefox |
| Processor | | System log | (latest version) ✓ |
| Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores Processor threads Processor cache CPU configuration (max) | Intel Intel Xeon E E-2334 3.4 GHz 4.8 GHz 4 8 8 MB | Hot spare Disk scan S.M.A.R.T. support Share folder Software Operating system installed * Operating system version | Thick, Thin QuTS hero h5.0.1 |
| Memory | | | |
| Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor ECC Flash memory | 16 GB DDR4 128 GB 4 UDIMM ✓ 5000 MB | | |
| Network | | | |
| Ethernet LAN * Ethernet LAN data rates | 100,1000,2500 Mbit/s | | |

| Motuvouk | | Coffware | |
|---|----------------------------------|--|--|
| Network DHCP server | 1 | Software | Windows 10, Windows 10 |
| Jumbo frames support | 1 | | Education, Windows 10 Education |
| iSCSI support | V | | x64, Windows 10 Enterprise, Windows 10 Enterprise x64, |
| Supported network protocols | IPv4, IPv6 | | Windows 10 Home, Windows 10 |
| Dynamic DNS (DDNS) | ✓ | | Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, |
| Ports & interfaces | | | Windows 10 Pro, Windows 10 Pro |
| USB port * | ✓ | | x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A | 4 | Windows anarating systems | Windows 7 Enterprise, Windows 7 |
| ports quantity Ethernet LAN (RI-45) ports * | 4 | Windows operating systems supported | Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, |
| Number of SATA III connectors | 18 | | Windows 7 Home Premium, Windows 7 Home Premium x64, |
| Concurrent connections | 11000 | | Windows 7 Professional, Windows 7 |
| PCI Express x8 (Gen 4.x) slots | 1 | | Professional x64, Windows 7 Starter, Windows 7 Starter x64, |
| Design | | | Windows 7 Ultimate, Windows 7 |
| Chassis type * | Rack (2U) | | Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, |
| Cooling type * | Active | | Windows 8 Enterprise x64, Windows |
| Product colour | Black, White | | 8 Pro, Windows 8 Pro x64, Windows 8 x64 |
| Number of fans | 4 fan(s) | Linux operating systems supported | CentOS 7.0, Ubuntu 14.04, |
| Fan diameter LED indicators | 6 cm HDD, LAN, Status, USB | Linux operating systems supported | openSUSE 12.1, openSUSE 12.2 |
| | TIDD, LAIN, Status, OSB | | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 |
| Performance | NAC | | Sierra, Mac OS X 10.13 High Sierra, |
| Type * Device class * | NAS Large Enterprise Business | Mac operating systems supported | Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 |
| Device class | Large Effectprise Business | | Catalina, Mac OS X 11.0 Big Sur, |
| | | | Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura |
| | | | Windows Server 2008 R2, Windows |
| | | Server operating systems supported | Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows |
| | | | |
| | | | Server 2019 |
| | | Other operating systems supported | |
| | | Other operating systems supported Power | |
| | | Power Power supply location | IBM AIX 7.1, Solaris 10 Built-in |
| | | Power Power supply location Power supply unit (PSU) capacity | IBM AIX 7.1, Solaris 10 Built-in 550 W |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units | IBM AIX 7.1, Solaris 10 Built-in |
| | | Power Power supply location Power supply unit (PSU) capacity | IBM AIX 7.1, Solaris 10 Built-in 550 W |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) | IBM AIX 7.1, Solaris 10 Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * | Built-in 550 W 2 148.94 W 432 mm 511.2 mm |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * | IBM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight | Built-in 550 W 2 148.94 W 432 mm 511.2 mm |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Trusted Execution Technology | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Trusted Execution Technology (VT-x) Intel Virtualization Technology for | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Trusted Execution Technology (VT-x) Intel Virtualization Technology for Directed I/O (VT-d) | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Trusted Execution Technology (VT-x) Intel Virtualization Technology for | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |

Operational conditions

Operating temperature (T-T) $0 - 40 \,^{\circ}\text{C}$ Operating relative humidity (H-H) 5 - 95%Storage temperature (T-T) $-20 - 70 \,^{\circ}\text{C}$

