QNAP

QNAP TS-h1887XU-RP NAS Rack (2U) Intel Xeon E E-2334 16 GB DDR4 192 TB QuTS hero Black, White

Brand : QNAP **Product code:** TS-H1887XU-RP-E2334-16G/192TB-EV

Product name: TS-h1887XU-RP

Copper ethernet cabling technology 10GBASE-T

Intel Xeon E-2334, 16 GB ECC DDR4, 5GB Flash, 12×3.5 " + 6×2.5 ", RJ-45, USB 3.2 Gen 2, 2U, 13 kg QNAP TS-h1887XU-RP. Type: NAS. Chassis type: Rack (2U). Device class: Large Enterprise Business. Processor family: Intel Xeon E, Processor model: E-2334, Processor frequency: 3.4 GHz. Internal memory: 16 GB, Internal memory type: DDR4. Total installed storage capacity: 192 TB. Operating system installed: QuTS hero



| Storage | | Performance | |
|--|---|---|--|
| Storage drive interface * | Serial ATA | Backup function * | ✓ |
| Supported storage drive interfaces | Serial ATA | Backup features | Cloud, iSCSI LUN |
| Storage drive sizes supported | 2.5,3.5" | Multilingual support | ✓ |
| System drive sizes supported | 3.5" | Number of users | 16000 user(s) |
| RAID support * | ✓ | Snapshot | ✓ |
| RAID levels | 1, 5, 6, 10, 50, 60, JBOD | Management protocols | SMB/CIFS, AFP, NFS |
| Online RAID migration | ✓ | Web-based management | ✓ |
| Online RAID expansion | ✓ | Share folder access right | √ |
| RAID rebuild | ✓ | management | * |
| Supported file systems | FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 | Security algorithms Access Control List (ACL) | HTTPS, SNMPv2, SNMPv3, SSH ✓ |
| Storage drives installed * | ✓ | Reset button | ✓ |
| Total installed storage capacity * | 192 TB | On/off switch | ✓ |
| Number of storage drives supported | 18 | Built-in FTP server | ✓ |
| * Supported storage drive types * Disk roaming | HDD & SSD ✓ | Browser supported | Apple Safari (latest version), Google Chrome (latest version), Microsoft Edge (latest version), Mozilla Firefo (latest version) |
| Processor | | System log | V |
| Processor manufacturer * | Intel | Hot spare | ✓ |
| Processor family * | Intel Xeon E | Disk scan | ✓ |
| Processor model * | E-2334 | S.M.A.R.T. support | ✓ |
| Processor frequency * | 3.4 GHz | Share folder | Thick, Thin |
| Processor boost frequency | 4.8 GHz | Software | |
| Processor cores | 4 | Operating system installed * | QuTS hero |
| Processor threads | 8 | | h5.0.1 |
| Processor cache | 8 MB | Operating system version | 115.0.1 |
| CPU configuration (max) | 1 | | |
| Memory | | | |
| Internal memory * | 16 GB | | |
| Internal memory type | DDR4 | | |
| Maximum RAM supported | 128 GB | | |
| Memory slots | 4 | | |
| Memory form factor | UDIMM | | |
| ECC | 1 | | |
| Flash memory | 5000 MB | | |
| Network | | | |
| Ethernet LAN * | 1 | | |
| Ethernet LAN data rates | 100,1000,2500 Mbit/s | | |
| | | | |

| Motuvouk | | Coffware | |
|---|----------------------------------|--|--|
| Network DHCP server | 1 | Software | Windows 10, Windows 10 |
| Jumbo frames support | 1 | | Education, Windows 10 Education |
| iSCSI support | V | | x64, Windows 10 Enterprise, Windows 10 Enterprise x64, |
| Supported network protocols | IPv4, IPv6 | | Windows 10 Home, Windows 10 |
| Dynamic DNS (DDNS) | ✓ | | Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, |
| Ports & interfaces | | | Windows 10 Pro, Windows 10 Pro |
| USB port * | ✓ | | x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A | 4 | Windows anarating systems | Windows 7 Enterprise, Windows 7 |
| ports quantity Ethernet LAN (RI-45) ports * | 4 | Windows operating systems supported | Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, |
| Number of SATA III connectors | 18 | | Windows 7 Home Premium, Windows 7 Home Premium x64, |
| Concurrent connections | 11000 | | Windows 7 Professional, Windows 7 |
| PCI Express x8 (Gen 4.x) slots | 1 | | Professional x64, Windows 7 Starter, Windows 7 Starter x64, |
| Design | | | Windows 7 Ultimate, Windows 7 |
| Chassis type * | Rack (2U) | | Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, |
| Cooling type * | Active | | Windows 8 Enterprise x64, Windows |
| Product colour | Black, White | | 8 Pro, Windows 8 Pro x64, Windows 8 x64 |
| Number of fans | 4 fan(s) | Linux operating systems supported | CentOS 7.0, Ubuntu 14.04, |
| Fan diameter LED indicators | 6 cm HDD, LAN, Status, USB | Linux operating systems supported | openSUSE 12.1, openSUSE 12.2 |
| | TIDD, LAIN, Status, OSB | | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 |
| Performance | NAC | | Sierra, Mac OS X 10.13 High Sierra, |
| Type * Device class * | NAS Large Enterprise Business | Mac operating systems supported | Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 |
| Device class | Large Effectprise Business | | Catalina, Mac OS X 11.0 Big Sur, |
| | | | Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura |
| | | | Windows Server 2008 R2, Windows |
| | | Server operating systems supported | Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows |
| | | | |
| | | | Server 2019 |
| | | Other operating systems supported | |
| | | Other operating systems supported Power | |
| | | Power Power supply location | IBM AIX 7.1, Solaris 10 Built-in |
| | | Power Power supply location Power supply unit (PSU) capacity | IBM AIX 7.1, Solaris 10 Built-in 550 W |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units | IBM AIX 7.1, Solaris 10 Built-in |
| | | Power Power supply location Power supply unit (PSU) capacity | IBM AIX 7.1, Solaris 10 Built-in 550 W |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) | IBM AIX 7.1, Solaris 10 Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * | Built-in 550 W 2 148.94 W 432 mm 511.2 mm |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * | IBM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight | Built-in 550 W 2 148.94 W 432 mm 511.2 mm |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws | Built-in 550 W 2 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Trusted Execution Technology | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 | BM AIX 7.1, Solaris 10 Built-in 550 W 2 ✓ 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Trusted Execution Technology (VT-x) Intel Virtualization Technology for | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Trusted Execution Technology (VT-x) Intel Virtualization Technology for Directed I/O (VT-d) | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |
| | | Power Power supply location Power supply unit (PSU) capacity Number of power supply units Redundant power supply (RPS) support Power consumption (typical) Weight & dimensions Width * Depth * Height * Package weight Packaging content Cables included Power cables quantity Number of screws Processor special features Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Trusted Execution Technology (VT-x) Intel Virtualization Technology for | Built-in 550 W 2 148.94 W 432 mm 511.2 mm 88.6 mm 19 kg AC, LAN (RJ-45) 2 112 |

Operational conditions

Operating temperature (T-T) $0 - 40 \,^{\circ}\text{C}$ Operating relative humidity (H-H) 5 - 95%Storage temperature (T-T) $-20 - 70 \,^{\circ}\text{C}$

