

LevelOne GEMINI 8-Channel PoE Network Video Recorder, 8 PoE Outputs, H.265

Brand : LevelOne

Product code: NVR-0508

Product name : GEMINI 8-Channel PoE Network Video Recorder, 8 PoE Outputs, H.265

- Supports video resolutions up to 8 megapixels

- Supports 4k2k HDMI local display
- Built-in 8 PoE ports for PoE devices
- 2 x 3.5" hard drive bays support disk capacity of up to 6TB
- Video compression: H.265, H.264, MPEG4
- Free CMS (Central Management System) software with 64-channel license
- 8ch, 8 x PoE, H.265/264, VGA, HDMI, USB, 10/100/1000 Mbps, 110~230 VAC, 3 kg

LevelOne GEMINI 8-Channel PoE Network Video Recorder, 8 PoE Outputs, H.265. Video input channels: 8 channels, Maximum resolution: 3840 x 2160 pixels, Video recording modes: 720p, 1080p. Maximum storage capacity: 12 TB, HDD interface: Serial ATA. Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.3at, Supported network protocols:

TCP,UDP,IPv4,IPv6,Http,Https,SMTP,NTP,SNTP. LED indicators: Alarm, HDD, Power, Product colour: Black, Compatible products: Onvif camera. Power consumption (typical): 180 W, AC input voltage: 100 - 230 V





PerformanceFeaturesVideo input channels& SchannelsCompatible productsOn/cameraVideo recording modes3 20p, 1080pContury of originChinaMaximum resolution*& 44 sec1(s)CertificationCertificationNumber of users6 4 user(s)PererPererVideo formats supported16 264, 1264, 14, 265, MPEGAPererNumber of usersOperating system installed160 Mbit/sStemequirementsNumber of usersNumber of fans16 0 Mbit/sStemequirementsNumber of usersMir-Fi*StemequirementsNumber of usersNumber of usersMir-Fi*StemequirementsNumber of usersNumber of usersMir-Fi*StemequirementsNumber of USD supportedNumber of HDD supported2 Normal relative humidity(H=)Number of HDD supported2 NormalStemequirementNumber of HDD supported2 Normal relative humidity(H=)Normar of supported2 Normal relative humidity(H=)Number of HDD supported2 Normal relative humidity(H=)Normar of supported2 Normal relative humidity(H=)Normal relative humidity(H=)Normal relative humidity(H=)Normar of supported2 Normal relative humidity(H=)Normal relative humidity(H=)Normal relative humidity(H=)Normar of supported2 Normal relative humidity(H=)Normal relative humidity(H=)Normal relative humidity(H=)Normar of supported2 Normal relative humidity(H=)Normal relative humidity(H=)Normal relative humidity(H=) <t< th=""><th></th><th></th><th></th><th></th></t<>				
Nideo recording models720p. 1080pCountry of originChina Cartifaction	Performance		Features	
Video formats supported H.264, H.264, H.265, MPEG4 Power consumption (typical) 180 W Operating system installed Embedded LINUX Power consumption (typical) 180 W Number of fans 1 fan(s) System requirements Internet Explorer 9+ Wireless LAN features Fowser supported Internet Explorer 9+ Wireless LAN features Operating temperature (T-T) -10 - 55 °C HDD capacity* 0 GB Operating relative humidity (H-H) 10 - 90% HDD tapacity* 0 GB Width 315 mm Number of HDDs supported 2 Width 315 mm HDD interface Serial ATA Depth 52 mm Power over Ethemet (NoE) Veright 3kg 3kg Power over Ethemet (NoE) ports* 9 Package depth 435 mm Power over Ethemet (NoE) ports 1 Package depth 450 mm VGA (D-Sub) output ports 1 Package depth 523 kg VGA (D-Sub) output ports 1 Package depth 450 mm VGA (D-Sub) output ports 1 Package depth 450 mm VGA (D-Sub) output ports 1 Cables included AC VGA (D-Sub) output ports 1 Cablesin cluded AC VGA (D-Sub)	Video recording modes	720p, 1080p	Country of origin	China
Operating system installedEmbedded LINUXPower consumption (typical)180 WThroughput data rate160 Mbit/sAC input voltage100 - 230 VNumber of fans1 fan(s)System requirementsWi-Fi*XOperating requirementsWi-Fi*XOperating temperature (T-T)10 - 55 °CHard drive0 GB10 - 00%HDD capacity*0 GB10 - 00%Number of HDDs supported2Weight & dimensionsMumber of Ki Interface*5 erial ATADepth52 nmHDD interface*5 erial ATADepth3 kgPorts i interfaces10 - 00.000 Mbit/sPackage width3 kgPower over Ethernet (PoE)-Package depth450 nmPower over Ethernet (PoE)-Package keight367 nmPower over Ethernet (PoE) ports9Package keight377 nmPower over Ethernet (PoE) ports9Package keight377 nmPower over Ethernet (PoE) ports0Package height323 kgHDM output-Package tricted3.23 kgVGA (D-Sub) output ports1Calaes included-SB 3.2 GR (1.31 Gen 1) Type.1Calaes included-VGA (D-Sub) output ports1Calaes included-VGA (D-Sub) output ports1AC calaeter included-VGA (D-Sub) output ports1AC calaeter included-VGA (D-Sub) output ports1AC calaeter included-VGA (D-Sub) output ports<	Number of users		Power	
Number of fans1 fan(s)System requirementsWireless LAN featuresBrowser supportedInternet Explorer 9+Wi-Fi*×Operational conditionsHard drive0 GB0 perating relative humidity (H+H)10 - 55 °CHDD capacity *0 GB0 gerating relative humidity (H+H)10 - 90%Number of HDDs supported2Weight & dimensions10 - 90%Maximum storage capacity *12 TBWidth315 mmHDD interface *Serial ATADepth385 mmPorts & interfaces9Package width3kgEthernet LAN (8/45) ports *9Package width450 mmPower over Ethernet (PoE)*Package keight387 mmPower over Ethernet (PoE)*Package keight387 mmPower over Ethernet (PoE) ports quantity*Package keight32 kgYGA (D-Sub) output ports1Package keight32 kgYGA (D-Sub) output ports1Cables includedYGA	Operating system installed	Embedded LINUX		
Wi-Fi* × Operational conditions Hard drive -10 - 55 °C Hard drive Operating temperature (T-T) -10 - 55 °C HDD capacity * 0 GB Operating relative humidity (H-H) 10 - 90% Number of HDDs supported 2 Weight & dimensions Serial ATA Depth 52 mm HDD interface * Serial ATA Depth 52 mm Serial ATA Ports & interfaces 9 Package width 345 mm Ethernet LAN (RJ-45) ports * 9 Package width 435 mm Power over Ethernet (PoE) ✓ Package depth 450 mm Power over Ethernet (PoE) ports Package keight 387 mm Quantity ✓ Package keight 3.23 kg VSG (D-Sub) output ports 1 Package weight 3.23 kg VSG (D-Sub) output ports 1 Package weight 3.23 kg VSG (D-Sub) output ports 1 Package weight 3.23 kg USB 3.2 Gen 1 (3.1 Gen 1) Type-A C Coales included AC Audio RCA inputs 1 Gables included AC Supported network p	51	1 fan(s)	System requirements	
Hard drive - 0 GB Operating relative humidity (H-H) 10 - 55 °C HDD capacity * 0 GB Querating relative humidity (H-H) 10 - 90% Maximum storage capacity * 12 TB Width 315 mm HDD interface * Serial ATA Depth 52 mm Ports 6 interfaces Serial ATA Depth 385 mm Power over Ethernet LAN (R)-45) ports * 9 Package width 435 mm Power over Ethernet (PoE) ✓ Package depth 387 mm Power over Ethernet (PoE) ✓ Package depth 387 mm Power over Ethernet (PoE) ports quantity Package type Box HDMI output ✓ Package type Box HDMI output ✓ Package weight 3.23 kg VGA (D-Sub) output ports 1 Gables included AC Audio RCA inputs 1 Cables included AC Audio RCA outputs 1 Master (outer) case width 548 mm Supported network protocols 1EEE 802.3at CD manual ✓ Supported network protocols IEEE 802.3at Master (outer) case lenghth <td< td=""><td>Wireless LAN features</td><td></td><td>Browser supported</td><td>Internet Explorer 9+</td></td<>	Wireless LAN features		Browser supported	Internet Explorer 9+
Hard drive Operating relative humidity (H-H) 10 - 90% HDD capacity * 0 GB Gelating relative humidity (H-H) 10 - 90% Number of HDDs supported 2 Weight & dimensions Maximum storage capacity * 12 TB Width 315 mm HDD interface * Serial ATA Depth 52 mm Ports & interfaces Serial ATA Poth S 3 kg Ethernet LAN (RJ-45) ports * 9 Package depth 435 mm Power over Ethernet (PoE) ✓ Package depth 450 mm Power over Ethernet (PoE) ports augustity 10.0000 Mbit/s Package depth 450 mm Power over Ethernet (PoE) ports augustity 2 Package depth 3.2 kg VSA (D-Sub) output ports 1 Package type Box VGA (D-Sub) output ports 1 Package type Box VGA (D-Sub) output ports 1 Cadapter included AC Audio RCA inputs 1 Cadapter included AC Audio RCA inputs IEEE 802.3at CD manual - Supported network protocols ICP.UPP.IPV.HM.SMTP.NTP.SMTP.MIDES Master (outer) case length 450 mm Rack mounting ✓ Master (outer) case length 450 mm Rack mounting ✓<	Wi-Fi *	×	Operational conditions	
Number of HDDs supported2Weight & dimensionsMaximum storage capacity*12 TBWidth315 mmHDD interface*Serial ATADepth52 mmPorts & interfacesHeight385 mmEthernet LAN (RJ-45) ports*9Package width435 mmPower over Ethernet (POE)<				
Maximum storage capacity*12 TBWidth315 mmHDD interface*Serial ATADepth52 mmPorts & interfacesHeight385 mmEthernet LAN (R)-45) ports*9Package width435 mmPower over Ethernet (POE)/Package depth435 mmPower over Ethernet (POE)/Package depth450 mmPower over Ethernet (POE) ports quantity10,100,1000 Mbit/sPackage depth387 mmPower over Ethernet (POE) ports quantity8Package typeBoxPOWer over Ethernet (POE) ports quantity1Package weight3.23 kgVGA (D-Sub) output ports1Package weight3.23 kgUSB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity2Cables includedACAudio RCA outputs1Cables includedACAudio RCA outputs1CD manual*Networking standardsTCP,UDP,IPv4,IIPv6,Http,Https,SMTP,NTP,SMTP Logistics data 548 mmFeaturesMaster (outer) case width450 mmLED indicatorsAlarm, HDD, PowerMaster (outer) case length412 mmOn/off switchVMaster (outer) case gross weight14.1 kg	1 2		Weight & dimensions	
Ports & interfaces Weight 3 kg Ethernet LAN (RJ-45) ports * 9 Package width 435 mm Power over Ethernet (PoE) / Package depth 450 mm Ethernet LAN data rates 10,100,1000 Mbit/s Package depth 387 mm Power over Ethernet (PoE) ports quantity 1 Package width 387 mm POWer over Ethernet (PoE) ports quantity - Package depth Box VGA (D-Sub) output ports 1 Package weight 3.23 kg VGA (D-Sub) output ports 1 Cables included AC VGA (D-Sub) output ports 1 Cables included AC Audio RCA inputs 1 CD manual - Networking standards IEEE 802.3at CD manual - Supported network protocols TCP_UPIP.V4.IPV6,Https,SMTP,NTP,SMT Master (outer) case length 548 mm Rack mounting Alarm, HDD, Power Master (outer) case length 412 mm Dn/off switch _ Master (outer) case spress weight 14.1 kg	Maximum storage capacity *	12 TB		
Etherner LAN (R)-45) ports* 9 Package width 435 mm Power over Ethernet (PoE) ✓ Package depth 450 mm Power over Ethernet (PoE) 10,100,1000 Mbit/s Package height 387 mm Power over Ethernet (PoE) ports quantity Package height 387 mm POM output ✓ Package keight 387 mm VGA (D-Sub) output ports I Package weight 3.23 kg VGA (D-Sub) output ports I Package weight AC VGA (D-Sub) output ports I Cables included AC VGA (D-Sub) output ports I Cables included AC Audio RCA inputs I CD manual · Audio RCA outputs IEEE 802.3at CD manual · Supported network protocols TCP-UP, IPV4, IPV6, Https, SMTP, NTP, SMT Distics data · Features Mater (outer) case width 548 mm Rack mounting Alarm, HDD, Power Mater (outer) case length 410 mm LED indicators Alarm, HDD, Power Mater (outer) case gross weight 41.1 kg	Ports & interfaces			
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity2Packaging contentAudio RCA inputs1Cables includedACAudio RCA outputs1AC adapter includedNetworking standardsIEEE 802.3atCD manualSupported network protocolsTCP,UDP,IPv4,IPv6,Http,Https,SMTP,NTP,SMTPLogistics dataFeaturesMaster (outer) case width548 mmRack mountingMaster (outer) case length450 mmLED indicatorsAlarm, HDD, PowerMaster (outer) case height412 mmOn/off switchMaster (outer) case gross weight14.1 kg	Power over Ethernet (PoE) Ethernet LAN data rates Power over Ethernet (PoE) ports quantity	✓ 10,100,1000 Mbit/s 8	Package width Package depth Package height Package type	435 mm 450 mm 387 mm Box
ports quantity2Cables includedACAudio RCA inputs1AC adapter included·Audio RCA outputs1CD manual·Networking standardsIEEE 802.3atCD manual·Supported network protocolsTCP,UDP,IPv4,IPv6,Http,Https,SMTP,NTP,SNTPMaster (outer) case width548 mmRack mounting·Master (outer) case length450 mmLED indicatorsAlarm, HDD, PowerMaster (outer) case height412 mmOn/off switch·Master (outer) case gross weight14.1 kg		1	Packaging content	
FeaturesMaster (outer) case width548 mmRack mounting✓Master (outer) case length450 mmLED indicatorsAlarm, HDD, PowerMaster (outer) case height412 mmOn/off switch✓Master (outer) case gross weight14.1 kg	ports quantity Audio RCA inputs Audio RCA outputs	1 1	AC adapter included	1
Rack mounting✓Master (outer) case length450 mmLED indicatorsAlarm, HDD, PowerMaster (outer) case height412 mmOn/off switch✓Master (outer) case gross weight14.1 kg	Supported network protocols	TCP,UDP,IPv4,IPv6,Http,Https,SMTP,NTP,SNT	^P Logistics data	
LED indicatorsAlarm, HDD, PowerMaster (outer) case height412 mmOn/off switch✓Master (outer) case gross weight14.1 kg	Features		Master (outer) case width	548 mm
Floduces per master (buter) case 4 pc(s)	LED indicators	Alarm, HDD, Power	Master (outer) case height	412 mm

Features

Product colour

Black



4015867202272

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.