

## QNAP TS-932PX-4G NAS Tower Ethernet LAN Black Alpine AL-324





**Brand :** QNAP **Product code:** TS-932PX-4G/50TB-REDPRO

Product name: TS-932PX-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports empower bandwidth-demanding tasks and accelerate file sharing
- HBS provides comprehensive backup and data recovery; QuDedup deduplicates the data at the source to optimize storage and bandwidth usage, while reducing backup times
- Snapshots record your system status, allowing you to protect files and data from accidental deletion and malware attacks
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
- Qtier auto-tiering technology and SSD caching enable constant storage optimization
- Increase the storage capacity of the TS-932PX with QNAP TR RAID expansion enclosures or TL JBOD Alpine AL-324 1.7GHz, 4 GB DDR4, 512 MB, 5x 3.5, 4x 2.5", 2x 2.5G LAN, 2x 10G SFP+, 3x USB 3.2, 182.7x224.6x224.1 mm

Storage		Design	
Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays	Serial ATA III  2.5,3.5"  ✓  0, 1, 5, 6, 10, 50, 60, JBOD  ✓  ✓  ✓	Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators Cable lock slot Cable lock slot type	Tower Active Black 1 fan(s) 14 cm HDD, LAN, SSD, Status, USB  ✓ Kensington
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4	Performance	
Storage drives installed * Total installed storage capacity * Number of storage drives supported *	9	Type * Device class * Backup function *	NAS Small & Medium Business
Installed storage drive type * Supported storage drive types * Bad block scan Disk roaming	HDD HDD & SSD ✓	Backup features Buzzer Multilingual support Snapshot	Cloud, iSCSI LUN
Processor		Web-based management	<b>√</b>
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor architecture	Annapurna Labs Annapurna Labs Alpine AL-324 1.7 GHz ARM Cortex-A57	Security algorithms  Access Control List (ACL)  Reset button  On/off switch  Built-in FTP server	256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH, SSL/TLS
Memory		Browser supported	Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+,
Internal memory type Maximum RAM supported Memory slots Internal memory * Memory form factor Flash memory	DDR4 16 GB 1 4 GB SO-DIMM 512 MB	System log Hot spare S.M.A.R.T. support Share folder USB copy function	Mozilla Firefox
Network		Software	
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max)	100,1000,2500,10000 Mbit/s 10000 Mbit/s	Operating system installed * Operating system version Windows operating systems supported	QNAP Turbo System 4.4.2 Windows 10, Windows 7, Windows 8
DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready	1 1 1	Linux operating systems supported  Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina

Network		Software	
Supported network protocols  Link aggregation  Load balancing system  Dynamic DNS (DDNS)  WLAN adapter supported	regation ancing system  DNS (DDNS) Appear supported  interfaces  *  Gen 1 (3.1 Gen 1) Type-A antity  ts quantity  ts quantity  LAN (RJ-45) ports *  Query  Query  Serve  Serve  Serve  Serve  Serve  Powe  Numl  AC in  Fan v  Weig  the quantity  Pack  Exter  Oper  Oper	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Power	
		Power supply location Power supply unit (PSU) capacity Number of power supply units AC input voltage Fan voltage	External
Ports & interfaces			120 W
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports *			1 100 - 240 V 12 V
		Weight & dimensions	
		Width * Depth * Height *	224.6 mm 224.1 mm 182.7 mm
		Packaging content	
		External power adapter	✓
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

