QNAP TVS-872XT-i5-16G 96TB (Seagate Exos) 8-Bay NAS; Intel core i5-8400T 6-core 1.7 GHz Processor(max 3.3 Tower Ethernet LAN Black

Brand : QNAP

×

Product code: TVS-872XT-I5-16G/96TB-FXOS

Product name : TVS-872XT-i5-16G 96TB (Seagate Exos) 8-Bay NAS; Intel core i5-8400T 6-core 1.7 GHz Processor(max 3.3

- High-speed Thunderbolt<sup>™</sup> 3 with SMB protocol, allowing Mac® and Windows® users to collaborate on media editing

- 5-speed 10GBASE-T RJ45 connectivity accelerates virtualization applications and file sharing across teams and devices

- PCIe expandability allows the use of an entry-level graphics card to accelerate NAS video processing and GPU computing

- Install M.2 PCIe (Gen 3 x2, 2 GB/s) NVMe SSDs (sold separately) to set up caching or storage pools, improving file access efficiency

- 4K media playback and real-time transcoding; directly view creative works on an HDTV via HDMI 2.0 (4K @60Hz) output

- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks

Intel Core i5-8400T 1.7 GHz, DDR4, 8x 2.5/3.5" SATA III, 2x M.2, 1x 10G RJ-45, 2x 1G RJ-45, 2x PCIe, USB 3.0, 2x USB 3.1 C, 2x USB 3.1 A, HDMI 2.0, 2x 3.5mm, 188.2x329.3x279.6 mm

Supported storage drive sizes supportedSerial ATA IIIDevice class *Small & Medium BusinessStorage drive sizes supported2.5.3.5"Backup fracturesCloud, iSCSI LUNNumber of MZ (M & B) slots4BuzzerCloud, iSCSI LUNALD support *Multilingual supportOnline RAID migrationMultilingual supportOnline RAID expansionSecurity algorithmsSiche States, FIPS 140-2, HTTPS, SiMPV3, SSH, SSL/TLSRAID rebuildAccess Control List (ACL)Number of Storage drives installed *Storage drives installed *Moltes ServerNumber of storage drives supportedBuilt-in Tunes serverNumber of storage drive type *HDDStorage drive supportedSupported storage drive type *HDD & SSDBrowser supportedProcessor frequency *1.7 GHzSM.A.R.T. supportProcessor frequency *1.7 GHzSM.A.R.T. supportProcessor frequency *1.7 GHzSM.A.R.T. supportProcessor frequency *1.7 GHzSM.A.R.T. supportConfiguration (max)1.6 (1.8 (1.8 +2x4, 2x8)Windows operating system supportedProcessor frequency *1.7 GHzSM.A.R.T. supportProcessor codeSAS6More Storage system supportedProcessor frequency *1.7 GHzSM.A.R.T. supportProcessor frequency *1.7 GHzSM.A.R.T.	Storage		Performance	
Installed storage drive type * Supported storage drive types * Bad block scanHDD HDD & SSD *Browser supportedApple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla FirefoxBad block scan*System logProcessor*Hot spareProcessor frequency *1.7 GHzS.M.A.R.T. supportProcessor boost frequency3.3 GHzShare folderCIFS/SMBProcessor cache9 MBUniversal Plug and Play (UPnP)Bus typeDMI3USB copy functionConfigurable TDP-down frequency1SoftwareCPU configuration (max)1Operating system versionPCI Express configurations1x16, 1x8+2x4, 2x8Windows operating systems suportedWindows 10, Windows 7, Windows 8Processor codeSmart CacheFrocessor codeSR3X6Mac operating systems supportedProcessor codeSR3X6Mac operating systems supportedProcessor poerating modes64-bitMac operating systems supportedNo.11 El Capitan, Mac OS X 10.3 Hyß Sierra, Mac OS X 10.3	Supported storage drive interfaces Storage drive sizes supported Number of M.2 (M & B) slots RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed *	2.5,3.5" 2 4 0, 1, 5, 6, 10, 50, 60, JBOD 4 4 FAT32, HFS+, NTFS, ext3, ext4	Backup function * Backup features Buzzer Multilingual support Web-based management Security algorithms Access Control List (ACL) Reset button On/off switch Built-in iTunes server	Cloud, iSCSI LUN Cloud,
Processor frequency*1.7 GHzS.M.A.R.T. supportImage of the supportProcessor frequency3.3 GHzS.M.A.R.T. supportCIFS/SMBProcessor cache9 MBUniversal Plug and Play (UPnP)Image of the supportBus typeDMI3USB copy functionImage of the supportConfigurable TDP-down frequency1.2 GHzSoftwareImage of the supportCPU configuration (max)1SoftwareImage of the support	Supported storage drive types * Bad block scan	HDD & SSD	Browser supported	Microsoft Internet Explorer 10+, Mozilla Firefox
Processor boost frequency3.3 GHzShare folderCIFS/SMBProcessor cache9 MBUniversal Plug and Play (UPnP)Bus typeDMI3USB copy functionConfigurable TDP-down frequency1.2 GHzSoftwareCPU configuration (max)1Operating system version4.4.0ECC supported by processorXWindows operating systemsWindows 10, Windows 7, Windows 8PCI Express configurations1x16, 1x8+2x4, 2x8Windows operating systemsWindows 10, Windows 7, Windows 8PCI Express slots version3.0Linux operating systems supportedProcessor cache typeSmart CacheMac operating systems supportedMac OS X 10.10 Yosemite, Mac OS X 10.12Processor porating modes64-bitMac operating systems supportedNac OS X 10.13 High Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.13 Migh Sierra, Mac OS X 10.14 Migh Sierra, Mac OS X 10.14 Migh Sierra, Mac OS X 10.14 Migh Sierra, Mac OS X 10.13 Mig	Processor		Hot spare	1
CPU configuration (max)1SoftwareCPU configuration (max)1Operating system version4.4.0ECC supported by processorXWindows operating systems supportedWindows 10, Windows 7, Windows 8PCI Express configurations3.0Linux operating systems supportedMac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.11 Posemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.11 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.9 MavericksProcessor operating modes64-bitMac operating systems supportedMac OS X 10.10 Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.9 MavericksProcessor package size37.5 x 37.5 mmServer operating systems supportedWindows Server 2003, Windows Server 2003, Windows Server 2012, R2, Windows Server 2012 R2, Windows Server 2016	Processor boost frequency Processor cache	3.3 GHz 9 MB	Share folder Universal Plug and Play (UPnP)	✓
ECC supported by processorXOperating system version4.4.0PCI Express configurations1x16, 1x8+2x4, 2x8Windows operating systems supportedWindows 10, Windows 7, Windows 8PCI Express slots version3.0Linux operating systems supportedImage: Constant of the system supportedProcessor cache typeSmart CacheMac operating systems supportedImage: Constant of the system supportedProcessor codeSR3X6Mac operating systems supportedImage: Constant of the system supportedProcessor lithography14 nmMac operating systems supportedSierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS XProcessor operating modes64-bitSierra system supportedSierra systems supportedProcessor package size37.5 x 37.5 mmServer operating systems supportedWindows Server 2003, WindowsSteppingU0Server operating systems supportedServer 2008 R2, Windows Server 2012 R2, Windows Server 2012, Windows Server 2016	5 ,	1.2 GHz	Software	
Wildows Server 2010	ECC supported by processor PCI Express configurations PCI Express slots version Processor cache type Processor code Processor lithography Processor operating modes Processor package size Scalability Stepping	X 1x16, 1x8+2x4, 2x8 3.0 Smart Cache SR3X6 14 nm 64-bit 37.5 x 37.5 mm 1S U0	Windows operating systems supported Linux operating systems supported Mac operating systems supported	Windows 10, Windows 7, Windows 8 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks Windows Server 2003, Windows Server 2008 R2, Windows Server
	•			Windows Server 2016

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date

×

×

××

Processor		Power	
Thermal Design Power (TDP)	35 W	Power supply location	Built-in
Maximum internal memory	64 GB	Power supply unit (PSU) capacity	250 W
supported by processor Memory bandwidth supported by		Number of power supply units	1
processor (max)	41.6 GB/s	AC input voltage	100 - 240 V
Conflict-Free processor	1	Fan voltage	12 V
Memory		Weight & dimensions	
Internal memory type	DDR4	Width *	329.3 mm
Maximum RAM supported	32 GB	Depth *	279.6 mm
Memory slots	2	Height *	188.2 mm
Internal memory *	16 GB	Weight	7.06 kg
Flash memory	4000 MB	Packaging content	
Network		Cables included	AC, LAN (RJ-45)
Ethernet LAN *	1	Quick installation guide	4
Ethernet LAN data rates	10,100,1000,10000 Mbit/s	Processor special features	
Ethernet LAN data rate supported	10000 Mbit/s	Embedded options available	×
(max)	10000 Mbit/s	Enhanced Intel SpeedStep	1
Wi-Fi	×	Technology	•
DHCP client		Execute Disable Bit	
DHCP server	4	Idle States Intel 64	4
Jumbo frames support iSCSI support	4	Intel Clear Video Technology	4
Wake-on-LAN ready		Intel Enhanced Halt State	1
Supported network protocols	TCP/IP, IPv4, IPv6	Intel Identity Protection Technology	•
Dynamic DNS (DDNS)	<ul> <li>,,</li></ul>	version	1.00
WLAN adapter supported	4	Intel Secure Key Technology version	
Ports & interfaces		Intel Stable Image Platform Program	×
USB port *	1	(SIPP) Intel Trusted Execution Technology	×
USB 3.2 Gen 1 (3.1 Gen 1) Type-A		Intel TSX-NI	Â
ports quantity	1	Intel TSX-NI version	0.00
USB 3.2 Gen 2 (3.1 Gen 2) Type-A	2	Intel Virtualization Technology (VT-	
ports quantity		x)	4
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Intel Virtualization Technology for Directed I/O (VT-d)	1
HDMI ports quantity	1	Intel VT-x with Extended Page	
Ethernet LAN (RJ-45) ports *	3	Tables (EPT)	4
Thunderbolt 3 ports quantity	2	Intel® AES New Instructions (Intel®	1
3.5 mm (1/8-inch) out	4	AES-NI)	
PCI Express x4 (Gen 3.x) slots	1	Intel <sup>®</sup> Clear Video HD Technology (Intel <sup>®</sup> CVT HD)	✓
Microphone in	4	Intel <sup>®</sup> Clear Video Technology for	
Graphics		Mobile Internet Devices (Intel CVT for MID)	4
On-board graphics card base	350 MHz	Intel® Hyper Threading Technology	
frequency		(Intel® HT Technology)	×
On-board graphics card dynamic frequency (max)	1050 MHz	Intel® Identity Protection	4
On-board graphics card ID	0x3E92	Technology (Intel® IPT)	
Maximum on-board graphics card	64 GB	Intel® InTru™ 3D Technology	
memory		Intel® OS Guard Intel® Quick Sync Video Technology	
Number of displays supported (on- board graphics)	3	Intel® Secure Key	·
		Intel® Turbo Boost Technology	2.0
Design	<b>T</b>	Maximum number of PCI Express	16
Chassis type *	Tower Active	lanes	
Cooling type * Product colour	Black	Thermal Monitoring Technologies	
Number of fans	4 fan(s)	Thermal solution specification	PCG 2015A
Fan diameter	12 cm	Memory channels supported by processor	Dual
Fan diameter 2	6 cm	Memory types supported by	DDR4-SDRAM
LED indicators	HDD, LAN, USB	processor	
Built-in display	1	Operational conditions	
Cable lock slot	1	Operating temperature (T-T)	0 - 40 °C
Cable lock slot type	Kensington		

Design		<b>Operational conditions</b>	
Built-in speaker(s) Number of built-in speakers	4	Operating relative humidity (H-H)	5 - 95%
	1	Logistics data	
Performance		Harmonized System (HS) code	84714100
Туре *	NAS	Other features	
		Digital Living Network Alliance (DLNA) certified	√

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.