## QNAP TS-h686 NAS Tower Intel® Xeon® D D-1602 8 GB DDR4 4 TB HDD QuTS hero Black

Brand : QNAP

Product code: TS-H686-D1602-8G/4TB-GOLD

Product name : TS-h686

Intel Xeon D-1602 (2x 2.5GHz), 8GB DDR4, 5GB Flash, 4x 2.5"/3.5" + 2x 2.5", 2x M.2, 4x 2.5G RJ-45, 3x USB 3.2 Gen1

QNAP TS-h686. Type: NAS. Chassis type: Tower. Device class: Home & Home Office. Processor family: Intel® Xeon® D, Processor model: D-1602, Processor frequency: 2.5 GHz. Internal memory: 8 GB, Internal memory type: DDR4. Total installed storage capacity: 4 TB, Installed storage drive type: HDD. Operating system installed: QuTS hero





## Performance Storage 4 TB Storage drive capacity \* Backup function \* Serial ATA II. Serial ATA III Storage drive interface \* Backup features Cloud, iSCSI LUN M.2, Serial ATA II, Serial ATA III Supported storage drive interfaces Buzzer 1 Storage drive sizes supported 2.5,3.5,M.2 Multilingual support 1 Number of M.2 (M & B) slots 2 Noise level 18.6 dB RAID support \* Snapshot **RAID** levels 0, 1, 5, 6, 10, 50, 60, JBOD Management protocols **SNMP 2/3** Online RAID migration Web-based management **Online RAID expansion** 1 256-bit AES, AES, FIPS 140-2, Security algorithms RAID rebuild . HTTPS, SSH, SSL/TLS Access Control List (ACL) Hot-swap drive bays 1 FAT32, HFS+, NTFS, ZFS, exFAT, Reset button Supported file systems ext3, ext4 On/off switch Storage drives installed \* Built-in FTP server Total installed storage capacity \* 4 TB Safari, Chrome, Internet Explorer, Browser supported Number of storage drives installed \* 4 Firefox Number of storage drives supported 6 System log Hot spare 1 Installed storage drive type \* HDD S.M.A.R.T. support 1 Supported storage drive types \* HDD & SSD Share folder CIFS/SMB Bad block scan Universal Plug and Play (UPnP) 1 Disk roaming USB copy function Processor Software Processor manufacturer \* Intel Operating system installed \* OuTS hero Processor family \* Intel® Xeon® D Processor model \* D-1602 Operating system version h5.0.0 2.5 GHz Windows operating systems Processor frequency \* Windows 10, Windows 7, Windows 8 supported 3.2 GHz Processor boost frequency CentOS 7.0, Ubuntu 14.04, Processor cores 2 Linux operating systems supported openSUSE 12.1, openSUSE 12.2 Processor threads 4 Mac OS X 10.10 Yosemite, Mac OS X 3 MR Processor cache 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, CPU configuration (max) 1 Mac OS X 10.14 Mojave, Mac OS X Mac operating systems supported Memory 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Internal memory \* 8 GB Mac OS X 12.0 Monterey, Mac OS X DDR4 Internal memory type 13.0 Ventura

| Memory  |                            | Software  |  |
|---|----------------------------|---|--|
| Maximum RAM supported<br>Memory slots<br>Memory form factor | 128 GB<br>4<br>UDIMM       | Server operating systems supported                          | Windows Server 2008 R2, Windows<br>Server 2012, Windows Server 2012<br>R2, Windows Server 2016, Windows<br>Server 2019 |
| ECC<br>Flash memory   | ✓<br>5000 MB               | Power   |  |
|   | 2000 MB                    | Power supply location                                       | Built-in   |
| Network   |                            | Power supply unit (PSU) capacity                            | 250 W  |
| Ethernet LAN *  | ✓                          | Number of power supply units<br>Power consumption (typical) | 1<br>61.115 W  |
| Ethernet LAN data rates<br>DHCP client                      | 10,100,1000,2500 Mbit/s    | AC input voltage  | 100 - 240 V  |
| DHCP server   |                            | Fan voltage   | 12 V   |
| Jumbo frames support  |                            | Weight & dimensions   |  |
| iSCSI support   |                            | Width *   | 224.9 mm   |
| Wake-on-LAN ready   |                            | Depth *   | 319.8 mm   |
| Dynamic DNS (DDNS)  | -<br>-                     | Height *  | 231.9 mm   |
| Ports & interfaces  |                            | Packaging content   |  |
|   | 1                          | Cables included   | AC, LAN (RJ-45)  |
| USB port *<br>USB 3.2 Gen 1 (3.1 Gen 1) Type-A              |                            | Power cables quantity                                       | 1  |
| ports quantity  | 3                          | Number of screws  | 24   |
| Ethernet LAN (RJ-45) ports *                                | 4                          | Drive tray key included                                     | <b>V</b>   |
| PCI Express x8 (Gen 3.x) slots                              | 2                          | Processor special features                                  |  |
| Design  |                            | Embedded options available                                  | ×  |
| Chassis type *  | Tower                      | Enhanced Intel SpeedStep<br>Technology                      | 1  |
| Cooling type *<br>Product colour                            | Active<br>Black            | Execute Disable Bit   | 1  |
| Number of fans  | 2 fan(s)                   | Idle States   |  |
| Fan diameter  | 9 cm                       | Intel 64  | <b>v</b>   |
| Fan diameter 2  | 9.7 cm                     | Intel QuickAssist Technology                                | ×  |
| LED indicators  | HDD, LAN, SSD, Status, USB | Intel Trusted Execution Technology                          | <i>v</i>   |
| Built-in display  | ×                          | Intel TSX-NI  | 1  |
| Cable lock slot   | 1                          | Intel Virtualization Technology (VT-                        |  |
| Cable lock slot type  | Kensington                 | x)  | •  |
| Performance   |                            | Intel Virtualization Technology for<br>Directed I/O (VT-d)  | ✓  |
| Type *<br>Device class *                                    | NAS<br>Home & Home Office  | Intel VT-x with Extended Page<br>Tables (EPT)               | 1  |
|   |                            | Operational conditions                                      |  |
|   |                            | Operating temperature (T-T)                                 | 0 - 40 °C  |
|   |                            | Operating relative humidity (H-H)                           | 5 - 95%  |

## Storage relative humidity (H-H) Logistics data

Storage temperature (T-T)

Harmonized System (HS) code 84714100

-20 - 70 °C

5 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.