## Brand : QNAP

Product code: TS-H886-D1622-16G/60TB-IW

×

Product name : TS-H886-D1622-16G

- Four 2.5GbE ports accelerate file sharing across teams and devices, virtual machine applications or multimedia transmission

- DDR4 ECC memory detects and corrects single-bit memory errors, demonstrating high reliability for crucial applications

- Two M.2 NVMe Gen 3 x4 SSD slots (each slot providing up to 3.2 GB/s bandwidth) enable SSD caching to boost random read/write performance

- Two PCIe slots allow for 5GbE/10GbE/25GbE/40GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance

- Scalable storage supporting virtual machines, containerized apps, centralized storage, backup, sharing, and disaster recovery

- QuTS hero combines ZFS advantages with the QTS App Center ecosystem to empower your business Xeon D-1622 2.6 GHz, 16 GB DDR4, 5GB, 6x 3.5" + 2x 2.5", 2x M.2, 4x 2.5G LAN, 3x USB 3.2,

231.9x292.9x319.8 mm

Storage		Performance	
Storage Supported storage drive interfaces Storage drive sizes supported Number of M.2 (M & B) slots RAID support * RAID levels Online RAID migration Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity *	Serial ATA II, Serial ATA III 2.5,3.5" 2 ✓ 0, 1, 5, 6, 10, 50, 60 ✓ ✓ FAT32, HFS+, NTFS, ZFS, ext3, ext4 ✓ 60 TB	Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Snapshot Web-based management Security algorithms Access Control List (ACL)	NAS Large Enterprise Business Cloud, iSCSI LUN 20.4 dB 256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Number of storage drives installed * Number of storage drives supported *		Reset button On/off switch Built-in FTP server	1 1 1
Installed storage drive type * Supported storage drive types * Bad block scan Disk roaming	HDD HDD & SSD ✓	Browser supported System log	Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox
Processor		Hot spare S.M.A.R.T. support	
Processor manufacturer * Processor family * Processor model *	Intel Intel® Xeon® D D-1622	Share folder Universal Plug and Play (UPnP) USB copy function	CIFS/SMB
Processor frequency *	2.6 GHz	Software	
Processor boost frequency Processor cores	3.2 GHz 4	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Processor threads Processor cache CPU configuration (max) On-board graphics card model	8 6 MB 1 Not available	Linux operating systems supported Mac operating systems supported	✓ Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X
Memory Internal memory type Maximum RAM supported Memory slots	DDR4 128 GB 4	Server operating systems supported	10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Internal memory *	16 GB	Power	
Memory form factor Flash memory	UDIMM 5000 MB	Power supply location Power supply unit (PSU) capacity	Built-in 250 W
Network		Number of power supply units	1
Ethernet LAN *	4	Power consumption (typical)	75.79 W

Network		Power	
Ethernet LAN data rates DHCP client DHCP server Jumbo frames support Supported network protocols WLAN adapter supported	10,100,1000,2500 Mbit/s	AC input voltage AC input frequency Weight & dimensions Width * Depth * Height *	100 - 240 V 50 - 60 Hz 292.9 mm 319.8 mm 231.9 mm
Ports & interfaces		Weight	8.5 kg
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity 3 Ethernet LAN (RJ-45) ports * 4 PCI Express x8 (Gen 3.x) slots 2	3	Packaging content Cables included Number of screws	AC, LAN (RJ-45) 32
		Processor special features	
Design Chassis type * Cooling type * Product colour Number of fans Fan diameter Fan diameter 2 LED indicators Built-in display Cable lock slot Cable lock slot type	Tower Active Black 3 fan(s) 8 cm 9.7 cm HDD, SSD, Status Kensington	Embedded options available Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel QuickAssist Technology Intel Trusted Execution Technology Intel TSX-NI Intel Virtualization Technology (VT- x) Intel Virtualization Technology for Directed I/O (VT-d) Intel VT-x with Extended Page Tables (EPT)	×    ✓   ✓   ✓   ✓   ✓   ✓   ✓   ✓

Operating temperature (T-T)0 - 35 °COperating relative humidity (H-H)5 - 95%

## Logistics data

Harmonized System (HS) code

84714100

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.