QNAP

QNAP TS-H3087XU-RP NAS Rack (4U) Intel Xeon E E-2378 64 GB DDR4 528 TB QuTS hero Black, White

Brand : QNAP **Product code:** TS-H3087XU-RP-E2378-64G/528TB-

HC



Product name: TS-H3087XU-RP

Intel Xeon E-2378, 64 GB ECC DDR4, 5GB Flash, 24 x 3.5" SATA + 6 x 2.5" SATA, RJ-45, USB 3.2 Gen 2, 4U, 21.78 kg

QNAP TS-H3087XU-RP. Type: NAS. Chassis type: Rack (4U). Device class: Large Enterprise Business. Processor family: Intel Xeon E, Processor model: E-2378, Processor frequency: 2.6 GHz. Internal memory: 64 GB, Internal memory type: DDR4. Total installed storage capacity: 528 TB. Operating system installed: QuTS hero



		D. C	
Storage		Performance	
Storage Storage drive interface * Supported storage drive interfaces Storage drive sizes supported System drive sizes supported RAID support * RAID levels Online RAID expansion RAID rebuild Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type *	Serial ATA Serial ATA 2.5,3.5" 3.5" ✓ 1, 5, 6, 10, 50, 60, JBOD ✓ FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 × 528 TB 30	Backup function * Backup features Multilingual support Number of users Snapshot Management protocols Web-based management Share folder access right management Security algorithms Access Control List (ACL) Reset button On/off switch Built-in FTP server	Cloud, iSCSI LUN 16000 user(s) SMB/CIFS, AFP, NFS HTTPS, SNMPv2, SNMPv3, SSH
Supported storage drive types * Auto-rebuild Disk roaming	HDD & SSD ✓	Browser supported System log	Apple Safari (latest version), Google Chrome (latest version), Microsoft Edge (latest version), Mozilla Firefox (latest version)
Processor		Hot spare	✓
Processor manufacturer * Processor family * Processor model *	Intel Intel Xeon E E-2378	Disk scan S.M.A.R.T. support Share folder	√ √ Thick, Thin
Processor frequency *	2.6 GHz	Software	
Processor boost frequency Processor cores Processor threads Processor cache CPU configuration (max)	4.8 GHz 8 16 16 MB 1	Operating system installed * Operating system version	QuTS hero h5.0.0
Memory			
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor ECC Flash memory	64 GB DDR4 128 GB 4 UDIMM ✓ 5000 MB		
Network			
Ethernet LAN * Ethernet LAN data rates	√ 100,1000,2500 Mbit/s		

Matanada		Coffee	
Network Conner othernet cabling technology	10CDACE T	Software	Windows 10 Windows 10
Copper ethernet cabling technology DHCP server iSCSI support Supported network protocols Dynamic DNS (DDNS)	10GBASE-T ✓ ✓ IPv4, IPv6 ✓		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core,
Ports & interfaces			Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro
USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity Ethernet LAN (RJ-45) ports * Number of SATA III connectors PCI Express x8 (Gen 4.x) slots	4 4 30 1	Windows operating systems supported	x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7
Design			Professional x64, Windows 7 Starter, Windows 7 Starter x64
Chassis type * Cooling type * Product colour Number of fans Fan diameter	Rack (4U) Active Black, White 4 fan(s) 8 cm		Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64 CentOS 7.0, Ubuntu 14.04,
LED indicators	HDD, LAN, Status, USB	Linux operating systems supported	openSUSE 12.1, openSUSE 12.2
Performance Type * Device class *	NAS Large Enterprise Business	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
		Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Other operating systems supported	IBM AIX 7.1, Solaris 10
		Power	
		Power supply location Power supply unit (PSU) capacity	Built-in 800 W 2
		Power supply location Power supply unit (PSU) capacity Number of power supply units	
		Power supply location Power supply unit (PSU) capacity	800 W
		Power supply location Power supply unit (PSU) capacity Number of power supply units Weight & dimensions Width * Depth * Height * Weight	800 W 2 483 mm 630 mm 178 mm 21.8 kg
		Power supply location Power supply unit (PSU) capacity Number of power supply units Weight & dimensions Width * Depth * Height * Weight Package weight	800 W 2 483 mm 630 mm 178 mm 21.8 kg
		Power supply location Power supply unit (PSU) capacity Number of power supply units Weight & dimensions Width * Depth * Height * Weight Package weight Packaging content Cables included Power cables quantity Number of screws	800 W 2 483 mm 630 mm 178 mm 21.8 kg 29.6 kg AC, LAN (RJ-45)
		Power supply location Power supply unit (PSU) capacity Number of power supply units Weight & dimensions Width * Depth * Height * Weight Package weight Packaging content Cables included Power cables quantity	800 W 2 483 mm 630 mm 178 mm 21.8 kg 29.6 kg AC, LAN (RJ-45)

Operating temperature (T-T)

0 - 40 °C

Operational conditions

Operating relative humidity (H-H) \$5 - 95% Storage temperature (T-T) \$-20 - $70\ ^{\circ}\text{C}$

