

## QNAP TS-H686-D1602-8G NAS Tower Ethernet LAN Black D-1602





**Brand**: QNAP Product code: TS-H686-D1602-8G/32TB-IW

Product name: TS-H686-D1602-8G

- Four 2.5GbE ports accelerate file sharing across teams and devices, virtual machine applications or multimedia transmission
- DDR4 ECC memory detects and corrects single-bit memory errors, demonstrating high reliability for crucial applications
- Two M.2 NVMe Gen 3 x4 SSD slots (each slot providing up to 3.2 GB/s bandwidth) enable SSD caching to boost random read/write performance
- Two PCle slots allow for 5GbE/10GbE/25GbE/40GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance
- Scalable storage supporting virtual machines, containerized apps, centralized storage, backup, sharing, and disaster recovery
- QuTS hero combines ZFS advantages with the QTS App Center ecosystem to empower your business Xeon D-1602 2.5 GHz, 8 GB DDR4, 5GB, 4x 3.5" + 2x 2.5", 2x M.2, 4x 2.5G LAN, 3x USB 3.2, 231.9x224.9x319.8 mm

Storage		Performance	
-	Codel ATA III Codel ATA III		Ch. d. SCCLLIN
Supported storage drive interfaces		Backup features	Cloud, iSCSI LUN
Storage drive sizes supported  Number of M.2 (M & B) slots	2.5,3.5" 2	Buzzer Multilingual support	1
, ,	∠ ✓	•	<b>√</b> 18.6 dB
RAID support * RAID levels	0, 1, 5, 6, 10, 50, 60	Noise level Snapshot	10.0 UB  ✓
Online RAID migration	0, 1, 5, 0, 10, 50, 60 ✓	•	*
Online RAID inigration  Online RAID expansion	4	Web-based management	256-bit AES, AES, FIPS 140-2,
RAID rebuild	<b>V</b>	Security algorithms	HTTPS, SSH, SSL/TLS
Hot-swap drive bays	1	Access Control List (ACL)	<b>✓</b>
Supported file systems	FAT32, HFS+, NTFS, ZFS, ext3, ext4	Reset button	✓
Storage drives installed *	✓	On/off switch	✓
Total installed storage capacity *	32 TB	Built-in FTP server	✓
Number of storage drives supported *	6	Browser supported	Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox
Installed storage drive type *	HDD	System log	✓
Supported storage drive types *	HDD & SSD	Hot spare	✓
Bad block scan	<b>V</b>	S.M.A.R.T. support	✓
Disk roaming	1	Share folder	CIFS/SMB
Processor		Universal Plug and Play (UPnP)	✓
Processor manufacturer *	Intel	USB copy function	✓
Processor family *	Intel® Xeon® D	Software	
Processor model *	D-1602	Operating system version	4.5.0
Processor frequency *	2.5 GHz	Windows operating systems	
Processor boost frequency	3.2 GHz	supported	Windows 10, Windows 7, Windows 8
Processor cores	2	Linux operating systems supported	✓
Processor threads	4		Mac OS X 10.10 Yosemite, Mac OS X $$
Processor cache	3 MB	Mac operating systems supported	10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra,
CPU configuration (max)	1	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X
Memory			10.15 Catalina
Internal memory type	DDR4		Windows Server 2008 R2, Windows
Maximum RAM supported	128 GB	Server operating systems supported	Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
Memory slots	4		Server 2019
Internal memory *	8 GB	Power	
Memory form factor	UDIMM		Duilt in
Flash memory	5000 MB	Power supply location	Built-in
Network		Power supply unit (PSU) capacity  Number of power supply units	250 W 1
Ethernet LAN *	1	Power consumption (typical)	61.115 W
Ethernet LAN data rates	100,1000,2500 Mbit/s	AC input voltage	100 - 240 V
DHCP client	100,1000,2500 MBIUS  ✓	AC input frequency	50 - 60 Hz
Direct Circuit	•	Ac input inequency	30 00 HZ

Network		Weight & dimensions	
DHCP server Jumbo frames support Supported network protocols WLAN adapter supported	✓ ✓ TCP/IP, HTTP/HTTPS ✓	Width * Depth * Height * Weight	224.9 mm 319.8 mm 231.9 mm 7.27 kg
Ports & interfaces		Packaging content	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	4	Cables included Number of screws	AC, LAN (RJ-45) 30
ports quantity Ethernet LAN (RJ-45) ports *	4	Processor special features	
PCI Express x8 (Gen 3.x) slots	2	Embedded options available	×
Design		Enhanced Intel SpeedStep Technology	✓
Chassis type *	Tower	Execute Disable Bit	✓
Cooling type *	Active	Idle States	✓
Product colour	Black	Intel 64	✓
Number of fans	2 fan(s)	Intel QuickAssist Technology	×
Fan diameter	8 cm	Intel Trusted Execution Technology	✓
Fan diameter 2	9.7 cm	Intel TSX-NI	✓
LED indicators Cable lock slot	HDD, SSD, Status ✓	Intel Virtualization Technology (VT-x)	✓
Cable lock slot type	Kensington	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Performance		Intel VT-x with Extended Page	1
Type *	NAS	Tables (EPT)	•
Device class *	Large Enterprise Business	Operational conditions	
Backup function *	<b>√</b>	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 35 °C 5 - 95%
		, , ,	
		Logistics data	
		Harmonized System (HS) code	84714100

