

CyberPower CP900EPFCLCD-UK uninterruptible power supply (UPS) Line-Interactive 0.9 kVA 540 W 6 AC outlet(s)

Brand : CyberPower

Product code: CP900EPFCLCD-UK

Product name : CP900EPFCLCD-UK

Nominal 230 V, 10 A, Cord 1.83 m, 100 x 275 x 230 mm, 6.6 kg, 0 - 40°C

CyberPower CP900EPFCLCD-UK. UPS topology: Line-Interactive, Output power capacity: 0.9 kVA, Output power: 540 W. AC outlet types: C13 coupler, Type G (BS 1363), Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 230 V, Typical backup time at full load: 1 min. Form factor: Tower, Product colour: Black, Housing material: Plastic. Compliance certificates: RoHS, Certification: CE, EAC, RCM



Features		Battery	
UPS topology *	Line-Interactive	Number of batteries supported	1
Output power capacity *	0.9 kVA	Typical backup time at full load	1 min
Output power *	540 W	Typical backup time at half load	7 min
Waveform *	Sine	Battery recharge time	8 h
Input operation voltage (min) *	170 V	Design	
Input operation voltage (max) *	270 V	Form factor *	Tower
Input frequency *	50/60 Hz	Housing material	Plastic
Output frequency	50/60 Hz	Cable length	1.83 m
Automatic Voltage Regulation (AVR)	✓	Product colour *	Black
Maximum current	10 A	Display type	LCD
Surge energy rating	405 J	LED indicators	Power
Output voltage Total Harmonic Distortion (THD)	10%	Operational conditions	
EMI/RFI noise filtering	✓	Operating temperature (T-T)	0 - 40 °C
Surge protection	✓	Operating relative humidity (H-H)	0 - 95%
Surge protection features	Fax, Modem, Network, Telephone	Operating altitude	0 - 300 m
Power protection features	Over current	Certificates	
Audible alarm(s)	✓	Compliance certificates	RoHS
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Certification	CE, EAC, RCM
Auto-restart	✓	Weight & dimensions	
Ports & interfaces		Width	100 mm
AC outlet types	C13 coupler, Type G (BS 1363)	Depth	275 mm
Power plug	C14 coupler	Height	230 mm
AC outlets quantity	6 AC outlet(s)	Weight	6.6 kg
USB 2.0 ports quantity	1	Packaging data	
Modem (RJ-11) ports	2	Package width	195 mm
Battery		Package depth	365 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	335 mm
Battery voltage	230 V	Package weight	7.8 kg
		Other features	
		Suitable for use in country/location	United Kingdom



4712364146244

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.