QNAP

Product name: QSW-M2106PR-2S2T

QNAP QSW-M2106PR-2S2T network switch Managed L2 10G Ethernet (100/1000/10000) Power over Ethernet (PoE) 1U Black

Brand : QNAP Product code: QSW-M2106PR-2S2T

....


DITTO ONNE

Half-width Rackmount 10GbE and 2.5GbE PoE++ Layer 2 Web Managed Switch for New-generation Wi-Fi Deployment

QNAP QSW-M2106PR-2S2T. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 2, Installed SFP+ modules quantity: 2, Console port: RJ-45. MAC address table: 16000 entries, Switching capacity: 110 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af,.... Power over Ethernet (PoE). Rack mounting, Form factor: 1U



Management features		Design	
Switch type *	Managed	Number of fans	2 fan(s)
Switch layer	L2	Electromagnetic compatibility	CLASS A
Ports & interfaces		Certification	CE, FCC, VCCI, BSMI
Basic switching RJ-45 Ethernet ports quantity *	2	Power	40
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Power source * Power supply included *	AC ✓
2.5G Ethernet (copper) ports quantity	6	AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz
Installed SFP+ modules quantity *	2	Power consumption (max)	350 W
Console port	RJ-45	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✓
	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad,	Power over Ethernet 4PPoE (PoE++) ports quantity	8
Networking standards *	IEEE 802.3ae, IEEE 802.3af, IEEE 802.3an, IEEE 802.3at, IEEE	Total Power over Ethernet (PoE) budget	310 W
	802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Operational conditions	
Data transmission		Operating temperature (T-T)	0 - 40 °C
Switching capacity *	110 Gbit/s	Operating relative humidity (H-H)	5 - 95%
Throughput	55 Gbit/s	Weight & dimensions	
MAC address table *	16000 entries	Width	207 mm
Jumbo frames support	✓	Depth	248.8 mm
Design		Height	43.3 mm
Rack mounting *	1	Weight	1.77 kg
Stackable *	1	Packaging data	
Form factor	1U	Package weight	2.54 kg
Product colour	Black	- 5	-
Reset button	1		
LED indicators	Activity, Fan, Link, PoE, Speed, Status		



4711103082805

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.