CyberPower OLS1500ERT2U uninterruptible power supply (UPS) Double-conversion (Online) 1.5 kVA 1200 W 6 AC outlet(s)

Brand : CyberPower Product code: OLS1500ERT2U

Product name: OLS1500ERT2U



Online (Double Conversion), 1500VA, 1200W, 1 x IEC C14 In, 6 x IEC C13 Out, RJ11/RJ45, 2U CyberPower OLS1500ERT2U. UPS topology: Double-conversion (Online), Output power capacity: $1.5\,$ kVA, Output power: $1200\,$ W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: $6\,$ AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: $8.5\,$ Ah, Battery voltage: $12\,$ V. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: $20.\,$ Width: $438\,$ mm, Depth: $430\,$ mm, Height: $88\,$ mm



	Ports & interfaces	
Double-conversion (Online)	Ethernet LAN (RJ-45) ports	2
1.5 kVA 1200 W Sine 40/70 Hz 208 V nax) 240 V 95% Inic 3% Fax, Modem, Network, Telephone Overload Battery replacement	Battery	
	Battery technology Battery capacity Battery voltage Number of batteries supported Typical backup time at full load Typical backup time at half load Battery recharge time Automatic battery test	Sealed Lead Acid (VRLA) 8.5 Ah 12 V 3 5 min 14 min 5 h
	Design Form factor * Rack capacity Cooling type Product colour * Display type	Rackmount/Tower 2U Active Black LCD
C12 coupler	LED indicators	Battery replacement
AC outlet types Power plug C14 coupler AC outlets quantity G AC outlet(s) USB 2.0 ports quantity Serial ports quantity Modem (RJ-11) ports 2	Width Depth Height Weight Packaging data	438 mm 430 mm 88 mm 14.6 kg
	1.5 kVA 1200 W Sine 40/70 Hz 208 V 240 V 95% Fax, Modem, Network, Telephone Overload Battery replacement C13 coupler C14 coupler 6 AC outlet(s) 1	1.5 kVA 1200 W Sine 40/70 Hz 208 V 240 V 95% V Typical backup time at full load Typical backup time at half load Battery recharge time Automatic battery test Cold start V Design Fax, Modem, Network, Telephone Overload V Battery replacement V Cooling type Battery replacement V Display type LED indicators Weight & dimensions C14 coupler Automatic battery test Cold start Form factor * Rack capacity Cooling type V Display type LED indicators Weight & dimensions Height Height Weight



4712856270358

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.