
## QNAP

## QNAP TS-H1887XU-RP NAS Rack (2U) Intel Xeon E E-2336 32 GB DDR4 168 TB QuTS hero Black, White

**Brand**: QNAP Product code: TS-H1887XU-RP-E2336-32G/168TB-

Product name: TS-H1887XU-RP

Copper ethernet cabling technology 10GBASE-T







| Storage                            |   | Performance                          |   |
|------------------------------------|---|--------------------------------------|---|
| Storage drive interface *          | Serial ATA                                | Type *                               | NAS   |
| Supported storage drive interfaces | Serial ATA                                | Device class *                       | Large Enterprise Business   |
| Storage drive sizes supported      | 2.5,3.5"                                  | Backup function *                    | ✓   |
| System drive sizes supported       | 3.5"                                      | Backup features                      | Cloud, iSCSI LUN  |
| RAID support *                     | ✓   | Number of users                      | 16000 user(s)   |
| RAID levels                        | 1, 5, 6, 10, 50, 60, JBOD                 | Snapshot                             | 1   |
| Online RAID expansion              | ✓   | Management protocols                 | SMB/CIFS, AFP, NFS  |
| RAID rebuild                       | ✓   | Web-based management                 | 1   |
| Supported file systems             | FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 | Share folder access right management | ✓   |
| Storage drives installed *         | ×   | Security algorithms                  | HTTPS, SNMPv2, SNMPv3, SSH  |
| Total installed storage capacity * | 168 TB                                    | Access Control List (ACL)            | ✓   |
| Number of storage drives supported | 18  | Reset button                         | ✓   |
| *                                  |   | On/off switch                        | ✓   |
| Installed storage drive type *     | X   | Built-in FTP server                  | ✓   |
| Supported storage drive types *    | HDD & SSD                                 |                                      | Apple Safari (latest version), Google                                     |
| Disk roaming  Processor            | <b>✓</b>                                  | Browser supported                    | Chrome (latest version), Microsoft Edge (latest version), Mozilla Firefox |
| Processor manufacturer *           | Intel                                     | System log                           | (latest version) ✓  |
| Processor family *                 | Intel Xeon E                              | System log<br>Hot spare              | Ž   |
| Processor model *                  | E-2336                                    | Disk scan                            | 1   |
| Processor frequency *              | 2.9 GHz                                   | S.M.A.R.T. support                   | ,   |
| Processor boost frequency          | 4.8 GHz                                   | Share folder                         | Thick, Thin   |
| Processor cores                    | 6   |                                      | THER, THIII   |
| Processor threads                  | 12  | Software                             |   |
| Processor cache                    | 12 MB                                     | Operating system installed *         | QuTS hero   |
| CPU configuration (max)            | 1   | Operating system version             | h5.0.0  |
| Memory                             |   |                                      |   |
| •                                  | 22 CB                                     |                                      |   |
| Internal memory *                  | 32 GB<br>DDR4                             |                                      |   |
| Internal memory type               | 128 GB                                    |                                      |   |
| Maximum RAM supported              | 128 GB<br>4                               |                                      |   |
| Memory slots Memory form factor    | 4<br>UDIMM                                |                                      |   |
| ECC                                | UDIIMIMI<br>✓                             |                                      |   |
| Flash memory                       | 5000 MB                                   |                                      |   |
| Network                            | 3333 1115                                 |                                      |   |
| Ethernet LAN *                     | 1   |                                      |   |
| Ethernet LAN data rates            | 100,1000,2500 Mbit/s                      |                                      |   |
| Ethernet LAN udta rates            | 100,1000,2300 MDICS                       |                                      |   |

| Notwork  |   | Software  |   |
|--|---|---|---|
| Network  DHCD conver   | ,   | Software  | Windows 10 Windows 10   |
| DHCP server iSCSI support Supported network protocols Dynamic DNS (DDNS)   | √<br>IPv4, IPv6<br>✓  |   | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10   |
| Ports & interfaces   |   |   | Home x64, Windows 10 IOT Core,<br>Windows 10 IoT Enterprise,  |
| USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity Ethernet LAN (RJ-45) ports * Number of SATA III connectors PCI Express x8 (Gen 4.x) slots | 4<br>4<br>18  | Windows operating systems supported   | Windows 10 Pro, Windows 10 Pro<br>x64, Windows 10 x64, Windows 11,<br>Windows 11 x64, Windows 7,<br>Windows 7 Enterprise, Windows 7<br>Enterprise x64, Windows 7 Home<br>Basic, Windows 7 Home Basic x64,<br>Windows 7 Home Premium,<br>Windows 7 Home Premium x64, |
| Design   |   |   | Windows 7 Professional, Windows 7   |
| Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators  | Rack (2U) Active Black, White 4 fan(s) 6 cm HDD, LAN, Status, USB |   | Professional x64, Windows 7<br>Starter, Windows 7 Starter x64,<br>Windows 7 Ultimate, Windows 7<br>Ultimate x64, Windows 7 x64,<br>Windows 8, Windows 8 Enterprise,<br>Windows 8 Enterprise x64, Windows<br>8 Pro, Windows 8 Pro x64, Windows<br>8 x64              |
|  | TIDD, LAIN, Status, OSD   | Linux operating systems supported   | CentOS 7.0, Ubuntu 14.04, openSUSE 12.1, openSUSE 12.2  |
|  |   | Mac operating systems supported   | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura              |
|  |   | Server operating systems supported  | Windows Server 2008 R2, Windows<br>Server 2012, Windows Server 2012<br>R2, Windows Server 2016, Windows<br>Server 2019  |
|  |   | Other operating systems supported   | IBM AIX 7.1, Solaris 10   |
|  |   | Power   |   |
|  |   | Power supply location Power supply unit (PSU) capacity Number of power supply units | Built-in<br>550 W<br>2  |
|  |   | Weight & dimensions   | _   |
|  |   | Width *   | 483 mm  |
|  |   | Depth *   | 630 mm  |
|  |   | Height *  | 88 mm   |
|  |   | Weight  | 13 kg   |
|  |   | Package weight  | 19 kg   |
|  |   | Processor special features  |   |
|  |   | Embedded options available<br>Enhanced Intel SpeedStep<br>Technology                | <b>x</b><br>✓   |
|  |   | Execute Disable Bit   | ✓   |
|  |   | Idle States   | ✓   |
|  |   | Intel 64  | <b>√</b>  |
|  |   | Intel Trusted Execution Technology<br>Intel Virtualization Technology (VT-x)        | 1   |
|  |   | Intel Virtualization Technology for<br>Directed I/O (VT-d)                          | ✓   |
|  |   | Intel VT-x with Extended Page<br>Tables (EPT)                                       | ✓   |
|  |   | Operational conditions  |   |
|  |   | Operating temperature (T-T)   | 0 - 40 °C   |
|  |   | Operating relative humidity (H-H) Storage temperature (T-T)                         | 5 - 95%<br>-20 - 70 °C  |

