QNAP

QNAP TS-H1887XU-RP NAS Rack (2U) Intel Xeon E E-2336 32 GB DDR4 240 TB QuTS hero Black, White

Brand : QNAP **Product code:** TS-H1887XU-RP-E2336-32G/240TB-

HC



Product name: TS-H1887XU-RP

Copper ethernet cabling technology 10GBASE-T

Intel Xeon E-2336, 32 GB ECC DDR4, 5GB Flash, 12 x 3.5" + 6 x 2.5", RJ-45, USB 3.2 Gen 2, 2U, 13 kg QNAP TS-H1887XU-RP. Type: NAS. Chassis type: Rack (2U). Device class: Large Enterprise Business. Processor family: Intel Xeon E, Processor model: E-2336, Processor frequency: 2.9 GHz. Internal memory: 32 GB, Internal memory type: DDR4. Total installed storage capacity: 240 TB. Operating system installed: QuTS hero



Storage		Performance	
Storage drive interface *	Serial ATA	Type *	NAS
Supported storage drive interfaces	Serial ATA	Device class *	Large Enterprise Business
Storage drive sizes supported	2.5,3.5"	Backup function *	✓
System drive sizes supported	3.5"	Backup features	Cloud, iSCSI LUN
RAID support *	1	Number of users	16000 user(s)
RAID levels	1, 5, 6, 10, 50, 60, JBOD	Snapshot	1
Online RAID expansion	1	Management protocols	SMB/CIFS, AFP, NFS
RAID rebuild	1	Web-based management	1
Supported file systems	FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4	Share folder access right management	✓
Storage drives installed *	×	Security algorithms	HTTPS, SNMPv2, SNMPv3, SSH
Total installed storage capacity *	240 TB	Access Control List (ACL)	✓
Number of storage drives supported	18	Reset button	✓
*		On/off switch	✓
Installed storage drive type *	×	Built-in FTP server	1
Supported storage drive types *	HDD & SSD		Apple Safari (latest version), Google
Disk roaming	✓	Browser supported	Chrome (latest version), Microsoft Edge (latest version), Mozilla Firefox
Processor			(latest version)
Processor manufacturer *	Intel	System log	✓
Processor family *	Intel Xeon E	Hot spare	✓
Processor model *	E-2336	Disk scan	✓
Processor frequency *	2.9 GHz	S.M.A.R.T. support	✓
Processor boost frequency	4.8 GHz	Share folder	Thick, Thin
Processor cores	6	Software	
Processor threads	12	Operating system installed *	OuTS hero
Processor cache	12 MB	Operating system version	h5.0.0
CPU configuration (max)	1	operating system version	113.0.0
Memory			
Internal memory *	32 GB		
Internal memory type	DDR4		
Maximum RAM supported	128 GB		
Memory slots	4		
Memory form factor	UDIMM		
ECC	✓		
Flash memory	FOOO MD		
	5000 MB		
Network	2000 MB		
Network Ethernet LAN *	√ 2000 MB		

Notwork		Software	
Network DHCD conver	,	Software	Windows 10 Windows 10
DHCP server iSCSI support Supported network protocols Dynamic DNS (DDNS)	√ IPv4, IPv6 ✓		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10
Ports & interfaces			Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise,
USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity Ethernet LAN (RJ-45) ports * Number of SATA III connectors PCI Express x8 (Gen 4.x) slots	4 4 18	Windows 10 Pro, Windows 10 F x64, Windows 10 x64, Windows Windows 11 x64, Windows 7, Windows 7 Enterprise, Window Vindows operating systems upported Enterprise x64, Windows 7 Home Basic Windows 7 Home Premium, Windows 7 Home Premium x64	Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64,
Design			Windows 7 Professional, Windows 7
Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators	Rack (2U) Active Black, White 4 fan(s) 6 cm HDD, LAN, Status, USB		Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64
	,,	Linux operating systems supported	CentOS 7.0, Ubuntu 14.04, openSUSE 12.1, openSUSE 12.2
		Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
		Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Other operating systems supported	IBM AIX 7.1, Solaris 10
		Power	
		Power supply location Power supply unit (PSU) capacity Number of power supply units	Built-in 550 W 2
		Weight & dimensions	_
		Width *	483 mm
		Depth *	630 mm
		Height *	88 mm
		Weight	13 kg
		Package weight	19 kg
		Processor special features	
		Embedded options available Enhanced Intel SpeedStep Technology	x ✓
		Execute Disable Bit	✓
		Idle States	✓
		Intel 64	√
		Intel Trusted Execution Technology Intel Virtualization Technology (VT-x)	1
		Intel Virtualization Technology for Directed I/O (VT-d)	✓
		Intel VT-x with Extended Page Tables (EPT)	✓
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H) Storage temperature (T-T)	5 - 95% -20 - 70 °C

