QNAP TVS-672X-I3-8G/60TB-EXOS NAS/storage server Tower Ethernet LAN Black i3-8100T

Brand : QNAP

Product code: TVS-672X-I3-8G/60TB-EXOS

Product name : TVS-672X-I3-8G/60TB-EXOS

- 5-speed 10GBASE-T RJ45 connectivity accelerates virtualization, intensive file access, large

backup/restoration tasks, and media transfer

- Dual M.2 PCIe Gen 3 x2 NVMe SSD slots enable cache acceleration or SSD storage pools for improved performance

- PCle expansion allows for 2.5/5/10/25GbE network cards, QM2 card, QXP storage expansion cards, or graphics cards

- 4K media playback and real-time transcoding; display multimedia content saved on the NAS via HDMI 2.0 (4K @60Hz) output

- Host multiple virtual machines and containers to run a wide range of applications and services

- A business-class backup center supporting backup/restore of cloud data and VMs (including Google™ Workspace, Microsoft 365®, VMware® and Hyper-V)

Intel Core i3-8100T (4x 3.1GHz), Intel UHD Graphics 630, 8GB DDR4, 5GB Flash, 6x 2.5"/3.5" SATA, 2x M.2, LAN, HDMI, USB, LCD

| Storage | | Performance | |
|---|--|---|---|
| Storage drive interface * Supported storage drive interfaces Storage drive sizes supported Number of M.2 (M & B) slots RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive types * | | Device class * Backup function * Backup features Buzzer Multilingual support Number of users Noise level Third-party support Snapshot Web-based management Share folder access right management Security algorithms Access Control List (ACL) Reset button On/off switch Built-in BitTorrent client | Small & Medium Business Cloud, USB drive, iSCSI LUN 4096 user(s) 23.8 dB 256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH, SSL/TLS, TLS 4 |
| Bad block scan | ✓ | Built-in UPnP AV media server Built-in FTP server | 4 |
| Disk roaming Processor | ✓ | Browser supported | Mozilla Firefox, Microsoft Edge, Google Chrome, Apple Safari |
| Processor manufacturer * Processor generation Processor family * Processor model * Processor frequency * Processor cores Processor threads | Intel 8th gen Intel® Core™ i3 Intel® Core™ i3 i3-8100T 3.1 GHz 4 4 | System log Hot spare Password authentication Disk scan S.M.A.R.T. support Remotely operated USB copy function | Google Chrome, Apple Salari |
| Bus type | DMI3 | Software | |
| Configurable TDP-down frequency CPU configuration (max) Number of processors supported On-board graphics card model | 2.4 GHz 1 1 Intel® UHD Graphics 630 | Operating system installed * Operating system version Windows operating systems supported | QNAP Turbo System 4.5.1 Windows 10, Windows 7, Windows 8 |
| Memory | | Linux operating systems supported | < |
| Internal memory type Maximum RAM supported Memory slots Internal memory * | DDR4 64 GB 2 8 GB | Mac operating systems supported Server operating systems supported | Vindows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 |

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date



××

| Memory | | Power | |
|---|---------------------------------|---|---------------------|
| Memory form factor | SO-DIMM | Power supply location | Built-in |
| Flash memory | 5000 MB | Power supply unit (PSU) capacity | 250 W |
| Network | | Number of power supply units | 1 |
| Ethernet LAN * | 4 | Power consumption (typical) | 45.6 W |
| Ethernet LAN data rates | 100,1000,2500,5000,10000 Mbit/s | Power consumption (HDD standby) | 26.52 W |
| Ethernet LAN data rate supported (max) | 10000 Mbit/s | AC input voltage Fan voltage | 100 - 240 V 12 V |
| DHCP client | < | Weight & dimensions | |
| DHCP server | ✓ | Width * | 264.3 mm |
| Jumbo frames support | ✓ | Depth * | 279.6 mm |
| iSCSI support | ✓ | Height * | 188.2 mm |
| Wake-on-LAN ready | ✓ | Packaging content | |
| Link aggregation | ✓ | | |
| Load balancing system | 4 | Cables included | AC, LAN (RJ-45) |
| Dynamic DNS (DDNS) | V | Power cables quantity | 1 |
| WLAN adapter supported | × | Processor special features | |
| Ports & interfaces | | Embedded options available | ✓ |
| USB port * | 4 | Enhanced Intel SpeedStep Technology | ✓ |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 1 | Execute Disable Bit | ✓ |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A | 2 | Idle States | 4 |
| ports quantity | - | Intel 64 | |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity | 2 | Intel Clear Video Technology | 4 |
| HDMI ports quantity | 1 | Intel Enhanced Halt State Intel Identity Protection Technology | ý. |
| HDMI version | 2.0 | version | 1.00 |
| Ethernet LAN (RJ-45) ports * | 3 | Intel Secure Key Technology version | 1.00 |
| PCI Express x4 (Gen 3.x) slots | 1 | Intel Stable Image Platform Program (SIPP) | × |
| Design | | Intel Stable Image Platform Program | 0.00 |
| Chassis type * | Tower | (SIPP) version | |
| Cooling type * | Active | Intel Trusted Execution Technology | × |
| Product colour | Black | Intel TSX-NI | × |
| Number of fans | 3 fan(s) | Intel TSX-NI version | 0.00 |
| Fan diameter | 12 cm | Intel Virtualization Technology (VT- x) | 1 |
| Fan diameter 2 Drive bay locking | 6 cm | Intel Virtualization Technology for | , |
| LED indicators | × | Directed I/O (VT-d) | ✓ |
| Built-in display | · | Intel VT-x with Extended Page | 1 |
| Display type | LCD | Tables (EPT) | |
| Cable lock slot | ✓ | Operational conditions | |
| Cable lock slot type | Kensington | Operating temperature (T-T) | 0 - 40 °C |
| Performance | - | Operating relative humidity (H-H) | 5 - 95% |
| | NAC | Storage temperature (T-T) | -20 - 70 °C |
| Type * | NAS | Storage relative humidity (H-H) | 5 - 95% |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.