

QNAP TS-H886-D1622-16G NAS Tower Ethernet LAN Black D-1622





Brand: QNAP Product code: TS-H886-D1622-16G/72TB-**REDPRO**

Product name: TS-H886-D1622-16G

- Four 2.5GbE ports accelerate file sharing across teams and devices, virtual machine applications or multimedia transmission
- DDR4 ECC memory detects and corrects single-bit memory errors, demonstrating high reliability for crucial applications
- Two M.2 NVMe Gen 3 x4 SSD slots (each slot providing up to 3.2 GB/s bandwidth) enable SSD caching to boost random read/write performance
- Two PCIe slots allow for 5GbE/10GbE/25GbE/40GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance
- Scalable storage supporting virtual machines, containerized apps, centralized storage, backup, sharing, and disaster recovery
- QuTS hero combines ZFS advantages with the QTS App Center ecosystem to empower your business Xeon D-1622 2.6 GHz, 16 GB DDR4, 5GB, 6x 3.5" + 2x 2.5", 2x M.2, 4x 2.5G LAN, 3x USB 3.2, 231.9x292.9x319.8 mm

CPU configuration (max) 1 On-board graphics card model Not available Mac operating systems supported On-board graphics card model Not available Mac operating systems supported Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Uniternal memory type DDR4 Maximum RAM supported 128 GB Server operating systems supported Nemory slots 4 Server operating systems supported Nemory form factor UDIMM Server 2019 Power Supply location Built-in	Storage		Performance	
Number of M.2 (M & B) slots 2 Backup features Cloud, ISCSI LUN RAID support * * Backup features Cloud, ISCSI LUN RAID levels 0, 1, 5, 6, 10, 50, 60 Buzzer * Online RAID migration * Multilingual support * Online RAID expansion * Noise level 20.4 dB RAID rebuild * Snapshot * Hot-swap drive bays * Web-based management * Supported file systems FAT32, HFS+, NTFS, ZFS, ext3, ext4 Scurity algorithms * 256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS Storage drives installed * * Reset button *	Supported storage drive interfaces	Serial ATA II, Serial ATA III	Type *	NAS
RAID support * Cloud, ISCSI LUN RAID levels 0, 1, 5, 6, 10, 50, 60 Buzzer Cloud, ISCSI LUN Online RAID migration 4 Multilingual support 4 Online RAID expansion 4 Noise level 20.4 dB RAID rebuild 4 Snapshot 4 Hot-swap drive bays FAT32, HF5+, NTFS, ZF5, ext3, ext4 Web-based management 256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS Storage drives installed * 7 Y2 TB Access Control List (ACL) 4 Number of storage drives installed * 6 Reset button 4 Number of storage drives supported * BDD Apple Safari 7+, Google Chrome, Microst Interent Explorer 10+, Mozilla Firefox Supported storage drive type * HDD Brower supported Apple Safari 7+, Google Chrome, Microst Interent Explorer 10+, Mozilla Firefox Supported Storage drive type * HDD & SSD System log 4 Processor Intel® Xeon® D Universal Plug and Play (UPnP) 4 Processor family * Intel® Xeon® D Universal Plug and Play (UPnP) 4 Processor frequency * 2.6 GH	Storage drive sizes supported	2.5,3.5"	Device class *	Large Enterprise Business
RAID levels	Number of M.2 (M & B) slots	2	Backup function *	✓
Online RAID migration V Multilingual support Z Online RAID expansion V Noise level 20.4 dB RAID rebuild V Snapshot V Hot-swap drive bays Web-based management V Supported file systems FAT32, HFS+, NTFS, ZFS, ext3, ext2 Security algorithms 256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS Total installed storage apacity** 72 TB Access Control List (ACL) V Number of storage drives installed * 6 Maccess Control List (ACL) V Number of storage drives supported for storage drive supported storage drive type * HDD Reset button V Installed storage adrive type * HDD & Browser supported Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox Supported storage drive types * HDD & SSD System log V Bad block scan V System log V Disk roaming V System log V Processor Intel MED & Xeon® D Universal Plug and Play (UPnP) V Processor frequency 10.1622 Software Processor frequency 2.6 GHz Software Processor threads 8 Windows operating systems supported V Processor cache	RAID support *	✓	Backup features	Cloud, iSCSI LUN
Online RAID expansion AID rebuild AID rebu	RAID levels	0, 1, 5, 6, 10, 50, 60	Buzzer	✓
RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed Y Total installed storage capacity Number of storage drives installed HDD Sapported storage drives installed HDD Sapported storage drives supported HDD SSD Bab block scan Disk roaming HDD SSD Bab block scan Disk roaming Hotel Rocessor Frocessor Frocessor family Processor family Processor family Processor frequency Frocessor frequency Frocessor frequency Frocessor crose A Reset button A Reset button On/off switch Browser supported Browser supported Microsoft internet Explorer 10+, Mozilla Firefox Mozilla	Online RAID migration	✓	Multilingual support	✓
Hot-swap drive bays	Online RAID expansion	✓	Noise level	20.4 dB
Supported file systems FAT32, HFS+, NTFS, ZFS, ext3, ext4 Storage drives installed V	RAID rebuild	✓	Snapshot	✓
Storage drives installed *	Hot-swap drive bays	✓	Web-based management	✓
Total installed storage capacity* 72 TB Access Control List (ACL) Number of storage drives installed * 6	• • • • • • • • • • • • • • • • • • • •		Security algorithms	
Number of storage drives installed * 6 Number of storage drives supported 6 Number of storage drive type * HDD Installed storage drive type * HDD & SSD Browser supported Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox Bad block scan Disk roaming Processor Processor Processor Intel Number of storage drive type * HDD & SSD Browser supported System log Hot spare Y Hot spare Y Name of System log Windows of Play (UPnP) Windows operating systems Supported Y Name of System supported Y Name of System supported Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sirra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Name of System supported Naximum RAM supported N	=	•	Access Control List (ACL)	✓
Number of storage drives supported * HDD Installed storage drive type * HDD & SSD Supported storage drive types * HDD & SSD Browser supported * Microsoft Internet Explorer 10+, Mozilla Firefox * Moz			Reset button	✓
Installed storage drive type * HDD			On/off switch	✓
Supported storage drive types* HDD & SSD Bad block scan Disk roaming Processor Processor Intel Intel Share folder Share folder Universal Plug and Play (UPnP) Processor manufacturer* Intel Share folder Universal Plug and Play (UPnP) Processor frequency* Processor frequency* Processor threads Processor threads Processor cache CPU configuration (max) On-board graphics card model Not available Memory Internal memory type Memory Memory Memory Memory Memory Internal memory * Internal memory * Memory Memory Memory Memory Internal memory * Memory Memory Internal memory * Memory Internal memory * Internal memory * Internal memory * Memory Memory Internal memory * Interna	*	6	Built-in FTP server	✓
Disk roaming Processor Processor Processor manufacturer* Intel Processor family* Processor frequency* Processor frequency* Processor trequency Processor trequency Processor cores Processor threads Processor cache Processor threads Processor threads Processor threads Processor cache Processor damperit contains and the processor cache Processor cache Processor cache Processor threads Processor threads Processor cache Processor cache Processor cache Processor threads Built-in Power supply location Processor treads Processor frequency Processor feduency	Supported storage drive types *	HDD & SSD	Browser supported	Microsoft Internet Explorer 10+,
Processor Processor manufacturer* Intel Share folder Some folder Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Folder folder Some folder Some folder Mac OS X 10.12 High Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2012, Windows Server 2012 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2012, Windows Server 2012 R2, Window			System log	✓
Processor manufacturer* Intel Processor family * Intel® Xeon® D Processor family * Intel® Xeon® D Processor model * D-1622 Processor frequency * 2.6 GHz Processor frequency * 3.2 GHz Processor cores Processor threads Processor threads Processor cache Processor cache Processor dade Processor cache Processor dade Processo	DISK roaming	✓	Hot spare	✓
Processor family * Intel® Xeon® D Universal Plug and Play (UPnP) Processor model * D-1622 USB copy function Processor frequency * 2.6 GHz Processor boost frequency Processor cores	Processor		S.M.A.R.T. support	✓
Processor model * D-1622 USB copy function ✓ Processor frequency * 2.6 GHz Processor frequency * 3.2 GHz Processor cores 4 Windows operating systems supported Processor threads 8 Linux operating systems supported Processor cache 6 MB CPU configuration (max) 1 On-board graphics card model Not available Memory Internal memory type DDR4 Maximum RAM supported 128 GB Memory Server operating systems supported 5 Server operating systems supported 5 Server operating systems supported 6 Windows Server 2012, Windows Server 2012, Windows Server 2019 Power Supply location Built-in	Processor manufacturer *	Intel	Share folder	CIFS/SMB
Processor frequency * 2.6 GHz Processor boost frequency Processor cores Processor threads Processor cache Processor cache Processor dard graphics card model Internal memory type Maximum RAM supported Max	Processor family *	Intel® Xeon® D	Universal Plug and Play (UPnP)	✓
Processor boost frequency Processor cores Processor cores Processor threads Processor cache Processor cache Processor cache Processor de G MB CPU configuration (max) On-board graphics card model Porestor de G MB Mac operating systems supported Processor cache Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.11 El Capitan, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2019 Memory slots Power Power supply location Built-in	Processor model *	D-1622	USB copy function	✓
Processor cores 4 Windows operating systems supported Processor threads 8 Linux operating systems supported Processor cache 6 MB CPU configuration (max) 1 On-board graphics card model Not available Mac operating systems supported Mac operating systems supported Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Memory Internal memory type Maximum RAM supported Memory slots Memory slots Internal memory * Memory form factor Windows 10, Windows 7, Windows 8 Windows 10, Windows 7, Windows 8 Wac OS X 10.10 Yosemite, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2012 Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2018 R2, Windows Server 2012, Windows Server 2012, R2, Windows Server 2012, R2, Windows Server 2019 Power Power supply location Built-in	' '		Software	
Processor cache Processor cache CPU configuration (max) On-board graphics card model Not available Mac operating systems supported Mac oS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Memory Internal memory type Maximum RAM supported Memory slots Memory slots Internal memory * Memory form factor DDR4 Server operating systems supported Server 2008 R2, Windows Server 2012, R2, Windows Server 2012, R2, Windows Server 2019 Power Power Power Power Power supply location Built-in	· ·			Windows 10, Windows 7, Windows 8
CPU configuration (max) 1 On-board graphics card model Not available Mac operating systems supported Sierra, Mac OS X 10.12 Gapitan, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2019 Internal memory * 16 GB Mac operating systems supported Server operating systems supported R2, Windows Server 2012, Windows Server 2012, Windows Server 2012, Windows Server 2012, Windows Server 2019 Power Memory form factor UDIMM Mac operating systems supported Sierra, Mac OS X 10.14 Hogierra, Mac OS X 10.12 Hogierra, Mac OS X 10.12 Hogierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.14 Mojave, Mac OS X 10.12 Hogierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Hogierra, Mac OS X 10.12 Hogierra, Mac OS X 10.14 Hogierra, Mac OS X 10.14 Hogierra, Mac OS X 10.12 Hogierra, Mac OS X 10.14 Hogierra, Mac OS X 10.12 Hogierra, Mac OS X 10.12 Hogierra, Mac OS X 10.14 Hogierra, Mac OS X 10.	Processor threads	8	Linux operating systems supported	✓
Internal memory type Maximum RAM supported Memory slots Internal memory * Memory form factor DDR4 Server operating systems supported Server operating systems supported Server operating systems supported R2, Windows Server 2012, Win	CPU configuration (max) On-board graphics card model	1	Mac operating systems supported	Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X
Maximum RAM supported 128 GB Memory slots Internal memory * Memory form factor DDR4 Server operating systems supported Server 2012, Windows Server 2012 R2, Windows Server 2019, Windows Server 2019 Power Power Power Power supply location Built-in	•			
Memory form factor UDIMM Power supply location Built-in	Maximum RAM supported	128 GB	Server operating systems supported	Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
Power supply location Built-in	•		Power	
Flack managers	•		Power supply location	Built-in
Power supply unit (PSU) capacity 250 W	Flash memory	5000 MB		
Network Number of power supply units 1	Network		* * * * * * * * * * * * * * * * * * * *	1

Network		Power	
Ethernet LAN * Ethernet LAN data rates DHCP client DHCP server Jumbo frames support Supported network protocols WLAN adapter supported Ports & interfaces	10,100,1000,2500 Mbit/s	Power consumption (typical) AC input voltage AC input frequency Weight & dimensions Width * Depth * Height * Weight	75.79 W 100 - 240 V 50 - 60 Hz 292.9 mm 319.8 mm 231.9 mm 8.5 kg
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Ethernet LAN (RJ-45) ports * PCI Express x8 (Gen 3.x) slots	✓342	Packaging content Cables included Number of screws Processor special features	AC, LAN (RJ-45) 32
	2		U Company
Chassis type * Cooling type * Product colour Number of fans Fan diameter Fan diameter 2 LED indicators Built-in display Cable lock slot Cable lock slot type	Tower Active Black 3 fan(s) 8 cm 9.7 cm HDD, SSD, Status Kensington	Embedded options available Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel QuickAssist Technology Intel Trusted Execution Technology Intel TSX-NI Intel Virtualization Technology (VT-x) Intel Virtualization Technology for Directed I/O (VT-d) Intel VT-x with Extended Page Tables (EPT)	X
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 35 °C 5 - 95%

