QNAP TVS-H1288X-W1250-16G NAS Tower Ethernet LAN Black W-1250

Brand : QNAP

×

Product code: TVS-H1288X-W1250-16G/128TB-IWP

Product name : TVS-H1288X-W1250-16G

Intel Xeon W-1250 6-core 3.3 GHz, 16 GB DDR4, 5 GB Flash, 8 x 3.5"/2.5" HDD/SSD + 4 x 2.5" SSD SATA 6Gb/s

QNAP TVS-H1288X-W1250-16G. Total installed storage capacity: 128 TB, Installed storage drive type: HDD, Supported storage drive types: HDD & SSD. Processor family: Intel® Xeon®, Processor manufacturer: Intel, Processor model: W-1250. Internal memory: 16 GB, Internal memory type: DDR4, Maximum RAM supported: 128 GB. Ethernet LAN data rates: 100,1000,2500,10000 Mbit/s, Ethernet LAN data rate supported (max): 10000 Mbit/s. HDMI version: 1.4b

Storage		Design	
Storage drive interface * Supported storage drive interfaces Storage drive sizes supported Number of M.2 (M & B) slots RAID support * RAID levels Online RAID migration Online RAID expansion	M.2, Serial ATA III M.2, Serial ATA III 2.5,3.5,M.2 2 ✓ 0, 1, 5, 6, 10, 50, 60, JBOD ✓	Fan diameter 2 LED indicators Built-in display Display type Cable lock slot Cable lock slot type Built-in speaker(s) Number of built-in speakers	9.7 cm HDD, LAN, SSD, System, USB LCD Kensington 1
RAID rebuild	1	Performance	
Hot-swap drive bays Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive types *		Type * Backup function * Backup features Buzzer Multilingual support Noise level Third-party support	NAS Cloud, USB drive, iSCSI LUN 26 dB
Processor		Security algorithms	256-bit AES, FIPS 140-2, HTTPS,
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency Processor cores Processor threads Processor cache CPU configuration (max)	Intel Intel® Xeon® W-1250 3.3 GHz 4.7 GHz 6 12 12 MB 1	Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported System log Hot spare S.M.A.R.T. support	SSH, SSL/TLS
Memory		Software	
Internal memory type Maximum RAM supported Memory slots Internal memory * Memory form factor ECC Flash memory	DDR4 128 GB 4 16 GB UDIMM ✓ 5000 MB	Windows operating systems supported Linux operating systems supported Mac operating systems supported Server operating systems supported	Windows 10, Windows 7, Windows 8 V Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Network		Other operating systems supported	
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) DHCP server Jumbo frames support iSCSI support	<pre> 100,1000,2500,10000 Mbit/s 10000 Mbit/s 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4</pre>	Power Power supply location Power supply unit (PSU) capacity Power consumption (typical) Power consumption (sleep) AC input voltage Fan voltage	Built-in 550 W 97.492 W 85.216 W 100 - 240 V 12 V

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date

Network		Weight & dimensions	
Wake-on-LAN ready Load balancing system Dynamic DNS (DDNS)	√ √ √	Width * Depth * Height *	369.9 mm 319.8 mm 234.6 mm
Ports & interfaces		Weight	11.3 kg
USB port *	√	Packaging content	
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	3	Cables included Number of screws	AC, LAN (RJ-45) 48
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Processor special features	
HDMI ports quantity	1	Embedded options available	×
HDMI version Ethernet LAN (RJ-45) ports *	1.4b 6	Enhanced Intel SpeedStep Technology	✓
3.5 mm (1/8-inch) out	1	Execute Disable Bit	✓
PCI Express x4 (Gen 3.x) slots	2	Idle States	✓
PCI Express x8 (Gen 3.x) slots	1	Intel 64	✓
Microphone in	1	Intel Clear Video Technology	✓
Audio in/out	4	Intel Trusted Execution Technology	✓
Design		Intel Virtualization Technology (VT- x)	1
Chassis type * Cooling type *	Tower Active	Intel Virtualization Technology for Directed I/O (VT-d)	1
Product colour Number of fans	Black 5 fan(s) 8 cm	Intel VT-x with Extended Page Tables (EPT)	1
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Storage temperature (T-T)	-20 - 70 °C
		Storage temperature (1-1)	

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.