Brand : QNAP

Product code: TS-870

×

Product name : TS-870

TS-870 - Intel 2.6GHz Dual-core Processor, 2GB SO-DIMM RAM, Flash 512MB DOM, 8 x 3.5" / 2.5" SATA 6Gb/s, SATA 3Gb/s HDD /SSD

QNAP TS-870. Supported storage drive types: HDD & SSD, Storage drive interface: Serial ATA II, Serial ATA III, Storage drive size: 2.5/3.5". Processor frequency: 2.6 GHz. Internal memory: 2 GB, Internal memory type: DDR3, Flash memory: 512 MB. Ethernet LAN data rates: 10,100,1000 Mbit/s. Chassis type: Tower, Cooling type: Active, Product colour: Black

-			
Storage		Design	
Storage drive interface * Storage drive size Maximum supported storage capacity RAID support * RAID levels	Serial ATA II, Serial ATA III 2.5/3.5" 32 TB	Fan diameter LED indicators Built-in display Display type Cable lock slot Cable lock slot type	9 cm HDD, LAN, Status, USB ✓ LCD ✓ Kensington
Hot-swap drive bays Storage drives installed *	×	Performance	
Number of storage drives supported * Supported storage drive types *		Type * Device class * Backup function *	NAS Small & Medium Business
Processor		Backup features	Cloud, iSCSI LUN
Processor frequency * Processor cores	2.6 GHz 2	Buzzer Reset button On/off switch	
Memory		Software	
Internal memory type Internal memory * Flash memory	DDR3 2 GB 512 MB	Operating system installed * Operating system version	QNAP Turbo System 4.0
Network		Power	
Ethernet LAN * Ethernet LAN data rates Wi-Fi iSCSI support	✓ 10,100,1000 Mbit/s ≍ ✓	Power supply unit (PSU) capacity Power consumption (typical) Power consumption (sleep) Power consumption (off) AC input voltage	250 W 59.9 W 29.1 W 1 W 100-240 V
Ports & interfaces		AC input frequency	50 - 60 Hz
USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3 2	Fan voltage Weight & dimensions	12 V
eSATA ports quantity HDMI ports quantity Ethernet LAN (RJ-45) ports *	2 1 4	Width * Depth * Height *	298.2 mm 235.4 mm 185.2 mm
Design		Weight Package weight	7.83 kg 8.9 kg
Chassis type * Cooling type * Product colour Number of fans	Tower Active Black 2 fan(s)	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 35 °C 0 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.