

QNAP TVS-h1688X-W1250-32G 48TB (Seagate Ironwolf) 16-Bay TurboNAS (12 x 3.5 HDD + 4 x 2.5 SSD); SATA 6G; Intel Xeon W-1250 6 cores 12 threads 3.3 GHz (boost up to 4.7 GHz); 32GB DDR4 ECC RAM (max. 128GB); 4 x 2.5GbE; 2 x 10GBASE-T 10GbE; 2 x M.2 22110/2 NAS Tower Ethernet LAN Black







**Brand**: QNAP

**Product code:** TVS-H1688X-W1250-32G/48TB-IW

**Product name :** TVS-h1688X-W1250-32G 48TB (Seagate Ironwolf) 16-Bay TurboNAS ( $12 \times 3.5 \text{ HDD} + 4 \times 2.5 \text{ SSD}$ ); SATA 6G; Intel Xeon W-1250 6 cores 12 threads 3.3 GHz (boost up to 4.7 GHz); 32GB DDR4 ECC RAM (max. 128GB); 4 x 2.5GbE; 2 x 10GBASE-T 10GbE; 2 x M.2 22110/2

- Attain quad-port Thunderbolt  $^{\rm m}$  3 connectivity by installing two QXP-T32P expansion cards in the PCle Gen 3 x4 slots
- Two 10GBASE-T and four 2.5GbE LAN ports accelerate virtualization, intensive file access, large backup/restoration tasks, and media transfer
- PCIe slots allow for installing 5/10/25/40GbE adapters, QM2 cards, or graphics cards to increase application performance
- 4K media playback and real-time transcoding; directly output videos to an HDMI display (up to 4K @30Hz)
- Supports virtual machines and containerized apps, centralized storage, backup, sharing, disaster recovery, and storage expansion
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud

Intel Xeon W-1250 6-core (3.3 GHz), Intel UHD Graphics P630, 4 x Long-DIMM DDR4, LCD, 6x USB 3.2 Gen 2, HDMI, 550 W

Storage		Design	
Storage drive interface *	Serial ATA II, Serial ATA III	Cable lock slot	✓
Supported storage drive interfaces	Serial ATA II, Serial ATA III	Cable lock slot type	Kensington
Storage drive sizes supported	2.5,3.5,M.2	Performance	
Number of M.2 (M & B) slots RAID support *	2	Type *	NAS
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD	Backup function * Backup features	✓ Cloud, USB drive, iSCSI LUN
Online RAID migration Online RAID expansion	<b>✓</b>	Buzzer	✓
RAID rebuild Hot-swap drive bays	1	Multilingual support Noise level	✓ 25.8 dB
Supported file systems	FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4	Third-party support Snapshot	1
Storage drives installed *	✓	Management protocols Web-based management	SNMP •
Total installed storage capacity * Number of storage drives supported *	48 TB 16	Share folder access right management	4
Supported storage drive types *	HDD & SSD	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Auto-rebuild Bad block scan	<b>✓</b>	Access Control List (ACL) Reset button	<b>√</b>
Processor		On/off switch	<b>*</b>
Processor manufacturer *	Intel	Built-in BitTorrent client	<b>√</b>
Processor family * Processor model * Processor frequency *	Intel® Xeon® W-1250 3.3 GHz	Built-in FTP server  Browser supported	Safari, Google Chrome, Internet Explorer, Mozilla Firefox
Processor boost frequency	4.7 GHz	System log Hot spare	1
Processor cores Processor threads	6 12	S.M.A.R.T. support	· ·
Processor cache CPU configuration (max)	12 MB 1	Universal Plug and Play (UPnP) USB copy function	<b>√</b>
On-board graphics card model	Intel UHD Graphics P630	Software	
		Operating system installed *	QuTS hero

Memory		Software	
Internal memory type  Maximum RAM supported  128 GB  Memory slots  Internal memory *  32 GB  Memory form factor  ECC  Flash memory  Network  Ethernet LAN *  Ethernet LAN data rates supported	128 GB 4 32 GB UDIMM  5000 MB  100,1000,2500,10000 Mbit/s 10000 Mbit/s	Software  Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported  Server operating systems supported  Other operating systems supported  Power  Power  Power supply location  Power supply unit (PSU) capacity  Power consumption (typical)	Server 2019
	<b>4 4 4</b>	Power consumption (sleep) AC input voltage Fan voltage	91.26 W 100 - 240 V 12 V
	* * * * * * * * * * * * * * * * * * *	Weight & dimensions Width * Depth * Height *	369.9 mm 319.8 mm 303.8 mm
Ports & interfaces		Packaging content	
USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	4	Cables included Power cables quantity Number of screws	AC, LAN (RJ-45) 1 72
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Processor special features	
HDMI ports quantity HDMI version Ethernet LAN (RJ-45) ports * PCI Express x4 (Gen 3.x) slots PCI Express x8 (Gen 3.x) slots	1 1.4b 6 2 1	Embedded options available Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64	× · · · · · · · · · · · · · · · · · · ·
Design		Intel Clear Video Technology	1
Chassis type * Cooling type * Product colour Number of fans Fan diameter Fan diameter 2 LED indicators Built-in display	Tower Active Black 5 fan(s) 8 cm 9.7 cm HDD, LAN, Status, System, USB	Intel Trusted Execution Technology Intel Virtualization Technology (VT-x) Intel Virtualization Technology for Directed I/O (VT-d) Intel VT-x with Extended Page Tables (EPT)  Operational conditions	1 1 1
Display type	LCD	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T)	0 - 40 °C 5 - 95% -20 - 70 °C

