QNAP TS-H886-D1622-16G NAS Tower Ethernet LAN Black D-1622

Brand : QNAP

Product code: TS-H886-D1622-16G/48TB-IWP

×

Product name : TS-H886-D1622-16G

- Four 2.5GbE ports accelerate file sharing across teams and devices, virtual machine applications or multimedia transmission

- DDR4 ECC memory detects and corrects single-bit memory errors, demonstrating high reliability for crucial applications

- Two M.2 NVMe Gen 3 x4 SSD slots (each slot providing up to 3.2 GB/s bandwidth) enable SSD caching to boost random read/write performance

- Two PCIe slots allow for 5GbE/10GbE/25GbE/40GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance

- Scalable storage supporting virtual machines, containerized apps, centralized storage, backup, sharing, and disaster recovery

- QuTS hero combines ZFS advantages with the QTS App Center ecosystem to empower your business Xeon D-1622 2.6 GHz, 16 GB DDR4, 5GB, 6x 3.5" + 2x 2.5", 2x M.2, 4x 2.5G LAN, 3x USB 3.2,

231.9x292.9x319.8 mm

Storage		Performance	
Supported storage drive interfaces	Serial ATA II, Serial ATA III	Type *	NAS
Storage drive sizes supported	2.5,3.5"	Device class *	Large Enterprise Business
Number of M.2 (M & B) slots	2	Backup function *	V
RAID support *	1	Backup features	Cloud, iSCSI LUN
RAID levels	0, 1, 5, 6, 10, 50, 60	Buzzer	1
Online RAID migration	1	Multilingual support	1
Online RAID expansion	1	Noise level	20.4 dB
RAID rebuild	1	Snapshot	1
Hot-swap drive bays	1	Web-based management	✓
Supported file systems Storage drives installed *	FAT32, HFS+, NTFS, ZFS, ext3, ext4	Security algorithms	256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Total installed storage capacity *	48 TB	Access Control List (ACL)	1
Number of storage drives installed *	6	Reset button	1
Number of storage drives supported		On/off switch	1
*	0	Built-in FTP server	1
Installed storage drive type * Supported storage drive types *	HDD HDD & SSD	Browser supported	Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox
Bad block scan		System log	1
Disk roaming	v	Hot spare	1
Processor		S.M.A.R.T. support	1
Processor manufacturer *	Intel	Share folder	CIFS/SMB
Processor family *	Intel® Xeon® D	Universal Plug and Play (UPnP)	1
Processor model *	D-1622	USB copy function	1
Processor frequency *	2.6 GHz	Software	
Processor boost frequency Processor cores	3.2 GHz 4	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Processor threads	8	Linux operating systems supported	1
Processor cache CPU configuration (max) On-board graphics card model	6 MB 1 Not available	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X
Memory			10.15 Catalina
Internal memory type Maximum RAM supported Memory slots	DDR4 128 GB 4	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Internal memory *	16 GB	Power	
Memory form factor	UDIMM	Power supply location	Built-in
Flash memory	5000 MB	Power supply unit (PSU) capacity	250 W
Network		Number of power supply units	1
Ethernet LAN *	1	Power consumption (typical)	75.79 W

Network		Power		
Ethernet LAN data rates DHCP client	10,100,1000,2500 Mbit/s 🗸	AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz	
DHCP server Jumbo frames support Supported network protocols WLAN adapter supported Ports & interfaces USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Ethernet LAN (RJ-45) ports *	✓ TCP/IP, HTTP/HTTPS ✓ 3 4	Weight & dimensions Width * Depth * Height * Weight Packaging content Cables included Number of screws	292.9 mm 319.8 mm 231.9 mm 8.5 kg AC, LAN (RJ-45) 32	
PCI Express x8 (Gen 3.x) slots	2	Processor special features		
Design Chassis type * Cooling type * Product colour Number of fans Fan diameter Fan diameter 2 LED indicators Built-in display Cable lock slot Cable lock slot type	Tower Active Black 3 fan(s) 8 cm 9.7 cm HDD, SSD, Status Kensington	Embedded options available Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel QuickAssist Technology Intel Trusted Execution Technology Intel TSX-NI Intel Virtualization Technology (VT- x) Intel Virtualization Technology for Directed I/O (VT-d) Intel VT-x with Extended Page Tables (EPT)	× 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	
		Operational conditions		

Operating temperature (T-T)0 - 35 °COperating relative humidity (H-H)5 - 95%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.