## QNAP

## QNAP TS-832PXU-RP-4G NAS Rack (2U) Ethernet LAN Black AL324

**Brand :** QNAP **Product code:** TS-832PXU-RP-4G/96TB-REDPLUS

Product name: TS-832PXU-RP-4G



- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing
- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning
- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of Google G Suite and Microsoft 365
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks
- Expand the application potential of the TS-832PXU-RP by installing a compatible PCIe card
- Increase the storage capacity of the TS-832PXU-RP with QNAP TR RAID expansion enclosures or TL IROD

8x 3.5", 4GB DDR4, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 2x 250W PSU, 89x482x534 mm



Storage		Design	
Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion	Serial ATA II, Serial ATA III 2.5,3.5" ✓ 0, 1, 5, 6, 10, JBOD ✓	Chassis type * Cooling type * Product colour Fan diameter Fan diameter 2 LED indicators	Rack (2U) Active Black 2 mm 7 cm HDD, LAN, Status
RAID rebuild	<b>√</b>	Performance	
Storage drives installed * 7  Total installed storage capacity * 96  Number of storage drives installed * 8  Number of storage drives supported * 8  Installed storage drive type * HDI	96 TB 8	Type * Device class * Backup function * Backup features Buzzer Multilingual support Snapshot Web-based management	NAS Small & Medium Business  Cloud, iSCSI LUN
Bad block scan	✓	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Processor  Processor manufacturer *  Processor family *  Processor model *  Processor frequency *  Processor cores	Annapurna Labs Annapurna Labs AL324 1.7 GHz	Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported	Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+, Google Chrome
Memory		System log	✓
Internal memory type Maximum RAM supported Memory slots Internal memory * Memory form factor	DDR4 16 GB 1 4 GB UDIMM	Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP) USB copy function	✓ ✓ CIFS/SMB ✓
Flash memory	512 MB	Software	
Network  Ethernet LAN *  Ethernet LAN data rates  Ethernet LAN data rate supported (max)  DHCP client  DHCP server  Jumbo frames support	100,1000,2500,10000 Mbit/s 10000 Mbit/s	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported	QNAP Turbo System 4.4.3 Windows 10, Windows 7, Windows 8  Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojaya, Mac OS X
iSCSI support	<b>*</b>		Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina

Network		Software	
Wake-on-LAN ready Supported network protocols Link aggregation Load balancing system WLAN adapter supported	PPTP, L2TP/IPSec, OpenVPN, QBelt	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Power	
Ports & interfaces	•	Power supply location Power supply unit (PSU) capacity	Built-in 250 W
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector	✓	Number of power supply units	2
	4 2 SFP+	AC input voltage	100 - 240 V
		Fan voltage	12 V
		Weight & dimensions	
Ethernet LAN (RJ-45) ports *	2	Width *	482 mm
		Depth *	534 mm
		Height *	89 mm
		Packaging content	
		Cables included	AC, LAN (RJ-45)
		Number of screws	56
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%

