

QNAP TVS-472XT-I3-4G/32TB-REDPRO NAS/storage server Tower Ethernet LAN Black i3-8100T





Brand : QNAP **Product code:** TVS-472XT-I3-4G/32TB-REDPRO

×

Product name: TVS-472XT-I3-4G/32TB-REDPRO

- High-speed Thunderbolt 3 with SMB protocol, allowing Mac and Windows users to collaborate on media editing
- $\hbox{-} 5\hbox{-speed 10GBASE-T RJ45 connectivity accelerates virtualization applications and file sharing across teams and devices}\\$
- PCIe expandability allows for graphics cards or $40\text{GbE}/\ 25\text{GbE}/\ 10\text{GbE}$ adapters to increase application performance
- Install M.2 PCIe (Gen 3 \times 2, 2 GB/s) NVMe SSDs (sold separately) to set up caching or storage pools, improving file access efficiency
- 4K media playback and real-time transcoding; directly view creative works on an HDTV via HDMI 2.0 (4K @60Hz) output
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks

Intel Core i3-8100T, 4 GB DDR4, 4x 3.5", 2x M.2, RJ-45, Thunderbolt, PCIe, USB 3.2, HDMI, $188.2\times199.3\times279.6$ mm

| Storage | | Design | |
|--|---|--|--|
| Supported storage drive interfaces Storage drive size Storage drive sizes supported Number of system drives installed System drive capacity | Serial ATA II, Serial ATA III Serial ATA II, Serial ATA III 2.5/3.5" 2.5,3.5" 1 5 GB | Fan diameter 2 LED indicators Built-in display Display type Cable lock slot Cable lock slot type | 6 cm HDD, LAN, Status, USB ✓ LCD ✓ Kensington |
| Number of M.2 (M & B) slots | 2 | Performance | |
| RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive type * | | Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Security algorithms Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported | NAS Small & Medium Business Cloud, iSCSI LUN 21.2 dB 256-bit AES, HTTPS, SSL/TLS Mozilla Firefox, Microsoft Edge, |
| Processor | | System log | Google Chrome, Apple Safari |
| Processor manufacturer * Intel Processor generation 8th gen Intel® Core™ i3 Processor family * Intel® Core™ i3 Processor model * i3-8100T | 8th gen Intel® Core™ i3 Intel® Core™ i3 i3-8100T | Hot spare S.M.A.R.T. support Share folder USB copy function | √ CIFS/SMB |
| Processor frequency * Processor cores | 3.1 GHz 4 | Software | |
| Processor cores Processor threads Processor cache Bus type Configurable TDP-down frequency CPU configuration (max) Number of processors supported On-board graphics card model | essor threads 4 essor cache 6 MB ype DMI3 gurable TDP-down frequency 2.4 GHz configuration (max) 1 ber of processors supported 1 | Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported | QNAP Turbo System 4.4.0 Windows 10, Windows 7, Windows 8 |
| Memory | | | |
| Internal memory type | DDR4 | | |

| Momory | | Software | |
|---|---------------------------------------|--|---|
| Memory | C4 CD | SULWATE | M 00 V 10 10 V |
| Maximum RAM supported | 64 GB | | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 |
| Memory slots | 2 4 CP | | Sierra, Mac OS X 10.13 High Sierra, |
| Internal memory * | 4 GB | Mag apparating quetamag gunnarted | Mac OS X 10.14 Mojave, Mac OS X |
| Memory form factor | SO-DIMM 5000 MB | Mac operating systems supported | 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac |
| Flash memory Network | 3000 MB | | OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big |
| Ethernet LAN * | ✓ | | Sur |
| Ethernet LAN data rates | 10,100,1000,2500,5000,10000 Mbit/s | Server operating systems supported | Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, |
| Ethernet LAN data rate supported (max) | 10000 Mbit/s | | Windows Server 2016 |
| DHCP client | ✓ | Power | |
| DHCP server | ✓ | Power supply location | Built-in |
| Jumbo frames support | ✓ | Power supply unit (PSU) capacity | 250 W |
| iSCSI support | ✓ | Number of power supply units | 1 |
| Wake-on-LAN ready | ✓ | Power consumption (typical) | 37.32 W |
| Link aggregation | ✓ | Power consumption (sleep) | 24.14 W |
| Load balancing system | ✓ | AC input voltage | 100-240 V |
| Dynamic DNS (DDNS) | ✓ | Fan voltage | 12 V |
| WLAN adapter supported | ✓ | Weight & dimensions | |
| Ports & interfaces | | Width * | 199.3 mm |
| USB port * | √ | Depth * | 279.6 mm |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A | 1 | Height * | 188.2 mm |
| ports quantity | 1 | Weight | 5.4 kg |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 2 | Packaging content | |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity | 2 | Cables included Power cables quantity | AC, LAN (RJ-45) 1 |
| HDMI ports quantity | 1 | Processor special features | |
| HDMI version | 2.0 | Embedded options available | ✓ |
| Ethernet LAN (RJ-45) ports * | 3 | Enhanced Intel SpeedStep | 1 |
| Thunderbolt 3 ports quantity | 2 | Technology | * |
| PCI Express x4 (Gen 3.x) slots | 1 | Execute Disable Bit | ✓ |
| Design | | Idle States | V |
| Chassis type * | Tower | Intel 64 | V |
| Cooling type * | Active | Intel Clear Video Technology | V |
| Product colour | Black | Intel Enhanced Halt State | ✓ |
| Number of fans Fan diameter | 3 fan(s) 12 cm | Intel Identity Protection Technology version | 1.00 |
| | | Intel Secure Key Technology version | |
| | | Intel Stable Image Platform Program (SIPP) | |
| | | Intel Stable Image Platform Program (SIPP) version | 0.00 |
| | | Intel Trusted Execution Technology | X |
| | | Intel TSX-NI | X |
| | | Intel TSX-NI version | 0.00 |
| | | Intel Virtualization Technology (VT-x) | 1 |
| | | Intel Virtualization Technology for Directed I/O (VT-d) | 1 |
| | | Intel VT-x with Extended Page Tables (EPT) | ✓ |
| | | Operational conditions | |
| | | Operating temperature (T-T) | 0 - 40 °C |
| | | Operating relative humidity (H-H) | 5 - 95% |
| | | Storage temperature (T-T) | -20 - 70 °C |

