QNAP

QNAP TVS-672XT NAS Tower Intel® Core™ i3 i3-8100T 8 GB DDR4 36 TB HDD QNAP Turbo System Black

Brand : QNAP **Product code:** TVS-672XT-I3-8G-36TB-IW

Product name: TVS-672XT

Intel Core i3-8100T 3.1 GHz, DDR4 SODIMM, 4 GB Flash, Intel UHD Graphics 630, 6 \times 3.5" SATA, 2 \times M.2, 1 \times 10GBASE-T RJ45, 1 \times USB 3.0, 2 \times Type-C USB 3.1 Gen2, 2 \times Type-A USB 3.1 Gen2, 1 \times HDMI 2.0, 250W

QNAP TVS-672XT. Type: NAS. Chassis type: Tower. Device class: Home & Home Office. Processor family: Intel® Core™ i3, Processor model: i3-8100T, Processor frequency: 3.1 GHz. Internal memory: 8 GB, Internal memory type: DDR4. Total installed storage capacity: 36 TB, Installed storage drive type: HDD. Operating system installed: QNAP Turbo System









_			
Storage		Design	
Supported storage drive interfaces	M.2, Serial ATA III	LED indicators	HDD, LAN, Status, USB
Storage drive sizes supported	2.5,3.5,M.2	Built-in display	✓
Number of M.2 (M & B) slots	2	Cable lock slot	✓
RAID support *	✓	Cable lock slot type	Kensington
RAID levels	0, 1, 5, 6, 10, 50, JBOD	Built-in speaker(s)	✓
Online RAID migration	✓	Number of built-in speakers	1
Online RAID expansion	✓	Performance	
Hot-swap drive bays	✓	Type *	NAS
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4	Device class *	Home & Home Office
Storage drives installed *	✓	Backup function *	✓
Total installed storage capacity *	36 TB	Backup features	iscsi lun
Number of storage drives supported	1 6	Buzzer	✓
*	-	Multilingual support	✓
Installed storage drive type *	HDD	Noise level	23.8 dB
Supported storage drive types *	HDD & SSD	Snapshot	✓
Auto-rebuild	✓	Management protocols	SNMP 2/3
Bad block scan	✓	Web-based management	✓
Disk roaming	✓	Share folder access right management	✓
Processor		Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH
Processor manufacturer *	Intel	Access Control List (ACL)	✓
Processor generation	8th gen Intel® Core™ i3	Reset button	✓
Processor family *	Intel® Core™ i3	On/off switch	✓
Processor model *	i3-8100T	Built-in iTunes server	✓
Processor frequency *	3.1 GHz	Built-in FTP server	✓
Processor cores Processor threads Processor cache	4 4 6 MB	Browser supported	Apple Safari 7, Google Chrome, Microsoft Internet Explorer 10, Mozilla Firefox
Bus type	DMI3	System log	√
Configurable TDP-down frequency	2.4 GHz	Hot spare	√
CPU configuration (max)	1	S.M.A.R.T. support	√
ECC supported by processor	·	Share folder	CIFS/SMB
PCI Express configurations	1x16, 1x8+2x4, 2x8	Universal Plug and Play (UPnP)	✓
PCI Express slots version	3.0	Software	
Processor cache type	Smart Cache		ONART de Caden
Processor code	SR3Y8	Operating system installed *	QNAP Turbo System
Processor codename	Coffee Lake	Operating system version	4.4.0
1 TOCCOSOF COUCHAINC	COLLEC EURC		

Виососсои		Software	
Processor	14 nm	Software	Windows 10 Windows 10
Processor lithography Processor operating modes Processor package size Processor socket Scalability Stepping System bus rate Tjunction Thermal Design Power (TDP) On-board graphics card model Maximum internal memory supported by processor Memory bandwidth supported by processor (max) Memory	14 nm 64-bit 37.5 x 37.5 mm LGA 1151 (Socket H4) 1S B0 8 GT/s 82 °C 35 W Intel® UHD Graphics 630 64 GB 37.5 GB/s	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate, Windows 7 Vf4, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8
Internal memory *	8 GB		8 Pro, Windows 8 Pro x64, Windows 8 x64
Internal memory type Maximum RAM supported Memory slots Memory form factor	DDR4 32 GB 2 SO-DIMM	Linux operating systems supported Mac operating systems supported	✓ Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra,
Flash memory	4000 MB	inde operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain
Network			Lion, Mac OS X 10.9 Mavericks
Ethernet LAN data rates Ethernet LAN data rate supported	10,100,1000,1200,2500,5000,10000 Mbit/s	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
(max)	10000 Mbit/s	Power	
Wi-Fi	×	Power supply unit (PSU) capacity	250 W
DHCP client	4	AC input voltage	100 - 240 V
DHCP server Jumbo frames support	4	Fan voltage	12 V
iSCSI support	1	Weight & dimensions	
Wake-on-LAN ready	1	Width *	264.3 mm
Supported network protocols	TCP/IP, IPv4, IPv6	Depth *	279.6 mm
Link aggregation	√	Height *	188.2 mm
Load balancing system	4	Packaging content	
Dynamic DNS (DDNS) WLAN adapter supported	V	Cables included	AC, LAN (RJ-45)
Ports & interfaces		Quick installation guide	✓
USB port *	1	Processor special features	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Embedded options available Enhanced Intel SpeedStep Technology	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Execute Disable Bit	✓
USB 3.2 Gen 2 (3.1 Gen 2) Type-C		Idle States	✓
ports quantity	2	Intel 64	V
HDMI ports quantity	1	Intel Clear Video Technology Intel Enhanced Halt State	*
HDMI version Ethernet LAN (BL 4E) parts *	2.0	Intel Identity Protection Technology	•
Ethernet LAN (RJ-45) ports * Thunderbolt 3 ports quantity	2	version	1.00
3.5 mm (1/8-inch) out	√	Intel Secure Key Technology version	
Microphone in	✓	Intel Stable Image Platform Program (SIPP)	×
PCI Express x4 (Gen 3.x) slots	1	Intel Stable Image Platform Program	0.00
Graphics		(SIPP) version Intel Trusted Execution Technology	×
On-board graphics card base frequency	350 MHz	Intel TSX-NI	×
On-board graphics card dynamic	1100 MHz	Intel TSX-NI version	0.00
frequency (max) On-board graphics card DirectX		Intel Virtualization Technology (VT-x)	1
version	12.0	Intel Virtualization Technology for Directed I/O (VT-d)	✓

Graphics		Processor special features	
On-board graphics card OpenGL version	4.5	Intel VT-x with Extended Page Tables (EPT)	✓
On-board graphics card ID Maximum on-board graphics card memory Number of displays supported (on- board graphics)	0x3E91 64 GB 3	Intel® AES New Instructions (Intel® AES-NI)	✓
		Intel® Clear Video HD Technology (Intel® CVT HD)	✓
		Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT	1
Design		for MID)	
Chassis type * Cooling type * Product colour Number of fans	Tower Active Black 4 fan(s)	Intel® Hyper Threading Technology (Intel® HT Technology)	×
		Intel® Identity Protection Technology (Intel® IPT)	✓
		Intel® InTru™ 3D Technology	✓
Fan diameter	9.2 cm	Intel® OS Guard	✓
Fan diameter 2	6 cm	Intel® Quick Sync Video Technology	✓
		Intel® Secure Key	✓
		Intel® Smart Cache	✓
		Intel® Turbo Boost Technology	×
		Maximum number of PCI Express lanes	16
		Thermal Monitoring Technologies	✓
		Thermal solution specification	PCG 2015A
		Memory channels supported by processor	Dual
		Memory types supported by processor	DDR4-SDRAM
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Other features	
		Digital Living Network Alliance (DLNA) certified	✓
		Processor ARK ID	129944

