

CyberPower BRICs LCD uninterruptible power supply (UPS) 1 kVA  
600 W 6 AC outlet(s)

Brand : CyberPower

Product code: BR1000ELCD-UK

Product name : BRICs LCD

Line-interactive, 1000VA, 600W, 6 Outlets, USB, LCD  
CyberPower BRICs LCD. Output power capacity: 1 kVA, Output power: 600 W, Waveform: Sine. AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Compact, Product colour: Black, Housing material: Plastic. Compliance certificates: RoHS, Certification: CE

| Features                           |                         | Battery                           |             |
|------------------------------------|-------------------------|-----------------------------------|-------------|
| Output power capacity *            | 1 kVA                   | Typical backup time at half load  | 6 min       |
| Output power *                     | 600 W                   | Battery recharge time             | 8 h         |
| Waveform *                         | Sine                    | Hot-swap battery                  | ✓           |
| Input operation voltage (min) *    | 165 V                   | Design                            |             |
| Input operation voltage (max) *    | 290 V                   | Form factor *                     | Compact     |
| Input frequency *                  | 45/65 Hz                | Housing material                  | Plastic     |
| Output operation voltage (min)     | 220 V                   | Cable length                      | 1.5 m       |
| Output operation voltage (max)     | 240 V                   | Product colour *                  | Black       |
| Automatic Voltage Regulation (AVR) | ✓                       | LED indicators                    | ✓           |
| Power factor                       | 0.6                     | Operational conditions            |             |
| Noise level                        | 40 dB                   | Operating temperature (T-T)       | 0 - 40 °C   |
| Audible alarm(s)                   | ✓                       | Storage temperature (T-T)         | -20 - 50 °C |
| Ports & interfaces                 |                         | Operating relative humidity (H-H) | 0 - 90%     |
| AC outlets quantity                | 6 AC outlet(s)          | Storage relative humidity (H-H)   | 0 - 90%     |
| Modem (RJ-11) ports                | 2                       | Operating altitude                | 0 - 3000 m  |
| Ethernet LAN (RJ-45) ports         | 2                       | Certificates                      |             |
| Battery                            |                         | Compliance certificates           | RoHS        |
| Battery technology                 | Sealed Lead Acid (VRLA) | Certification                     | CE          |
| Battery capacity                   | 9 Ah                    | Packaging content                 |             |
| Battery voltage                    | 12 V                    | Cables included                   | USB cable   |
| Number of batteries supported      | 1                       | Weight & dimensions               |             |
| Typical backup time at full load   | 1 min                   | Width                             | 166 mm      |
|                                    |                         | Depth                             | 288 mm      |
|                                    |                         | Height                            | 118 mm      |
|                                    |                         | Weight                            | 6.5 kg      |
| Packaging data                     |                         |                                   |             |
|                                    |                         | Bundled software                  | PPPE        |
| Other features                     |                         |                                   |             |
|                                    |                         | Battery type                      | RBP0006     |



4712856271348

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.