

CyberPower BR1200ELCD uninterruptible power supply (UPS) Line-Interactive 1.2 kVA 720 W 8 AC outlet(s)

Brand : CyberPower

Product code: BR1200ELCD-UK

Product name : BR1200ELCD

- Line-interactive UPS Topology
- Energy Saving Technology
- Simulated Sine Wave Output
- Automatic Voltage Regulation (AVR)
- USB Charging Port
- Surge and Spike Protection
- Phone/ Fax/ Modem/ DSL/ Network Protection
- LCD Status Display
- PowerPanel® Management Software
- Brick Form Factor

Line-Interactive, 1200VA/720W, AVR, LCD



CyberPower BR1200ELCD uninterruptible power supply (UPS) Line-Interactive 1.2 kVA 720 W 8 AC outlet(s):

CyberPower BR1200ELCD offers home and office users a reliable battery backup and safeguards office PCs, network communication equipment, and other electronic devices from surges, spikes, brownouts and other power incidents. Designed with GreenPower UPS™ Technology to improve operating efficiency and to minimize energy consumption, users can enjoy significant energy cost savings over conventional UPS systems.

Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at half load	9 min
Output power capacity *	1.2 kVA	Battery recharge time	8 h
Output power *	720 W	Charging current	1 A
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	170 V	Design	
Input operation voltage (max) *	290 V	Form factor *	Compact
Input frequency *	50/60 Hz	Housing material	Plastic
Output frequency	50/60 Hz	Cable length	1.5 m
Automatic Voltage Regulation (AVR)	✓	Product colour *	Black
Surge energy rating	125 J	Display type	LCD
Response time	4 ms	LED indicators	✓
EMI/RFI noise filtering	✓	Operational conditions	
Noise level	40 dB	Operating temperature (T-T)	0 - 40 °C
Surge protection	✓	Storage temperature (T-T)	-20 - 50 °C
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Network, Telephone	Operating relative humidity (H-H)	0 - 90%
Power protection features	Overload	Storage relative humidity (H-H)	0 - 90%
Audible alarm(s)	✓	Operating altitude	0 - 3000 m
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Non-operating altitude	0 - 3000 m
Ports & interfaces		Certificates	
AC outlets quantity	8 AC outlet(s)	Compliance certificates	RoHS
USB port	✓	Certification	CE , RCM
USB 2.0 ports quantity	1	Weight & dimensions	
Serial interface	✗	Width	166 mm
Modem (RJ-11) ports	2	Depth	288 mm
Ethernet LAN (RJ-45) ports	2	Height	118 mm
		Weight	8.2 kg

Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Bundled software	PowerPanel® Personal Edition
Typical backup time at full load	2 min	Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



4712856272741

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.