

## QNAP TS-H886-D1622-16G NAS Tower Ethernet LAN Black D-1622





Brand: QNAP Product code: TS-H886-D1622-16G/84TB-IWP

Product name: TS-H886-D1622-16G

- $\hbox{-} Four 2.5 \hbox{GbE ports accelerate file sharing across teams and devices, virtual machine applications or multimedia transmission}$
- DDR4 ECC memory detects and corrects single-bit memory errors, demonstrating high reliability for crucial applications
- Two M.2 NVMe Gen 3 x4 SSD slots (each slot providing up to 3.2 GB/s bandwidth) enable SSD caching to boost random read/write performance
- Two PCIe slots allow for 5GbE/10GbE/25GbE/40GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance
- Scalable storage supporting virtual machines, containerized apps, centralized storage, backup, sharing, and disaster recovery
- QuTS hero combines ZFS advantages with the QTS App Center ecosystem to empower your business Xeon D-1622 2.6 GHz, 16 GB DDR4, 5GB, 6x 3.5" + 2x 2.5", 2x M.2, 4x 2.5G LAN, 3x USB 3.2, 231.9x292.9x319.8 mm

Storage		Performance	
Supported storage drive interfaces	Serial ATA II, Serial ATA III	Type *	NAS
Storage drive sizes supported	2.5,3.5"	Device class *	Large Enterprise Business
Number of M.2 (M & B) slots	2	Backup function *	✓
RAID support *	✓	Backup features	Cloud, iSCSI LUN
RAID levels	0, 1, 5, 6, 10, 50, 60	Buzzer	✓
Online RAID migration	✓	Multilingual support	✓
Online RAID expansion	✓	Noise level	20.4 dB
RAID rebuild	✓	Snapshot	✓
Hot-swap drive bays	✓	Web-based management	✓
Supported file systems Storage drives installed *	FAT32, HFS+, NTFS, ZFS, ext3, ext4	Security algorithms	256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Total installed storage capacity *	84 TB	Access Control List (ACL)	✓
Number of storage drives installed *		Reset button	✓
Number of storage drives supported		On/off switch	✓
*	6	Built-in FTP server	✓
Installed storage drive type * Supported storage drive types *	HDD HDD & SSD	Browser supported	Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox
Bad block scan	4	System log	✓
Disk roaming	4	Hot spare	✓
Processor		S.M.A.R.T. support	✓
Processor manufacturer *	Intel	Share folder	CIFS/SMB
Processor family *	Intel® Xeon® D	Universal Plug and Play (UPnP)	✓
Processor model *	D-1622	USB copy function	✓
Processor frequency * Processor boost frequency	2.6 GHz 3.2 GHz	Software	
Processor cores	4	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Processor threads	8	Linux operating systems supported	✓
Processor cache CPU configuration (max) On-board graphics card model Memory	6 MB 1 Not available	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
	DDD4		Windows Server 2008 R2, Windows
Internal memory type Maximum RAM supported Memory slots	DDR4 128 GB 4	Server operating systems supported	Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Internal memory *	16 GB	Power	
Memory form factor	UDIMM	Power supply location	Built-in
Flash memory	5000 MB	Power supply unit (PSU) capacity	250 W
Network		Number of power supply units	1
Ethernet LAN *	1	Power consumption (typical)	75.79 W
	•		

Network		Power	
Ethernet LAN data rates DHCP client DHCP server Jumbo frames support Supported network protocols	10,100,1000,2500 Mbit/s	AC input voltage	100 - 240 V
		AC input frequency	50 - 60 Hz
		Weight & dimensions	
		Width *	292.9 mm
WLAN adapter supported	/ / / / / / / / / / / / / / / / / / /	Depth *	319.8 mm
	•	Height *	231.9 mm
Ports & interfaces		Weight	8.5 kg
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Ethernet LAN (RJ-45) ports *	<b>√</b> 3 4	Packaging content	
		Cables included	AC, LAN (RJ-45)
		Number of screws	32
PCI Express x8 (Gen 3.x) slots	2	Processor special features	
Design		Embedded options available	×
Chassis type *	Tower	Enhanced Intel SpeedStep Technology	✓
Cooling type * Product colour	Active Black	Execute Disable Bit	✓
Number of fans	3 fan(s)	Idle States	✓
Fan diameter	8 cm	Intel 64	✓
Fan diameter 2	9.7 cm	Intel QuickAssist Technology	×
LED indicators	HDD, SSD, Status  ✓	Intel Trusted Execution Technology	<b>V</b>
Built-in display		Intel TSX-NI Intel Virtualization Technology (VT-	<b>*</b>
Cable lock slot	✓	x)	✓
Cable lock slot type	Kensington	Intel Virtualization Technology for Directed I/O (VT-d)	✓
		Intel VT-x with Extended Page Tables (EPT)	✓
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 35 °C 5 - 95%

