QNAP

QNAP TS-1232PXU-RP-4G NAS Rack (2U) Annapurna Labs AL324 4 GB DDR4 72 TB HDD QNAP Turbo System Black

Brand : QNAP **Product code:** TS-1232PXU-RP-4G/72TB-IW

Product name: TS-1232PXU-RP-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing
- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning
- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of Google G Suite and Microsoft 365
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks
- Expand the application potential of the TS-1232PXU-RP by installing a compatible PCle card
- Increase the storage capacity of the TS-1232PXU-RP with QNAP TR RAID expansion enclosures or TL IBOD

12x 3.5", 4GB DDR4, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 2x 250W PSU, 89x482x534 mm



Character and		D. ciam	
Storage		Design	
Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration	Serial ATA II, Serial ATA III 2.5,3.5" ✓ 0, 1, 5, 6, 10, JBOD ✓	Cooling type * Product colour Number of fans Fan diameter LED indicators	Active Black 2 fan(s) 7 cm HDD, LAN, Status
Online RAID expansion	1	Performance	
RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported		Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level	NAS Small & Medium Business Cloud, iSCSI LUN 32.2 dB
Installed storage drive type * Supported storage drive types * Bad block scan	HDD HDD & SSD ✓	Snapshot Web-based management Security algorithms	✓ ✓ 256-bit AES, FIPS 140-2, HTTPS,
Processor		Access Control List (ACL)	SSH, SSL/TLS ✓
Processor manufacturer *	Annapurna Labs	Reset button	1
Processor family *	Annapurna Labs	On/off switch	√
Processor model *	AL324	Built-in FTP server	✓
Processor frequency * Processor cores	1.7 GHz 4	Browser supported	Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+, Google Chrome
Memory		System log	√
Internal memory *	4 GB	Hot spare	✓
Internal memory type	DDR4	S.M.A.R.T. support	✓
Maximum RAM supported	16 GB	Share folder	CIFS/SMB
Memory slots	1	Universal Plug and Play (UPnP)	√
Memory form factor Flash memory	UDIMM 512 MB	USB copy function	✓
Network	JIZ MD	Software	
	,	Operating system installed *	QNAP Turbo System
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported	100,1000,2500,10000 Mbit/s	Operating system version Windows operating systems supported	4.4.3 Windows 10, Windows 7, Windows 8
(max)	10000 Mbit/s	Linux operating systems supported	✓
DHCP client	✓		
DHCP server	1		
Jumbo frames support	✓		

Network		Software	
iSCSI support	1	Sortware	Mac OS X 10.10 Yosemite. Mac OS X
Wake-on-LAN ready Supported network protocols Link aggregation	PPTP, L2TP/IPSec, OpenVPN, QBelt	Mac operating systems supported	10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Load balancing system WLAN adapter supported	4	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
Ports & interfaces			Server 2019
USB port *	✓	Power	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports *	4 2 SFP+ 2	Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) AC input voltage	Built-in 250 W 2 83.57 W 100 - 240 V
Design		Fan voltage	12 V
Chassis type *	Rack (2U)	Weight & dimensions	
		Width * Depth * Height * Weight	482 mm 534 mm 89 mm 11.3 kg
		Packaging content	
		Cables included Number of screws	AC, LAN (RJ-45) 84
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

