

QNAP TS-932PX-4G NAS Tower Ethernet LAN Black Alpine AL-324





Brand : QNAP **Product code:** TS-932PX-4G/10TB-REDPRO

Product name: TS-932PX-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports empower bandwidth-demanding tasks and accelerate file sharing
- HBS provides comprehensive backup and data recovery; QuDedup deduplicates the data at the source to optimize storage and bandwidth usage, while reducing backup times
- Snapshots record your system status, allowing you to protect files and data from accidental deletion and malware attacks
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
- Qtier auto-tiering technology and SSD caching enable constant storage optimization
- Increase the storage capacity of the TS-932PX with QNAP TR RAID expansion enclosures or TL JBOD Alpine AL-324 1.7GHz, 4 GB DDR4, 512 MB, 5x 3.5, 4x 2.5", 2x 2.5G LAN, 2x 10G SFP+, 3x USB 3.2, 182.7x224.6x224.1 mm

| Storage | | Design | |
|--|--|--|---|
| Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays | Serial ATA III 2.5,3.5" | Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators Cable lock slot Cable lock slot type | Tower Active Black 1 fan(s) 14 cm HDD, LAN, SSD, Status, USB ✓ Kensington |
| Supported file systems | FAT32, HFS+, NTFS, ext3, ext4 | Performance | |
| Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type * Supported storage drive types * Bad block scan | HDD HDD & SSD ✓ | Type * Device class * Backup function * Backup features Buzzer Multilingual support Snapshot | NAS Small & Medium Business Cloud, iSCSI LUN |
| Disk roaming | 1 | Web-based management | 1 |
| Processor Processor manufacturer * Processor family * Processor model * Processor frequency * Processor architecture Memory Internal memory type Maximum RAM supported | Annapurna Labs Annapurna Labs Alpine AL-324 1.7 GHz ARM Cortex-A57 DDR4 16 GB | Security algorithms Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported System log | 256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH, SSL/TLS Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+, Mozilla Firefox |
| Memory slots Internal memory * Memory form factor Flash memory | 1 4 GB SO-DIMM 512 MB | Hot spare S.M.A.R.T. support Share folder USB copy function | ✓ ✓ CIFS/SMB |
| Network | | Software | |
| Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) DHCP client | 100,1000,2500,10000 Mbit/s 10000 Mbit/s | Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported | QNAP Turbo System 4.4.2 Windows 10, Windows 7, Windows 8 |
| DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready | * * * * * * * * * * * * * * * * * * * | Mac operating systems supported | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina |

| Network | | Software | |
|--|---|---|--|
| Supported network protocols Link aggregation Load balancing system Dynamic DNS (DDNS) WLAN adapter supported | Gen 1) Type-A 2 3 4 Server operating systems sup Power Power Power supply location Power supply unit (PSU) capace Number of power supply units AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * Packaging content External power adapter Operational conditions Operating temperature (T-T) | Server operating systems supported | Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 |
| | | Power | |
| | | Power supply location | External |
| Ports & interfaces | | Power supply unit (PSU) capacity | |
| USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports * | | AC input voltage | 1 100 - 240 V 12 V |
| | | Weight & dimensions | |
| | | Depth * | 224.6 mm 224.1 mm 182.7 mm |
| | | Packaging content | |
| | | External power adapter | ✓ |
| | | Operational conditions | |
| | | Operating temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C 5 - 95% |

