



LevelOne RJ45 to SC Fast Ethernet Media Converter, Multi-Mode Fiber, 2km

Brand : LevelOne

Product code: FVT-2001

Product name : RJ45 to SC Fast Ethernet Media Converter, Multi-Mode Fiber, 2km

1 x 10/100Base-TX, 1 x 100Base-FX, SC, 1310nm, 2 km, 420 g

LevelOne RJ45 to SC Fast Ethernet Media Converter, Multi-Mode Fiber, 2km. Maximum data transfer rate:

100 Mbit/s, Converter input interface: 10Base-T, 100Base-TX, Converter output interface: 100Base-FX.

Fiber optic connector: SC, Connectivity technology: Wired. Maximum transfer distance: 2000 m,

Wavelength: 1310 nm, Fiber mode structure: Multi-mode. LED indicators: Activity, Link, Product colour:

Black, Country of origin: China. Input voltage: 5 V, Input current: 1 A



Network		Design	
Maximum data transfer rate *	100 Mbit/s	LED indicators	Activity, Link
Converter input interface	10Base-T, 100Base-TX	Product colour	Black
Converter output interface	100Base-FX	Country of origin	China
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Certification	FCC, CE
Ethernet interface type	Fast Ethernet	Power	
Ethernet LAN data rates	10,100 Mbit/s	Input voltage	5 V
Flow control support	✓	Input current	1 A
Auto MDI/MDI-X	✓	Weight & dimensions	
Auto-negotiation	✓	Width	94 mm
Store-and-forward	✓	Depth	70 mm
Duplex system	Full, Half	Height	25 mm
Link Loss Carry Forward (LLCF) supported	✓	Weight	420 g
Link Loss Return (LLR) supported	✓	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	40 - 75 °C
Connectivity technology	Wired	Storage temperature (T-T)	-10 - 55 °C
Ethernet LAN (RJ-45) ports	1	Operating relative humidity (H-H)	5 - 90%
Fiber optic connector *	SC	Packaging data	
Power over Ethernet (PoE) ports quantity	1	Package width	235 mm
DC-in jack	✓	Package depth	125 mm
Package height		Package height	55 mm
Performance		Package weight	494 g
Maximum transfer distance *	2000 m	Package type	Box
Wavelength *	1310 nm	Packaging content	
Fiber mode structure	Multi-mode	AC adapter included	✓
Fiber cable diameters supported (core/cladding)	50/125,62.5/125 µm	Quick installation guide	✓
Design		Technical details	
Internal *	✗	Sustainability certificates	RoHS
		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	85176990



4015867185131



5050914863159




4052305869123



4015867225462



0846359031261



846359031261



8463590312618

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.