

QNAP TS-932PX-4G NAS Tower Ethernet LAN Black Alpine AL-324





Brand: QNAP **Product code**: TS-932PX-4G/30TB-IWP

Product name: TS-932PX-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports empower bandwidth-demanding tasks and accelerate file sharing
- HBS provides comprehensive backup and data recovery; QuDedup deduplicates the data at the source to optimize storage and bandwidth usage, while reducing backup times
- Snapshots record your system status, allowing you to protect files and data from accidental deletion and malware attacks
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
- Qtier auto-tiering technology and SSD caching enable constant storage optimization
- Increase the storage capacity of the TS-932PX with QNAP TR RAID expansion enclosures or TL JBOD Alpine AL-324 1.7GHz, 4 GB DDR4, 512 MB, 5x 3.5, 4x 2.5", 2x 2.5G LAN, 2x 10G SFP+, 3x USB 3.2, 182.7x224.6x224.1 mm

Storage		Design	
Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays	Serial ATA III 2.5,3.5" ✓ 0, 1, 5, 6, 10, 50, 60, JBOD ✓ ✓	Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators Cable lock slot Cable lock slot type	Tower Active Black 1 fan(s) 14 cm HDD, LAN, SSD, Status, USB ✓ Kensington
Supported file systems	FAT32, HFS+, NTFS, ext3, ext4	Performance	3
Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type * Supported storage drive types *	30 TB 9 HDD HDD & SSD	Type * Device class * Backup function * Backup features Buzzer	NAS Small & Medium Business Cloud, iSCSI LUN
Bad block scan	✓	Multilingual support	1
Disk roaming	1	Snapshot Web-based management	1
Processor Processor manufacturer *	Annapurna Labs	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSH, SSL/TLS
Processor family * Processor model * Processor frequency * Processor architecture	Annapurna Labs Alpine AL-324 1.7 GHz ARM Cortex-A57	Access Control List (ACL) Reset button On/off switch Built-in FTP server	√ √ √
Memory			Apple Safari 7+, Google Chrome,
Internal memory type Maximum RAM supported Memory slots Internal memory * Memory form factor Flash memory	DDR4 16 GB 1 4 GB SO-DIMM 512 MB	System log Hot spare S.M.A.R.T. support Share folder USB copy function	Microsoft Internet Explorer 10+, Mozilla Firefox ✓ ✓ CIFS/SMB
Network		Software	
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max)	100,1000,2500,10000 Mbit/s 10000 Mbit/s	Operating system installed * Operating system version Windows operating systems supported	QNAP Turbo System 4.4.2 Windows 10, Windows 7, Windows 8
DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready	4 4 4 4 4 4	Linux operating systems supported Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina

Network		Software	
Supported network protocols Link aggregation Load balancing system Dynamic DNS (DDNS) WLAN adapter supported	GBEIT Server operating system Power Power Power Power supply location Power supply unit (PSU) Number of power supply AC input voltage Fan voltage Weight & dimensions Width * Depth * Height * Packaging content External power adapter Operational condition Operating temperature	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Power	
		Power supply location	External
Ports & interfaces		Power supply unit (PSU) capacity	120 W
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports *			1 100 - 240 V 12 V
		Weight & dimensions	
		Depth *	224.6 mm 224.1 mm 182.7 mm
		Packaging content	
		External power adapter	✓
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

