

QNAP TVS-672XT NAS Tower Ethernet LAN Black i3-8100T





Brand: QNAP

Product code: TVS-672XT-I3-8G-48TB-EXOS

Product name: TVS-672XT

Intel Core i3-8100T 3.1 GHz, DDR4 SODIMM, 4 GB Flash, Intel UHD Graphics 630, 6 x 3.5" SATA, 2 x M.2, 1 x 10GBASE-T RJ45, 1 x USB 3.0, 2 x Type-C USB 3.1 Gen2, 2 x Type-A USB 3.1 Gen2, 1 x HDMI 2.0, 250W

QNAP TVS-672XT. Total installed storage capacity: 48 TB, Installed storage drive type: HDD, Supported storage drive types: HDD & SSD. Processor family: Intel® Core™ i3, Processor manufacturer: Intel, Processor model: i3-8100T. Internal memory: 8 GB, Internal memory type: DDR4, Maximum RAM supported: 32 GB. Ethernet LAN data rates: 10,100,1000,1200,2500,5000,10000 Mbit/s, Ethernet LAN data rate supported (max): 10000 Mbit/s, Supported network protocols: TCP/IP, IPv4, IPv6. On-board graphics card base frequency: 350 MHz, On-board graphics card dynamic frequency (max): 1100 MHz, On-board graphics card ID: 0x3E91

Storage		Design	
Supported storage drive interfaces	M.2, Serial ATA III	Built-in display	✓
Storage drive sizes supported	2.5,3.5,M.2	Cable lock slot	✓
Number of M.2 (M & B) slots	2	Cable lock slot type	Kensington
RAID support *	✓	Built-in speaker(s)	✓
RAID levels	0, 1, 5, 6, 10, 50, JBOD	Number of built-in speakers	1
Online RAID migration	✓	Performance	
Online RAID expansion	✓	Type *	NAS
Hot-swap drive bays	✓	Device class *	Home & Home Office
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4	Backup function *	✓
Storage drives installed *	✓	Backup features	iscsi lun
Total installed storage capacity *	48 TB	Buzzer	✓
Number of storage drives supported	^d 6	Multilingual support	✓
*	•	Noise level	23.8 dB
Installed storage drive type *	HDD	Snapshot	✓
Supported storage drive types *	HDD & SSD	Management protocols	SNMP 2/3
Auto-rebuild	✓	Web-based management	✓
Bad block scan Disk roaming	1	Share folder access right management	✓
Processor		Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH
		Access Control List (ACL)	✓
Processor manufacturer *	Intel	Reset button	✓
Processor generation	8th gen Intel® Core™ i3	On/off switch	✓
Processor family *	Intel® Core™ i3	Built-in iTunes server	✓
Processor model *	i3-8100T	Built-in FTP server	✓
Processor frequency *	3.1 GHz	Drawaar supported	Apple Safari 7, Google Chrome,
Processor cores Processor threads	4	Browser supported	Microsoft Internet Explorer 10, Mozilla Firefox
Processor cache	6 MB	System log	✓
Bus type	DMI3	Hot spare	✓
Configurable TDP-down frequency	2.4 GHz	S.M.A.R.T. support	✓
CPU configuration (max)	1	Share folder	CIFS/SMB
ECC supported by processor	✓	Universal Plug and Play (UPnP)	✓
PCI Express configurations	1x16, 1x8+2x4, 2x8	Software	
PCI Express slots version	3.0	Operating system installed *	QNAP Turbo System
Processor cache type	Smart Cache	Operating system version	4.4.0
Processor code	SR3Y8	3.,	
Processor codename	Coffee Lake		
Processor lithography	14 nm		
Processor operating modes	64-bit		
Processor package size	37.5 x 37.5 mm		
Processor socket	LGA 1151 (Socket H4)		
Scalability	1S		
Stepping	В0		

		0.6	
Processor		Software	
System bus rate Tjunction Thermal Design Power (TDP) On-board graphics card model Maximum internal memory supported by processor Memory bandwidth supported by processor (max) Memory Internal memory type Maximum RAM supported Memory slots Internal memory * Flash memory	8 GT/s 82 °C 35 W Intel® UHD Graphics 630 64 GB 37.5 GB/s DDR4 32 GB 2 x SO-DIMM 8 GB 4000 MB	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8, Windows 8, Windows 9,
Network			Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows
Ethernet LAN *	10 100 1000 1200 2500 5000 10000		8 x64
Ethernet LAN data rates	10,100,1000,1200,2500,5000,10000 Mbit/s	Linux operating systems supported	Mac OS V 10 10 Vacamita Mac OS V
Ethernet LAN data rate supported (max) Wi-Fi DHCP client DHCP server Jumbo frames support iSCSI support	10000 Mbit/s X ✓	Mac operating systems supported Server operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks Windows Server 2003, Windows Server 2012, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Wake-on-LAN ready	✓		Windows Server 2016
Supported network protocols Link aggregation	TCP/IP, IPv4, IPv6 ✓	Power	
Load balancing system	7	Power supply unit (PSU) capacity	250 W
Dynamic DNS (DDNS)	√	AC input voltage Fan voltage	100 - 240 V 12 V
WLAN adapter supported	✓	Weight & dimensions	12 4
Ports & interfaces		Width *	264.3 mm
USB port *	✓	Depth *	279.6 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	1	Height *	188.2 mm
ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-A		Packaging content	
ports quantity	2	Cables included	AC, LAN (RJ-45)
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Quick installation guide	✓
HDMI ports quantity	1	Processor special features	
HDMI version	2.0	Embedded options available	✓
Ethernet LAN (RJ-45) ports *	3	Enhanced Intel SpeedStep	✓
Thunderbolt 3 ports quantity 3.5 mm (1/8-inch) out	2	Technology Execute Disable Bit	/
PCI Express x4 (Gen 3.x) slots	1	Idle States	V
Microphone in	1	Intel 64	✓
Graphics		Intel Clear Video Technology	√
On-board graphics card base	250 MH-	Intel Enhanced Halt State	✓
frequency	350 MHz	Intel Identity Protection Technology version	1.00
On-board graphics card dynamic frequency (max)	1100 MHz	Intel Secure Key Technology version	
On-board graphics card DirectX version	12.0	Intel Stable Image Platform Program (SIPP)	^
On-board graphics card OpenGL version	4.5	Intel Stable Image Platform Program (SIPP) version	0.00
On-board graphics card ID	0x3E91		X
Maximum on-board graphics card	64 GB	Intel TSX-NI	0.00
memory	V-7 VID	Intel TSX-NI version Intel Virtualization Technology (VT-	0.00
Number of displays supported (on- board graphics)	3	x)	1
		Intel Virtualization Technology for Directed I/O (VT-d)	✓

Design		Processor special features	
Cooling type * Active Product colour Black Number of fans 4 fan Fan diameter 9.2 cr Fan diameter 2 6 cm	Tower	Intel VT-x with Extended Page Tables (EPT)	1
	Black 4 fan(s) 9.2 cm	Intel® AES New Instructions (Intel® AES-NI)	1
		Intel® Clear Video HD Technology (Intel® CVT HD)	1
		Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID)	√
		Intel® Hyper Threading Technology (Intel® HT Technology)	×
		Intel® Identity Protection Technology (Intel® IPT)	✓
		Intel® InTru™ 3D Technology	✓
		Intel® OS Guard	✓
		Intel® Quick Sync Video Technology	✓
		Intel® Secure Key	✓
		Intel® Smart Cache	✓
		Intel® Turbo Boost Technology	×
		Maximum number of PCI Express lanes	16
		Thermal Monitoring Technologies	✓
		Thermal solution specification	PCG 2015A
		Memory channels supported by processor	Dual
		Memory types supported by processor	DDR4-SDRAM
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Other features	
		Digital Living Network Alliance (DLNA) certified	✓
		Processor ARK ID	129944

