## QNAP

## QNAP TS-832PXU-RP-4G NAS Rack (2U) Ethernet LAN Black AL324

**Brand :** QNAP **Product code:** TS-832PXU-RP-4G/32TB-REDPLUS

Product name: TS-832PXU-RP-4G



- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing
- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning
- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of Google G Suite and Microsoft 365
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks
- Expand the application potential of the TS-832PXU-RP by installing a compatible PCIe card
- Increase the storage capacity of the TS-832PXU-RP with QNAP TR RAID expansion enclosures or TL JBOD

8x 3.5", 4GB DDR4, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 2x 250W PSU, 89x482x534 mm



Storage		Design	
Storage drive sizes supported  RAID support *  RAID levels  Online RAID migration  Online RAID expansion  RAID rebuild  Hot-swap drive bays  Supported file systems  Storage drives installed *  Total installed storage capacity *  Number of storage drives installed *  Number of storage drives supported  *  Installed storage drive type *  Supported storage drive types *  HDI  Supported storage drive types *	0, 1, 5, 6, 10, JBOD      FAT32, HFS+, NTFS, ext3, ext4   32 TB  8  HDD  HDD & SSD	Chassis type * Cooling type * Product colour Fan diameter Fan diameter 2 LED indicators	Rack (2U) Active Black 2 mm 7 cm HDD, LAN, Status
		Performance  Type * Device class * Backup function * Backup features Buzzer Multilingual support Snapshot Web-based management	NAS Small & Medium Business  ✓ Cloud, iSCSI LUN  ✓ ✓ ✓ 256-bit AES, FIPS 140-2, HTTPS,
Bad block scan  Processor	<b>√</b>	Security algorithms Access Control List (ACL)	SSH, SSL/TLS
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor cores	Annapurna Labs Annapurna Labs AL324 1.7 GHz	Reset button On/off switch Built-in FTP server Browser supported	✓ ✓ Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+,
Memory		System log	Google Chrome
Internal memory type Maximum RAM supported Memory slots Internal memory * Memory form factor Flash memory	DDR4 16 GB 1 4 GB UDIMM 512 MB	Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP) USB copy function	√ ✓ CIFS/SMB ✓
Network	312 116	Software	ONART de Calera
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) DHCP client DHCP server Jumbo frames support	100,1000,2500,10000 Mbit/s 10000 Mbit/s	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported Mac operating systems supported	QNAP Turbo System 4.4.3 Windows 10, Windows 7, Windows 8  Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina

Network		Software	
Wake-on-LAN ready Supported network protocols Link aggregation Load balancing system WLAN adapter supported  Ports & interfaces  USB port *  USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector	PPTP, L2TP/IPSec, OpenVPN, QBelt	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Power	
		Power supply location Power supply unit (PSU) capacity Number of power supply units	Built-in 250 W
	✓		2
	4 2 SFP+	AC input voltage	100 - 240 V
		Fan voltage	12 V
		Weight & dimensions	
Ethernet LAN (RJ-45) ports *	2	Width *	482 mm
		Depth *	534 mm
		Height *	89 mm
		Packaging content	
		Cables included	AC, LAN (RJ-45)
		Number of screws	56
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%

