QNAP TVS-472XT-I3-4G/48TB-GOLD NAS/storage server Tower Ethernet LAN Black i3-8100T

Brand : QNAP

Maximum RAM supported

64 GB

Product code: TVS-472XT-I3-4G/48TB-GOLD

××

×

Product name : TVS-472XT-I3-4G/48TB-GOLD

- High-speed Thunderbolt 3 with SMB protocol, allowing Mac and Windows users to collaborate on media editing

- 5-speed 10GBASE-T RJ45 connectivity accelerates virtualization applications and file sharing across teams and devices

- PCle expandability allows for graphics cards or 40GbE/ 25GbE/ 10GbE adapters to increase application performance

- Install M.2 PCIe (Gen 3 x2, 2 GB/s) NVMe SSDs (sold separately) to set up caching or storage pools, improving file access efficiency

- 4K media playback and real-time transcoding; directly view creative works on an HDTV via HDMI 2.0 (4K @60Hz) output

- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks

Intel Core i3-8100T, 4 GB DDR4, 4x 3.5", 2x M.2, RJ-45, Thunderbolt, PCIe, USB 3.2, HDMI, 188.2×199.3×279.6 mm

| Storage | | Design | |
|--|---|---|--|
| Supported storage drive interfacesSeStorage drive size2.Storage drive sizes supported2.Number of system drives installed1 | Serial ATA II, Serial ATA III Serial ATA II, Serial ATA III 2.5/3.5" 2.5,3.5" 1 5 GB | Fan diameter 2 LED indicators Built-in display Display type Cable lock slot Cable lock slot type | 6 cm HDD, LAN, Status, USB ✓ LCD ✓ Kensington |
| Number of M.2 (M & B) slots | 2 | Performance | |
| RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive types * | | Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Security algorithms Access Control List (ACL) Reset button On/off switch Built-in FTP server | NAS Small & Medium Business Cloud, iSCSI LUN 21.2 dB 256-bit AES, HTTPS, SSL/TLS Mozilla Firefox, Microsoft Edge, |
| Processor | | Browser supported | Google Chrome, Apple Safari |
| Processor manufacturer * Processor generation Processor family * Processor model * Processor frequency * | Intel 8th gen Intel® Core™ i3 Intel® Core™ i3 i3-8100T 3.1 GHz | System log Hot spare S.M.A.R.T. support Share folder USB copy function | ✓ ✓ CIFS/SMB ✓ |
| Processor cores | 4 | Software | |
| Processor threads Processor cache Bus type Configurable TDP-down frequency CPU configuration (max) Number of processors supported On-board graphics card model | 4 6 MB DMI3 requency 2.4 GHz 1 pported 1 | Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported | QNAP Turbo System 4.4.0 Windows 10, Windows 7, Windows 8 |
| Memory | | | |
| Internal memory type | DDR4 | | |

| Memory | | Software | |
|---|---------------------------------------|--|--|
| Memory slots Internal memory * Memory form factor Flash memory | 2 4 GB SO-DIMM 5000 MB | Mac operating systems supported | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac |
| Network | | | OS X 10.8 Mountain Lion, Mac OS X |
| Ethernet LAN * | < | | 10.9 Mavericks, Mac OS X 11.0 Big Sur |
| Ethernet LAN data rates | 10,100,1000,2500,5000,10000 Mbit/s | | Windows Server 2003, Windows |
| Ethernet LAN data rate supported (max) | 10000 Mbit/s | Server operating systems supported | Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016 |
| DHCP client | 4 | Power | |
| DHCP server | | Power supply location | Built-in |
| Jumbo frames support iSCSI support | 4 | Power supply unit (PSU) capacity | 250 W |
| Wake-on-LAN ready | 4 | Number of power supply units | 1 |
| Link aggregation | , , | Power consumption (typical) | 37.32 W |
| Load balancing system | 4 | Power consumption (sleep) | 24.14 W |
| Dynamic DNS (DDNS) | 4 | AC input voltage | 100-240 V |
| WLAN adapter supported | 1 | Fan voltage | 12 V |
| Ports & interfaces | | Weight & dimensions | |
| USB port * | 1 | Width * | 199.3 mm |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A | 1 | Depth * | 279.6 mm |
| ports quantity | I | Height * | 188.2 mm |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 2 | Weight | 5.4 kg |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C | 2 | Packaging content | |
| ports quantity | Z | Cables included | AC, LAN (RJ-45) |
| HDMI ports quantity | 1 | Power cables quantity | 1 |
| HDMI version Ethernet LAN (RJ-45) ports * | 2.0 3 | Processor special features | |
| Thunderbolt 3 ports quantity | 2 | Embedded options available | ✓ |
| PCI Express x4 (Gen 3.x) slots | 1 | Enhanced Intel SpeedStep Technology | 4 |
| Design | | Execute Disable Bit | 1 |
| Chassis type * | Tower | Idle States | 4 |
| Cooling type * | Active | Intel 64 | |
| Product colour | Black | Intel Clear Video Technology | |
| Number of fans | 3 fan(s) | Intel Enhanced Halt State | √ |
| Fan diameter | 12 cm | Intel Identity Protection Technology version | 1.00 |
| | | Intel Secure Key Technology version | |
| | | Intel Stable Image Platform Program (SIPP) | |
| | | Intel Stable Image Platform Program (SIPP) version | 0.00 |
| | | | × |
| | | Intel TSX-NI | × |
| | | Intel TSX-NI version | 0.00 |
| | | Intel Virtualization Technology (VT- x) | 4 |
| | | Intel Virtualization Technology for Directed I/O (VT-d) | 4 |
| | | Intel VT-x with Extended Page Tables (EPT) | 4 |
| | | Operational conditions | |
| | | Operating temperature (T-T) | 0 - 40 °C |
| | | Operating relative humidity (H-H) | 5 - 95% |
| | | Storage temperature (T-T) | -20 - 70 °C |
| | | | |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.