

## **QNAP TVS-672XT NAS Tower Ethernet LAN Black i3-8100T**





**Brand**: QNAP Product code: TVS-672XT-I3-8G-36TB-EXOS

**Product name:** TVS-672XT



Intel Core i3-8100T 3.1 GHz, DDR4 SODIMM, 4 GB Flash, Intel UHD Graphics 630, 6 x 3.5" SATA, 2 x M.2, 1 x 10GBASE-T RJ45, 1 x USB 3.0, 2 x Type-C USB 3.1 Gen2, 2 x Type-A USB 3.1 Gen2, 1 x HDMI 2.0, 250W

QNAP TVS-672XT. Total installed storage capacity: 36 TB, Installed storage drive type: HDD, Supported storage drive types: HDD & SSD. Processor family: Intel® Core™ i3, Processor manufacturer: Intel, Processor model: i3-8100T. Internal memory: 8 GB, Internal memory type: DDR4, Maximum RAM supported: 32 GB. Ethernet LAN data rates: 10,100,1000,1200,2500,5000,10000 Mbit/s, Ethernet LAN data rate supported (max): 10000 Mbit/s, Supported network protocols: TCP/IP, IPv4, IPv6. On-board graphics card base frequency: 350 MHz, On-board graphics card dynamic frequency (max): 1100 MHz, On-board graphics card ID: 0x3E91

Storage		Design	
Supported storage drive interfaces Storage drive sizes supported Number of M.2 (M & B) slots RAID support * RAID levels	M.2, Serial ATA III 2.5,3.5,M.2 2  ✓ 0, 1, 5, 6, 10, 50, JBOD	Built-in display Cable lock slot Cable lock slot type Built-in speaker(s) Number of built-in speakers	✓ ✓ Kensington ✓ 1
Online RAID migration	✓	Performance	
Online RAID expansion Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type *	HDD	Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Snapshot	NAS Home & Home Office  ISCSI LUN  23.8 dB
Supported storage drive types * Auto-rebuild Bad block scan Disk roaming	HDD & SSD  ✓  ✓	Management protocols Web-based management Share folder access right management	SNMP 2/3
Processor		Security algorithms Access Control List (ACL)	256-bit AES, FIPS 140-2, HTTPS, SSH
Processor manufacturer * Processor generation Processor family * Processor model * Processor frequency * Processor cores	Intel 8th gen Intel® Core™ i3 Intel® Core™ i3 i3-8100T 3.1 GHz	Reset button On/off switch Built-in iTunes server Built-in FTP server  Browser supported	Apple Safari 7, Google Chrome, Microsoft Internet Explorer 10, Mozilla Firefox
Processor threads Processor cache	4 6 MB	System log	✓
Bus type Configurable TDP-down frequency CPU configuration (max) ECC supported by processor	DMI3 2.4 GHz 1	Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP)	✓ ✓ CIFS/SMB ✓
PCI Express configurations	1x16, 1x8+2x4, 2x8	Software	
PCI Express slots version Processor cache type Processor code Processor codename Processor lithography Processor operating modes Processor package size Processor socket Scalability Stepping	3.0 Smart Cache SR3Y8 Coffee Lake 14 nm 64-bit 37.5 x 37.5 mm LGA 1151 (Socket H4) 1S B0	Operating system installed * Operating system version	QNAP Turbo System 4.4.0

		0.6	
Processor		Software	
System bus rate Tjunction Thermal Design Power (TDP) On-board graphics card model Maximum internal memory supported by processor Memory bandwidth supported by processor (max)  Memory Internal memory type Maximum RAM supported Memory slots Internal memory * Flash memory	8 GT/s 82 °C 35 W Intel® UHD Graphics 630 64 GB 37.5 GB/s  DDR4 32 GB 2 x SO-DIMM 8 GB 4000 MB	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8, Windows 8, Windows 9,
Network			Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows
Ethernet LAN *	10 100 1000 1200 2500 5000 10000		8 x64
Ethernet LAN data rates	10,100,1000,1200,2500,5000,10000 Mbit/s	Linux operating systems supported	Mac OS V 10 10 Vacamita Mac OS V
Ethernet LAN data rate supported (max) Wi-Fi DHCP client DHCP server Jumbo frames support iSCSI support	10000 Mbit/s  X  ✓	Mac operating systems supported  Server operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks Windows Server 2003, Windows Server 2012, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Wake-on-LAN ready	<b>7</b>		Windows Server 2016
Supported network protocols  Link aggregation	TCP/IP, IPv4, IPv6 ✓	Power	
Load balancing system	7	Power supply unit (PSU) capacity	250 W
Dynamic DNS (DDNS)	<b>√</b>	AC input voltage Fan voltage	100 - 240 V 12 V
WLAN adapter supported	✓	Weight & dimensions	12 4
Ports & interfaces		Width *	264.3 mm
USB port *	✓	Depth *	279.6 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	1	Height *	188.2 mm
ports quantity USB 3.2 Gen 2 (3.1 Gen 2) Type-A		Packaging content	
ports quantity	2	Cables included	AC, LAN (RJ-45)
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Quick installation guide	✓
HDMI ports quantity	1	Processor special features	
HDMI version	2.0	Embedded options available	✓
Ethernet LAN (RJ-45) ports *	3	Enhanced Intel SpeedStep	✓
Thunderbolt 3 ports quantity 3.5 mm (1/8-inch) out	2	Technology  Execute Disable Bit	/
PCI Express x4 (Gen 3.x) slots	1	Idle States	<b>V</b>
Microphone in	1	Intel 64	✓
Graphics		Intel Clear Video Technology	<b>√</b>
On-board graphics card base	250 MH-	Intel Enhanced Halt State	✓
frequency	350 MHz	Intel Identity Protection Technology version	1.00
On-board graphics card dynamic frequency (max)	1100 MHz	Intel Secure Key Technology version	
On-board graphics card DirectX version	12.0	Intel Stable Image Platform Program (SIPP)	^
On-board graphics card OpenGL version	4.5	Intel Stable Image Platform Program (SIPP) version	0.00
On-board graphics card ID	0x3E91		X
Maximum on-board graphics card	64 GB	Intel TSX-NI	0.00
memory	V-7 VID	Intel TSX-NI version Intel Virtualization Technology (VT-	0.00
Number of displays supported (on- board graphics)	3	x)	✓
		Intel Virtualization Technology for Directed I/O (VT-d)	✓

Design		Processor special features	
Cooling type * Acti Product colour Blac Number of fans 4 fa Fan diameter 9.2 Fan diameter 2 6 cr	Tower Active Black 4 fan(s) 9.2 cm 6 cm HDD, LAN, Status, USB	Intel VT-x with Extended Page Tables (EPT)	1
		Intel® AES New Instructions (Intel® AES-NI)	1
		Intel® Clear Video HD Technology (Intel® CVT HD)	1
		Intel® Clear Video Technology for Mobile Internet Devices (Intel CVT for MID)	<b>√</b>
		Intel® Hyper Threading Technology (Intel® HT Technology)	×
		Intel® Identity Protection Technology (Intel® IPT)	✓
		Intel® InTru™ 3D Technology	✓
		Intel® OS Guard	✓
		Intel® Quick Sync Video Technology	✓
		Intel® Secure Key	✓
		Intel® Smart Cache	✓
		Intel® Turbo Boost Technology	×
		Maximum number of PCI Express lanes	16
		Thermal Monitoring Technologies	✓
		Thermal solution specification	PCG 2015A
		Memory channels supported by processor	Dual
		Memory types supported by processor	DDR4-SDRAM
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Other features	
		Digital Living Network Alliance (DLNA) certified	✓
		Processor ARK ID	129944

