## QNAP

## QNAP TL-D1600S HDD/SSD enclosure Black, Grey 2.5/3.5"

Brand: QNAP Product code: TL-D1600S/224TB-GOLD

**Product name:** TL-D1600S

- Lockable hard drive trays prevent accidental drive removal
- SFF-8088 (or SFF-8644) connection cable supports four SATA 6Gb/s channels per cable (24Gb/s in total) and provides faster data transfer speeds than eSATA and USB
- Easy to use. QNAP NAS and PC can both use utility software to monitor, obtain, and manage JBOD information

12x 3.5" + 4x 2.5" SATA, 4x SFF-8088, 303.8x369.9x319.8 mm

QNAP TL-D1600S. Product type: HDD/SSD enclosure. Number of storage drives supported: 16, Storage drive size: 2.5/3.5", Supported storage drive interfaces: Serial ATA II, Serial ATA III. Data transfer rate: 6 Gbit/s. Total installed storage capacity: 224 TB, Hot-swap. Display type: LCD, Product colour: Black, Grey





| Storage   |   | Design  |                                  |
|---|---|---|----------------------------------|
| Number of storage drives supported  | <sup>1</sup> 16                                   | Display type  | LCD                              |
| Storage drive size * Supported storage drive interfaces * Number of storage drives installed Total installed storage capacity | 2.5/3.5" Serial ATA II, Serial ATA III 16 224 TB  | Performance   |                                  |
|   |   | Data transfer rate<br>Noise level                             | 6 Gbit/s<br>25 dB                |
|   |   | Power   |                                  |
| Hot-swap  | ✓   | Power source type   | AC                               |
| Ports & interfaces  |   | AC adapter input voltage                                      | 100 - 240 V                      |
| USB connectivity *  | ×   | AC adapter frequency  | 50/60 Hz                         |
| Design  |   | Operational conditions  |                                  |
| Product type * Product colour * LED indicators On/off switch Number of fans Fan diameter Built-in display                     | HDD/SSD enclosure Black, Grey Fan fail, HDD, Link | Operating temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C<br>5 - 95%             |
|   |   | Weight & dimensions   |                                  |
|   |   | Width<br>Depth<br>Height                                      | 369.9 mm<br>319.8 mm<br>303.8 mm |
|   |   | Packaging content   |                                  |
|   |   | Cables included<br>Screws included<br>Manual                  | AC, MiniSAS                      |

