

QNAP TS-1677XU-RP NAS Rack (3U) Ethernet LAN Black 2600

Brand : QNAP

Product code: TS-1677XU-RP-2600-8G-128TB-REDP

Product name : TS-1677XU-RP



3U, AMD Ryzen 5 2600 3.4 GHz, 8 GB DDR4, 16x 3.5", SATA 6 Gbps, 2x 10GbE SFP+, 2x RJ45, USB 3.1, USB 3.0, 4x PCIe, 100-240V AC, 50/60Hz, 2x 500W, QTS 4.3.4
 QNAP TS-1677XU-RP. Total installed storage capacity: 128 TB, Installed storage drive type: HDD, Supported storage drive types: HDD & SSD. Processor family: AMD Ryzen™ 5, Processor frequency: 3.4 GHz, Processor boost frequency: 3.9 GHz. Internal memory: 8 GB, Internal memory type: DDR4, Maximum RAM supported: 64 GB. Ethernet LAN data rates: 10,100,1000,10000 Mbit/s, Ethernet LAN data rate supported (max): 10000 Mbit/s, Supported network protocols: TCP/IP, IPv4, IPv6, NAT, STP, SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP. Fiber optic connector: SFP+



Storage		Design	
Supported storage drive interfaces	Serial ATA III	Fan diameter 2	9.2 cm
Storage drive sizes supported	2.5,3.5"	LED indicators	✓
RAID support *	✓	Built-in display	✗
RAID levels	0, 1, 5, 6, 10, 50, JBOD	Performance	
Online RAID migration	✓	Type *	NAS
Online RAID expansion	✓	Device class *	Small & Medium Business
RAID rebuild	✓	Backup function *	✓
Hot-swap drive bays	✓	Backup features	Cloud, iSCSI LUN
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4	Multilingual support	✓
Storage drives installed *	✓	Third-party support	✓
Total installed storage capacity *	128 TB	Built-in optical drive	✗
Number of storage drives supported *	16	Card reader integrated	✗
Installed storage drive type *	HDD	Snapshot	✓
Supported storage drive types *	HDD & SSD	Management protocols	SNMP
Bad block scan	✓	Web-based management	✓
Disk roaming	✓	Share folder access right management	✓
Processor		Security algorithms	256-bit AES, FIPS 140-2
Processor family *	AMD Ryzen™ 5	Access Control List (ACL)	✓
Processor model *	2600	Built-in BitTorrent client	✓
Processor frequency *	3.4 GHz	Built-in iTunes server	✓
Processor boost frequency	3.9 GHz	Built-in FTP server	✓
Processor cores	4	Browser supported	Microsoft Internet Explorer 10, Mozilla Firefox, Google Chrome, Apple Safari 7+
Processor threads	4	System log	✓
CPU configuration (max)	1	Hot spare	✓
Processor operating modes	64-bit	Password authentication	✓
Memory		Disk scan	✓
Internal memory type	DDR4	S.M.A.R.T. support	✓
Maximum RAM supported	64 GB	Share folder	CIFS/SMB
Memory slots	4 DIMM	Universal Plug and Play (UPnP)	✓
Internal memory *	8 GB	Software	
Network		Operating system installed *	QNAP Turbo System
Ethernet LAN *	✓	Operating system version	4.3.4
Ethernet LAN data rates	10,100,1000,10000 Mbit/s	Windows operating systems supported	Windows 10, Windows 7, Windows 8

Network		Software	
Ethernet LAN data rate supported (max)	10000 Mbit/s	Linux operating systems supported	✓ Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Wi-Fi	✗	Mac operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
DHCP client	✓	Server operating systems supported	
DHCP server	✓		
Jumbo frames support	✓		
iSCSI support	✓		
Wake-on-LAN ready	✓		
Supported network protocols	TCP/IP, IPv4, IPv6, NAT, STP, SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP		
Dynamic DNS (DDNS)	✓		
Ports & interfaces		Power	
USB port *	✓	Power supply location	Built-in
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Power supply unit (PSU) capacity	500 W
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	1	Number of power supply units	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1	Redundant power supply (RPS) support	✓
Fiber ports quantity	2	AC input voltage	100 - 240 V
Fiber optic connector	SFP+	AC input frequency	50 - 60 Hz
Ethernet LAN (RJ-45) ports *	2	Fan voltage	12 V
PCI Express x4 (Gen 3.x) slots	2	Weight & dimensions	
PCI Express x8 (Gen 3.x) slots	2	Width *	481 mm
		Depth *	573.5 mm
		Height *	130 mm
Design		Packaging content	
Chassis type *	Rack (3U)	Cables included	AC, LAN (RJ-45)
Cooling type *	Active	Quick installation guide	✓
Product colour	Black	Number of screws	128
Number of fans	2 fan(s)	Technical details	
Fan diameter	9.2 cm	Sustainability certificates	RoHS
		Compliance certificates	RoHS
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Other features	
		Digital Living Network Alliance (DLNA) certified	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.