QNAP

QNAP TS-h686 NAS Tower Intel® Xeon® D D-1602 8 GB DDR4 8 TB HDD QuTS hero Black

Brand : QNAP **Product code:** TS-H686-D1602-8G/8TB-REDPLUS

Product name: TS-h686

Intel Xeon D-1602 (2x 2.5GHz), 8GB DDR4, 5GB Flash, 4x 2.5"/3.5" + 2x 2.5", 2x M.2, 4x 2.5G RJ-45, 3x USB 3.2 Gen1

QNAP TS-h686. Type: NAS. Chassis type: Tower. Device class: Home & Home Office. Processor family: Intel® Xeon® D, Processor model: D-1602, Processor frequency: 2.5 GHz. Internal memory: 8 GB, Internal memory type: DDR4. Total installed storage capacity: 8 TB, Installed storage drive type: HDD. Operating system installed: QuTS hero





Storage		Performance	
Storage drive capacity * Storage drive interface * Supported storage drive interfaces Storage drive sizes supported Number of M.2 (M & B) slots RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type *	2.5,3.5,M.2 2	Performance Backup function * Backup features Buzzer Multilingual support Noise level Snapshot Management protocols Web-based management Security algorithms Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported System log Hot spare S.M.A.R.T. support	Cloud, iSCSI LUN 18.6 dB SNMP 2/3 256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS Safari, Chrome, Internet Explorer, Firefox
Supported storage drive types * Bad block scan	HDD & SSD ✓	S.M.A.R.1. support Share folder	CIFS/SMB
Disk roaming	,	Universal Plug and Play (UPnP) USB copy function	/
Processor		.,	•
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency	Intel Intel® Xeon® D D-1602 2.5 GHz 3.2 GHz	Software Operating system installed * Operating system version Windows operating systems supported	QuTS hero h5.0.0 Windows 10, Windows 7, Windows 8
Processor boost frequency Processor cores Processor threads Processor cache CPU configuration (max)	3.2 GHZ 2 4 3 MB 1	Linux operating systems supported	CentOS 7.0, Ubuntu 14.04, openSUSE 12.1, openSUSE 12.2 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra,
Memory Internal memory * Internal memory type	8 GB DDR4	Mac operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura

Memory		Software	
Maximum RAM supported	128 GB	JoitWale	Windows Sarvar 2009 D2 Windows
Memory slots Memory form factor	4 UDIMM	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
ECC	✓ 5000 MB	Power	
Flash memory	5000 MB	Power supply location	Built-in
Network		Power supply unit (PSU) capacity	250 W
Ethernet LAN *	✓	Number of power supply units	1
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Power consumption (typical)	61.115 W
DHCP client	✓	AC input voltage	100 - 240 V
DHCP server	✓	Fan voltage	12 V
Jumbo frames support	/	Weight & dimensions	
iSCSI support	*	Width *	224.9 mm
Wake-on-LAN ready	✓	Depth *	319.8 mm
Dynamic DNS (DDNS)	✓	Height *	231.9 mm
Ports & interfaces		Packaging content	
USB port *	✓	Cables included	AC, LAN (RJ-45)
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	3	Power cables quantity Number of screws	1
ports quantity			24
Ethernet LAN (RJ-45) ports *	4	Drive tray key included	✓
PCI Express x8 (Gen 3.x) slots	2	Processor special features	
Design		Embedded options available	×
Chassis type * Cooling type *	Tower Active	Enhanced Intel SpeedStep Technology	•
Product colour	Black	Execute Disable Bit	✓
Number of fans	2 fan(s)	Idle States	✓
Fan diameter	9 cm	Intel 64	✓
Fan diameter 2	9.7 cm	Intel QuickAssist Technology	×
LED indicators	HDD, LAN, SSD, Status, USB	Intel Trusted Execution Technology	✓
Built-in display	X	Intel TSX-NI	✓
Cable lock slot Cable lock slot type	Kensington	Intel Virtualization Technology (VT-x)	✓
Performance		Intel Virtualization Technology for Directed I/O (VT-d)	✓
Type * Device class *	NAS Home & Home Office	Intel VT-x with Extended Page Tables (EPT)	•
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 5 - 95% -20 - 70 °C 5 - 95%
		Logistics data	
		Harmonized System (HS) code	84714100

