QNAP

QNAP TS-1232PXU-RP-4G NAS Rack (2U) Annapurna Labs AL324 4 GB DDR4 96 TB HDD QNAP Turbo System Black

Brand : QNAP **Product code:** TS-1232PXU-RP-4G/96TB-IW

Product name: TS-1232PXU-RP-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports accelerate file sharing
- HBS (Hybrid Backup Sync) backs up and syncs data to other NAS, servers and cloud storage for comprehensive disaster recovery planning
- Boxafe provides an extra layer of protection by backing up emails, cloud drives, contacts, and calendars of Google G Suite and Microsoft 365
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks
- Expand the application potential of the TS-1232PXU-RP by installing a compatible PCle card
- Increase the storage capacity of the TS-1232PXU-RP with QNAP TR RAID expansion enclosures or TL IBOD

12x 3.5", 4GB DDR4, Alpine AL324, 2.5G RJ-45, 10G SFP+, USB 3.2, 2x 250W PSU, 89x482x534 mm



	Design	
Serial ATA II, Serial ATA III 2.5,3.5" ✓ 0, 1, 5, 6, 10, JBOD ✓	Cooling type * Product colour Number of fans Fan diameter LED indicators	Active Black 2 fan(s) 7 cm HDD, LAN, Status
✓	Performance	
✓ ✓ FAT32, HFS+, NTFS, ext3, ext4 ✓ 96 TB 12	Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level	NAS Small & Medium Business ✓ Cloud, iSCSI LUN ✓ 32.2 dB
HDD HDD & SSD ✓	Snapshot Web-based management Security algorithms	✓ ✓ 256-bit AES, FIPS 140-2, HTTPS,
	Access Control List (ACL)	SSH, SSL/TLS ✓
Annapurna Labs Annapurna Labs AL324 1.7 GHz	Reset button On/off switch Built-in FTP server Browser supported	Mozilla Firefox, Microsoft Internet Explorer 10+, Apple Safari 7+,
	System log	Google Chrome
4 GB DDR4 16 GB 1 UDIMM	Hot spare S.M.A.R.T. support Share folder Universal Plug and Play (UPnP) USB copy function	✓ ✓ CIFS/SMB ✓
512 MB	Software	
100,1000,2500,10000 Mbit/s 10000 Mbit/s	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported	QNAP Turbo System 4.4.3 Windows 10, Windows 7, Windows 8
	2.5,3.5" 0, 1, 5, 6, 10, JBOD FAT32, HFS+, NTFS, ext3, ext4 96 TB 12 12 HDD HDD & SSD Annapurna Labs Annapurna Labs Annapurna Labs Al324 1.7 GHz 4 4 GB DDR4 16 GB 1 UDIMM 512 MB	2.5,3.5" Product colour Number of fans 0, 1, 5, 6, 10, JBOD Fan diameter LED indicators Performance Type * Device class * Backup features Buzzer Multilingual support 12 Noise level HDD Snapshot HDD Snapshot Web-based management Security algorithms Access Control List (ACL) Annapurna Labs Annapurna Labs Annapurna Labs Annapurna Labs Al 324 1.7 GHz 4 Browser supported System log 4 GB DDR4 5 S.M.A.R.T. support 5 GB DDR4 5 Share folder Universal Plug and Play (UPnP) UDIMM USB copy function 5 Operating system installed * Operating system version Windows operating systems supported Windows operating systems supported Windows operating systems supported

Network		Software	
iSCSI support	1	Sortware	Mac OS X 10.10 Yosemite. Mac OS X
Wake-on-LAN ready Supported network protocols Link aggregation	PPTP, L2TP/IPSec, OpenVPN, QBelt	Mac operating systems supported	10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Load balancing system WLAN adapter supported	4	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
Ports & interfaces			Server 2019
USB port *	✓	Power	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports *	4 2 SFP+ 2	Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) AC input voltage	Built-in 250 W 2 83.57 W 100 - 240 V
Design		Fan voltage	12 V
Chassis type *	Rack (2U)	Weight & dimensions	
		Width * Depth * Height * Weight	482 mm 534 mm 89 mm 11.3 kg
		Packaging content	
		Cables included Number of screws	AC, LAN (RJ-45) 84
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%

