

## QNAP TS-932PX-4G NAS Tower Ethernet LAN Black Alpine AL-324





Brand: QNAP Product code: TS-932PX-4G/60TB-IWP

Product name: TS-932PX-4G

- Two 10GbE SFP+ and two 2.5GbE RJ45 network ports empower bandwidth-demanding tasks and accelerate file sharing
- HBS provides comprehensive backup and data recovery; QuDedup deduplicates the data at the source to optimize storage and bandwidth usage, while reducing backup times
- Snapshots record your system status, allowing you to protect files and data from accidental deletion and malware attacks
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
- Qtier auto-tiering technology and SSD caching enable constant storage optimization
- Increase the storage capacity of the TS-932PX with QNAP TR RAID expansion enclosures or TL JBOD Alpine AL-324 1.7GHz, 4 GB DDR4, 512 MB, 5x 3.5, 4x 2.5", 2x 2.5G LAN, 2x 10G SFP+, 3x USB 3.2, 182.7x224.6x224.1 mm

| Storage  |   | Design   |   |
|--|---|--|---|
| Supported storage drive interfaces Storage drive sizes supported RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays | Serial ATA III  2.5,3.5"  ✓  0, 1, 5, 6, 10, 50, 60, JBOD  ✓  ✓ | Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators Cable lock slot Cable lock slot type | Tower Active Black 1 fan(s) 14 cm HDD, LAN, SSD, Status, USB  ✓ Kensington  |
| Supported file systems   | FAT32, HFS+, NTFS, ext3, ext4                                   | Performance  | g.c   |
| Storage drives installed * Total installed storage capacity * Number of storage drives supported * Installed storage drive type *  | <ul><li>✓</li><li>60 TB</li><li>9</li><li>HDD</li></ul>         | Type *  Device class *  Backup function *  Backup features   | NAS Small & Medium Business  ✓ Cloud, iSCSI LUN   |
| Supported storage drive types * Bad block scan   | HDD & SSD<br>✓  | Buzzer<br>Multilingual support<br>Snapshot   | <b>* * * *</b>  |
| Disk roaming   | ✓   | Web-based management   | <b>*</b>  |
| Processor Processor manufacturer *   | Annapurna Labs  | Security algorithms  | 256-bit AES, FIPS 140-2, HTTPS,<br>SNMPv2, SNMPv3, SSH, SSL/TLS   |
| Processor family * Processor model * Processor frequency * Processor architecture  | Annapurna Labs<br>Alpine AL-324<br>1.7 GHz<br>ARM Cortex-A57    | Access Control List (ACL) Reset button On/off switch Built-in FTP server   | \frac{1}{4}   |
| Memory   |   | Duran and de   | Apple Safari 7+, Google Chrome,   |
| Internal memory type Maximum RAM supported Memory slots Internal memory * Memory form factor Flash memory  | DDR4 16 GB 1 4 GB SO-DIMM 512 MB                                | System log Hot spare S.M.A.R.T. support Share folder USB copy function   | Microsoft Internet Explorer 10+, Mozilla Firefox  ✓  ✓  CIFS/SMB  |
| Network  |   | Software   |   |
| Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max)  | 100,1000,2500,10000 Mbit/s 10000 Mbit/s                         | Operating system installed * Operating system version Windows operating systems supported                                    | QNAP Turbo System<br>4.4.2<br>Windows 10, Windows 7, Windows 8  |
| DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready   | 1<br>1<br>1<br>1  | Linux operating systems supported  Mac operating systems supported   | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina |

| Network  |   | Software  |  |
|--|---|---|--|
| Supported network protocols  Link aggregation  Load balancing system  Dynamic DNS (DDNS)  WLAN adapter supported                   | Server operating systems supported  Power  Power  Power supply location Power supply unit (PSU) capacit Number of power supply units AC input voltage Fan voltage  Yeight & dimensions Width * Depth * Height *  Packaging content External power adapter  Operational conditions Operating temperature (T-T) | Server operating systems supported                            | Windows Server 2008 R2, Windows<br>Server 2012, Windows Server 2012<br>R2, Windows Server 2016, Windows<br>Server 2019 |
|  |   | Power   |  |
|  |   | Power supply location   | External   |
| Ports & interfaces   |   | Power supply unit (PSU) capacity                              | 120 W  |
| USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Fiber ports quantity Fiber optic connector Ethernet LAN (RJ-45) ports * |   | AC input voltage  | 1<br>100 - 240 V<br>12 V   |
|  |   | Weight & dimensions   |  |
|  |   | Depth *   | 224.6 mm<br>224.1 mm<br>182.7 mm   |
|  |   | Packaging content   |  |
|  |   | External power adapter  | ✓  |
|  |   | Operational conditions  |  |
|  |   | Operating temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C<br>5 - 95%   |

