## j5create

## j5create JCD372 laptop dock/port replicator USB 3.2 Gen 2 (3.1 Gen 2) Type-C Silver

Brand : j5create

Product code: JCD372

Product name : JCD372

- SuperSpeed+ USB  $^{\tiny M}$  3.1 Gen 2 provides up to 10 Gbps transfer speeds, which is 2x faster than USB  $^{\tiny M}$  3.0, and 20x faster than USB  $^{\tiny M}$  2.0

- Backwards compatibility with USB<sup>™</sup> 3.1 Gen 1, and 3.0 hosts and devices
- 90-degree right angle connector to prevent cable damage due to bending
- Supports HDMI<sup>™</sup> resolutions up to 4K @ 30 Hz
- Two USB<sup>™</sup> 3.1 Gen 2 Type-A ports for everyday peripherals

- Memory card reader/writer slots allow for external memory access up to 2 TB, supporting SD<sup>™</sup> 3.0

- UHS-I with data transfer speeds up to 104 Mbps
- Plug-and-play, no driver installation required

USB-C 3.1 SuperSpeed+ Multi-Adapter

j5create JCD372. Host interface: USB 3.2 Gen 2 (3.1 Gen 2) Type-C. Product colour: Silver, Compatible memory cards: MicroSD (TransFlash), SD, HD type: 4K Ultra HD. Power supply type: USB. Windows operating systems supported: Windows 10. Width: 112 mm, Depth: 29.5 mm, Height: 10 mm





## Ports & interfaces

Forts & interfaces		Soltware
Host interface * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	USB 3.2 Gen 2 (3.1 Gen 2) Type-C 2	Windows operatin supported Mac operating sys
HDMI ports quantity *	1	Operational con
USB Type-C DisplayPort Alternate Mode	✓	Operating temperation
Performance		Storage temperation Operating relative
Card reader integrated *	1	Storage relative h
Compatible memory cards HD type	MicroSD (TransFlash), SD 4K Ultra HD	Weight & dimen
Number of displays supported	1	Width
Product colour *	Silver	Depth
Hub interfaces	HDMI, USB 3.2 Gen 2 (3.1 Gen 2) Type-A	Height
Plug and Play		Packaging data
	Acrylonitrile butadiene styrene (ABS), Aluminium	Quantity per pack
Housing material		Other features
Power		Cable length
Power supply type	USB	Maximum operatir

Software	
Windows operating systems supported	Windows 10
Mac operating systems supported	4
Operational conditions	
Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-1 - 41 °C -17 - 68 °C 0 - 85% 0 - 85%
Weight & dimensions	
Width Depth Height	112 mm 29.5 mm 10 mm
Packaging data	
Quantity per pack	1 pc(s)
Other features	
Cable length Maximum operating temperature	0.2 m -41 °C

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.