

Hypertec Transceiver- 10G MR SFP+ 1547.72 100 GHz Cisco ONS Compatible

Brand : Hypertec

Product code: ONS-SC+10G-47.7-HYP

Product name : Hypertec Transceiver- 10G MR SFP+ 1547.72 100 GHz Cisco ONS Compatible



Transceiver- 10G MR SFP+ 1547.72 100 GHz Cisco ONS Compatible

Hypertec Transceiver- 10G MR SFP+ 1547.72 100 GHz Cisco ONS Compatible:

Delivering the same high Service levels, Lifetime Warranty, and Technical Support as Hypertec Memory and SSDs, Hypertec Transceivers provide a cost-effective equivalent to over 1,300 market-leading OEM part codes.

Hypertec Transceiver- 10G MR SFP+ 1547.72 100 GHz Cisco ONS Compatible. SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Product colour: Silver, Housing material: Metal, Form factor: SFP+. Input voltage: 3.3 V. Compliance certificates: Federal Communications Commission (FCC), RoHS, CE. Weight: 20 g

| Performance                          |                     | Features                          |                                                   |
|--------------------------------------|---------------------|-----------------------------------|---------------------------------------------------|
| SFP transceiver type *               | Fiber optic         | Housing material                  | Metal                                             |
| Maximum data transfer rate *         | 10000 Mbit/s        | Form factor                       | SFP+                                              |
| Interface type *                     | SFP+                | Plug and Play                     | ✓                                                 |
| Single-mode fiber (SMF) supported    | ✓                   | Hot-Plug support                  | ✓                                                 |
| Fiber optic connector                | LC                  | Hot-swap                          | ✓                                                 |
| SFP transceiver standard             | DWDM                | Easy to install                   | ✓                                                 |
| Maximum transfer distance            | 80000 m             | Mean time between failures (MTBF) | 3000000 h                                         |
| Wavelength                           | 1547.72 nm          | Power                             |                                                   |
| Tx wavelength (max)                  | 1547.72 nm          | Input voltage                     | 3.3 V                                             |
| Rx wavelength (max)                  | 1547.72 nm          | Certificates                      |                                                   |
| Ethernet LAN                         | ✓                   | Compliance certificates           | Federal Communications Commission (FCC), RoHS, CE |
| Ethernet interface type              | 10 Gigabit Ethernet | Operational conditions            |                                                   |
| Fiber ethernet cabling technology    | 10GBASE             | Operating temperature (T-T)       | 0 - 70 °C                                         |
| Digital Diagnostics Monitoring (DDM) | ✓                   | Storage temperature (T-T)         | -40 - 85 °C                                       |
| Features                             |                     | Weight & dimensions               |                                                   |
| Product colour                       | Silver              | Weight                            | 20 g                                              |
|                                      |                     | Packaging content                 |                                                   |
|                                      |                     | Quantity per pack                 | 1 pc(s)                                           |



5050914238049

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.