QNAP

QNAP TS-H3087XU-RP NAS Rack (4U) Intel Xeon E E-2378 64 GB DDR4 96 TB QuTS hero Black, White

Brand: QNAP Product code: TS-H3087XU-RP-E2378-64G/96TB-

Product name: TS-H3087XU-RP

Intel Xeon E-2378, 64 GB ECC DDR4, 5GB Flash, 24 x 3.5" SATA + 6 x 2.5" SATA, RJ-45, USB 3.2 Gen 2, 4U, 21.78 kg

QNAP TS-H3087XU-RP. Type: NAS. Chassis type: Rack (4U). Device class: Large Enterprise Business. Processor family: Intel Xeon E, Processor model: E-2378, Processor frequency: 2.6 GHz. Internal memory: 64 GB, Internal memory type: DDR4. Total installed storage capacity: 96 TB. Operating system installed:



Storage		Performance	
-	Serial ATA	Backup function *	1
Storage drive interface * Supported storage drive interfaces	Serial ATA	Backup function ** Backup features	Cloud, iSCSI LUN
Storage drive sizes supported	2.5,3.5"	Multilingual support	✓
System drive sizes supported	3.5"	Number of users	16000 user(s)
RAID support *	√	Snapshot	10000 user(s) ✓
RAID levels	1, 5, 6, 10, 50, 60, JBOD	Management protocols	SMB/CIFS, AFP, NFS
Online RAID expansion	√ 1, 3, 0, 10, 30, 00, jb0b	Web-based management	✓
RAID rebuild	,	Share folder access right	*
NAID TEDUNU	FAT32, HFS+, NTFS, ZFS, exFAT,	management	✓
Supported file systems	ext3, ext4	Security algorithms	HTTPS, SNMPv2, SNMPv3, SSH
Storage drives installed *	×	Access Control List (ACL)	✓
Total installed storage capacity *	96 TB	Reset button	✓
Number of storage drives supported	30	On/off switch	✓
*	30	Built-in FTP server	✓
Installed storage drive type *	×		Apple Safari (latest version), Google
Supported storage drive types *	HDD & SSD	Browser supported	Chrome (latest version), Microsoft
Auto-rebuild	1	••	Edge (latest version), Mozilla Firefox (latest version)
Disk roaming	1	System log	√
Processor		Hot spare	,
Processor manufacturer *	Intel	Disk scan	·
Processor family *	Intel Xeon E	S.M.A.R.T. support	·
Processor model *	E-2378	Share folder	Thick, Thin
Processor frequency *	2.6 GHz	Software	
Processor boost frequency	4.8 GHz		
Processor cores	8	Operating system installed *	QuTS hero
Processor threads	16	Operating system version	h5.0.0
Processor cache	16 MB		
CPU configuration (max)	1		
Memory			
Internal memory *	64 GB		
Internal memory type	DDR4		
Maximum RAM supported	128 GB		
Memory slots	4		
Memory form factor	UDIMM		
ECC	√		
Flash memory	5000 MB		
Network			
Ethernet LAN *	1		
Ethernet LAN data rates	100,1000,2500 Mbit/s		
Edicinet Enit data rates	100,1000,2000 1.10140		

Matanada		Coffee	
Network Conner othernet cabling technology	10CDACE T	Software	Windows 10 Windows 10
Copper ethernet cabling technology DHCP server iSCSI support Supported network protocols Dynamic DNS (DDNS)	10GBASE-T ✓ ✓ IPv4, IPv6 ✓		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core,
Ports & interfaces			Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro
USB port * USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity Ethernet LAN (RJ-45) ports * Number of SATA III connectors PCI Express x8 (Gen 4.x) slots	4 4 30 1	Windows operating systems supported	x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7
Design			Professional x64, Windows 7 Starter, Windows 7 Starter x64
Chassis type * Cooling type * Product colour Number of fans Fan diameter	Rack (4U) Active Black, White 4 fan(s) 8 cm		Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64 CentOS 7.0, Ubuntu 14.04,
LED indicators	HDD, LAN, Status, USB	Linux operating systems supported	openSUSE 12.1, openSUSE 12.2
Performance Type * Device class *	NAS Large Enterprise Business	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
		Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Other operating systems supported	IBM AIX 7.1, Solaris 10
		Power	
		Power supply location Power supply unit (PSU) capacity	Built-in 800 W 2
		Power supply location Power supply unit (PSU) capacity Number of power supply units	
		Power supply location Power supply unit (PSU) capacity	800 W
		Power supply location Power supply unit (PSU) capacity Number of power supply units Weight & dimensions Width * Depth * Height * Weight	800 W 2 483 mm 630 mm 178 mm 21.8 kg
		Power supply location Power supply unit (PSU) capacity Number of power supply units Weight & dimensions Width * Depth * Height * Weight Package weight	800 W 2 483 mm 630 mm 178 mm 21.8 kg
		Power supply location Power supply unit (PSU) capacity Number of power supply units Weight & dimensions Width * Depth * Height * Weight Package weight Packaging content Cables included Power cables quantity Number of screws	800 W 2 483 mm 630 mm 178 mm 21.8 kg 29.6 kg AC, LAN (RJ-45)
		Power supply location Power supply unit (PSU) capacity Number of power supply units Weight & dimensions Width * Depth * Height * Weight Package weight Packaging content Cables included Power cables quantity	800 W 2 483 mm 630 mm 178 mm 21.8 kg 29.6 kg AC, LAN (RJ-45)

Operating temperature (T-T)

0 - 40 °C

Operational conditions

Operating relative humidity (H-H) \$5 - 95% Storage temperature (T-T) \$-20 - $70\ ^{\circ}\text{C}$

