

QNAP TVS-h1688X-W1250-32G 144TB (WD RED PRO) 16-Bay TurboNAS (12 x 3.5 HDD + 4 x 2.5 SSD); SATA 6G; Intel Xeon W-1250 6 cores 12 threads 3.3 GHz (boost up to 4.7 GHz); 32GB DDR4 ECC RAM (max. 128GB); 4 x 2.5GbE; 2 x 10GBASE-T 10GbE; 2 x M.2 22110/2280 N NAS Tower Ethernet LAN Black







Brand: QNAP Product code: TVS-H1688X-W1250-32G/144TB-REDPR

Product name: TVS-h1688X-W1250-32G 144TB (WD RED PRO) 16-Bay TurboNAS (12 x 3.5 HDD + 4 x 2.5 SSD); SATA 6G; Intel Xeon W-1250 6 cores 12 threads 3.3 GHz (boost up to 4.7 GHz); 32GB DDR4 ECC RAM (max. 128GB); 4 x 2.5GbE; 2 x 10GBASE-T 10GbE; 2 x M.2 22110/2280 N

- Attain quad-port Thunderbolt™ 3 connectivity by installing two QXP-T32P expansion cards in the PCle Gen 3 x4 slots
- Two 10GBASE-T and four 2.5GbE LAN ports accelerate virtualization, intensive file access, large backup/restoration tasks, and media transfer
- PCIe slots allow for installing 5/10/25/40GbE adapters, QM2 cards, or graphics cards to increase application performance
- $^4$ K media playback and real-time transcoding; directly output videos to an HDMI display (up to  $^4$ K @30Hz)
- Supports virtual machines and containerized apps, centralized storage, backup, sharing, disaster recovery, and storage expansion
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
- Intel Xeon W-1250 6-core (3.3 GHz), Intel UHD Graphics P630, 4 x Long-DIMM DDR4, LCD, 6x USB 3.2 Gen 2, HDMI, 550 W

Storage		Design	
Storage drive interface *	Serial ATA II, Serial ATA III	Cable lock slot	✓
Supported storage drive interfaces	Serial ATA II, Serial ATA III	Cable lock slot type	Kensington
Storage drive sizes supported	2.5,3.5,M.2	Performance	
Number of M.2 (M & B) slots RAID support *	2 ✓	Type * Backup function *	NAS
RAID levels Online RAID migration Online RAID expansion RAID rebuild	0, 1, 5, 6, 10, 50, 60, JBOD	Backup function  Backup features  Buzzer  Multilingual support	Cloud, USB drive, iSCSI LUN
Hot-swap drive bays	4	Noise level	25.8 dB
Supported file systems	FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4	Third-party support Snapshot	1
Storage drives installed *	✓	Management protocols	SNMP
Total installed storage capacity *	144 TB	Web-based management	✓
Number of storage drives supported *	16	Share folder access right management	✓
Supported storage drive types * Auto-rebuild	HDD & SSD ✓	Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
Bad block scan	4	Access Control List (ACL)	✓
	*	Reset button	✓
Processor		On/off switch	✓
Processor manufacturer *	Intel	Built-in BitTorrent client	✓
Processor family *	Intel® Xeon®	Built-in FTP server	✓
Processor model * Processor frequency *	W-1250 3.3 GHz	Browser supported	Safari, Google Chrome, Internet Explorer, Mozilla Firefox
Processor boost frequency	4.7 GHz	System log	✓
Processor cores	6	Hot spare	✓
Processor threads	12	S.M.A.R.T. support	✓
Processor cache	12 MB	Universal Plug and Play (UPnP)	✓

_			
Processor		Performance	
CPU configuration (max)	1	USB copy function	✓
On-board graphics card model	Intel UHD Graphics P630	Software	
Memory		Operating system installed *	QuTS hero
Internal memory type	DDR4	Operating system version	4.5.0
Maximum RAM supported Memory slots	128 GB 4	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Internal memory *	32 GB	Linux operating systems supported	✓
Memory form factor	UDIMM	Mac operating systems supported	<b>V</b>
ECC	✓		Windows Server 2008 R2, Windows Server 2012, Windows Server 2012
Flash memory  Network	5000 MB	Server operating systems supported	R2, Windows Server 2016, Windows Server 2019
	,	Other operating systems supported	✓
Ethernet LAN * Ethernet LAN data rates	100,1000,2500,10000 Mbit/s	Power	
Ethernet LAN data rate supported		Power supply location	Built-in
(max)	10000 Mbit/s	Power supply unit (PSU) capacity	550 W
DHCP client	✓	Power consumption (typical)	97.492 W
DHCP server	✓	Power consumption (sleep)	91.26 W
Jumbo frames support	✓	AC input voltage	100 - 240 V
iSCSI support	✓	Fan voltage	12 V
Wake-on-LAN ready	<b>V</b>	Weight & dimensions	
Link aggregation	<b>V</b>	Width *	369.9 mm
Load balancing system	<b>V</b>	Depth *	319.8 mm
Dynamic DNS (DDNS) WLAN adapter supported	4	Height *	303.8 mm
Ports & interfaces	•	Packaging content	
USB port *	1	Cables included	AC, LAN (RJ-45)
USB 3.2 Gen 2 (3.1 Gen 2) Type-A		Power cables quantity	1
ports quantity	4	Number of screws	72
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Processor special features	
HDMI ports quantity	1	Embedded options available	×
HDMI version	1.4b	Enhanced Intel SpeedStep Technology	✓
Ethernet LAN (RJ-45) ports *	6	Execute Disable Bit	✓
PCI Express x4 (Gen 3.x) slots	2	Idle States	✓
PCI Express x8 (Gen 3.x) slots	1	Intel 64	✓
Design		Intel Clear Video Technology	✓
Chassis type *	Tower	Intel Trusted Execution Technology	✓
Cooling type *	Active	Intel Virtualization Technology (VT-	✓
Product colour	Black	x) Intel Virtualization Technology for	
Number of fans	5 fan(s)	Directed I/O (VT-d)	✓
Fan diameter Fan diameter 2	8 cm 9.7 cm	Intel VT-x with Extended Page	<b>✓</b>
LED indicators	HDD, LAN, Status, System, USB	Tables (EPT)	·
Built-in display	✓	Operational conditions	
Display type	LCD	Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Storage temperature (T-T)	-20 - 70 °C

