

QNAP TVS-472XT-I3-4G/40TB-REDPRO NAS/storage server Tower Ethernet LAN Black i3-8100T





Brand : QNAP **Product code:** TVS-472XT-I3-4G/40TB-REDPRO

×

Product name: TVS-472XT-I3-4G/40TB-REDPRO

- High-speed Thunderbolt 3 with SMB protocol, allowing Mac and Windows users to collaborate on media editing
- 5-speed 10GBASE-T RJ45 connectivity accelerates virtualization applications and file sharing across teams and devices
- PCIe expandability allows for graphics cards or $40\text{GbE}/\ 25\text{GbE}/\ 10\text{GbE}$ adapters to increase application performance
- Install M.2 PCIe (Gen 3 x2, 2 GB/s) NVMe SSDs (sold separately) to set up caching or storage pools, improving file access efficiency
- 4 K media playback and real-time transcoding; directly view creative works on an HDTV via HDMI 2.0 (4K $^{\circ}$ 60Hz) output
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks

Intel Core i3-8100T, 4 GB DDR4, 4x 3.5", 2x M.2, RJ-45, Thunderbolt, PCIe, USB 3.2, HDMI, $188.2\times199.3\times279.6$ mm

Storage		Design	
Storage drive size Storage drive sizes supported Number of system drives installed System drive capacity	Serial ATA II, Serial ATA III Serial ATA II, Serial ATA III 2.5/3.5" 2.5,3.5" 1 5 GB	Fan diameter 2 LED indicators Built-in display Display type Cable lock slot Cable lock slot type	6 cm HDD, LAN, Status, USB ✓ LCD ✓ Kensington
Number of M.2 (M & B) slots	2	Performance	
RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive type *	ed * 4 rted 4 HDD	Type * Device class * Backup function * Backup features Buzzer Multilingual support Noise level Security algorithms Access Control List (ACL) Reset button On/off switch Built-in FTP server Browser supported	NAS Small & Medium Business Cloud, iSCSI LUN 21.2 dB 256-bit AES, HTTPS, SSL/TLS Mozilla Firefox, Microsoft Edge,
Processor		System log	Google Chrome, Apple Safari
Processor manufacturer * Intel Processor generation 8th gen Intel® Core™ i3 Processor family * Intel® Core™ i3 Processor model * i3-8100T	8th gen Intel® Core™ i3 Intel® Core™ i3	Hot spare S.M.A.R.T. support Share folder USB copy function	✓ ✓ CIFS/SMB ✓
Processor frequency * Processor cores	3.1 GHZ 4	Software	
Processor threads Processor cache Bus type Configurable TDP-down frequency CPU configuration (max) Number of processors supported On-board graphics card model	ssor threads 4 ssor cache 6 MB ype DMI3 gurable TDP-down frequency 2.4 GHz configuration (max) 1 per of processors supported 1	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported	QNAP Turbo System 4.4.0 Windows 10, Windows 7, Windows 8 ✓
Memory			
Internal memory type	DDR4		

Momory		Software	
Memory	C4 CD	SULWATE	M 00 V 10 10 V
Maximum RAM supported	64 GB		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Memory slots	2 4 CP		Sierra, Mac OS X 10.13 High Sierra,
Internal memory *	4 GB	Mag apparating quetamag gunnarted	Mac OS X 10.14 Mojave, Mac OS X
Memory form factor	SO-DIMM 5000 MB	Mac operating systems supported	10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac
Flash memory Network	3000 MB		OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big
Ethernet LAN *	✓		Sur
Ethernet LAN data rates	10,100,1000,2500,5000,10000 Mbit/s	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2,
Ethernet LAN data rate supported (max)	10000 Mbit/s		Windows Server 2016
DHCP client	✓	Power	
DHCP server	✓	Power supply location	Built-in
Jumbo frames support	✓	Power supply unit (PSU) capacity	250 W
iSCSI support	✓	Number of power supply units	1
Wake-on-LAN ready	✓	Power consumption (typical)	37.32 W
Link aggregation	✓	Power consumption (sleep)	24.14 W
Load balancing system	✓	AC input voltage	100-240 V
Dynamic DNS (DDNS)	✓	Fan voltage	12 V
WLAN adapter supported	✓	Weight & dimensions	
Ports & interfaces		Width *	199.3 mm
USB port *	√	Depth *	279.6 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	1	Height *	188.2 mm
ports quantity	1	Weight	5.4 kg
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Packaging content	
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Cables included Power cables quantity	AC, LAN (RJ-45) 1
HDMI ports quantity	1	Processor special features	
HDMI version	2.0	Embedded options available	✓
Ethernet LAN (RJ-45) ports *	3	Enhanced Intel SpeedStep	1
Thunderbolt 3 ports quantity	2	Technology	*
PCI Express x4 (Gen 3.x) slots	1	Execute Disable Bit	✓
Design		Idle States	V
Chassis type *	Tower	Intel 64	V
Cooling type *	Active	Intel Clear Video Technology	V
Product colour	Black	Intel Enhanced Halt State	✓
Number of fans Fan diameter	3 fan(s) 12 cm	Intel Identity Protection Technology version	1.00
		Intel Secure Key Technology version	
		Intel Stable Image Platform Program (SIPP)	
		Intel Stable Image Platform Program (SIPP) version	0.00
		Intel Trusted Execution Technology	X
		Intel TSX-NI	X
		Intel TSX-NI version	0.00
		Intel Virtualization Technology (VT-x)	1
		Intel Virtualization Technology for Directed I/O (VT-d)	1
		Intel VT-x with Extended Page Tables (EPT)	✓
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Storage temperature (T-T)	-20 - 70 °C

