

QNAP QVP-21C NAS/storage server Tower Ethernet LAN Black J6412



Brand : QNAP

Product code: QVP-21C

Product name : QVP-21C

Intel Celeron J6412, Intel UHD Graphics, 2 x SO-DIMM DDR4, 2x RJ45, 2x USB 2.0, 2x USB 3.2 Gen 2, 2x HDMI, Tower, QVR Pro OS

QNAP QVP-21C. Supported storage drive types: HDD & SSD, Supported storage drive interfaces: M.2, Serial ATA III, Storage drive sizes supported: 2.5,3.5,M.2. Processor family: Intel® Celeron®, Processor manufacturer: Intel, Processor model: J6412. Internal memory: 8 GB, Internal memory type: DDR4, Memory clock speed: 3200 MHz. Ethernet LAN data rates: 2500 Mbit/s. HDMI version: 1.4b

Storage		Ports & interfaces	
Supported storage drive interfaces	M.2, Serial ATA III	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
Storage drive sizes supported	2.5,3.5,M.2	HDMI ports quantity	2
RAID support *	✓	HDMI version	1.4b
RAID levels	0, 1, 5+HS, 5, 6, 10+HS, 10, JBOD	Ethernet LAN (RJ-45) ports *	2
Online RAID migration	✓	Design	
Hot-swap drive bays	✓	Chassis type *	Tower
Supported file systems	ext4	Cooling type *	Active
Storage drives installed *	✗	Product colour	Black
Number of storage drives supported *	2	Number of fans	1 fan(s)
Installed storage drive type *	✗	Fan diameter	7 cm
Supported storage drive types *	HDD & SSD	LED indicators	✓
Processor		Performance	
Processor manufacturer *	Intel	Type *	Storage server
Processor family *	Intel® Celeron®	Device class *	Home & Home Office
Processor model *	J6412	Backup function *	✓
Processor boost frequency	2.6 GHz	Buzzer	✓
Processor cores	4	Noise level	15.4 dB
On-board graphics card model	Intel® UHD Graphics	Video input channels	8 channels
Memory		Snapshot	✓
Internal memory type	DDR4	Reset button	✓
Memory clock speed	3200 MHz	On/off switch	✓
Maximum RAM supported	16 GB	S.M.A.R.T. support	✓
Memory slots	2	Software	
Internal memory *	8 GB	Operating system installed *	QVR Pro
Memory form factor	SO-DIMM	Power	
Flash memory	4000 MB	Power consumption (typical)	60 W
Network		AC input voltage	100 - 240 V
Ethernet LAN *	✓	Weight & dimensions	
Ethernet LAN data rates	2500 Mbit/s	Width *	102 mm
DHCP server	✓	Depth *	220.5 mm
Ports & interfaces		Height *	169.2 mm
USB port *	✓	Weight	1.57 kg
USB 2.0 ports quantity	2	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%



4711103084366

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date