

(max)

QNAP TS-H2477XU-RP-3700X-32G/288TB-EX NAS/storage server Rack (4U) Ethernet LAN Black





Brand: QNAP Product code: TS-H2477XU-RP-3700X-32G/288TB-EX

Product name: TS-H2477XU-RP-3700X-32G/288TB-EX

- Two built-in 10GbE SFP+ ports support iSER and empower bandwidth-demanding applications for virtualization, intensive file access, and large backup/restoration tasks
- PCIe slots allow for installing 5/10/25GbE adapters, QM2 cards, or Fibre Channel cards to increase application potential and performance
- SSD cache acceleration improves random read performance to boost IOPS-demanding applications
- Supports storage for virtualization, and directly hosts virtual machines and containers
- Cloud storage gateways realize hybrid cloud applications by working with the cache space reserved on NAS to ensure low-latency data access to the cloud
- Experience a business-class backup center, supporting backup/restore of cloud data and VMs (including Google Workspace, Microsoft 365, VMware and Hyper-V)

AMD Ryzen 7 3700X, 32 GB DDDR4, 5 GB, 24x 3.5" SATA, 1G RJ-45, 10G SFP+, PCIe, USB, 4U, 176.15×481.04×672.02 mm

| Storage | | Ports & interfaces | |
|---|---|--|--|
| Supported storage drive interfaces Storage drive sizes supported Storage drive sizes supported 2.5,3.5" RAID support * RAID levels 0, 1, 5, 6, 10, 50, 60 Online RAID migration Online RAID expansion Hot-swap drive bays Supported file systems FAT32, HFS+, NTFS, ZFS, ext3, ext4 Storage drives installed * Total installed storage capacity * Number of storage drives supported Number of storage drives supported 24 | 2.5,3.5" ✓ | Fiber optic connector Ethernet LAN (RJ-45) ports * PCI Express x4 (Gen 3.x) slots PCI Express x8 (Gen 3.x) slots | SFP+ 2 2 2 |
| | Chassis type * Cooling type * Product colour Number of fans Fan diameter LED indicators | Rack (4U) Active Black 4 fan(s) 9.2 cm ✓ | |
| to the line of the control of the control of | LIDE | Performance | |
| Installed storage drive type * Supported storage drive types * Auto-rebuild Bad block scan Disk roaming Processor Processor manufacturer * Processor family * Processor model * Processor frequency * | HDD HDD & SSD ✓ ✓ AMD AMD Ryzen™ 7 3700X 3.6 GHz | Type * Device class * Backup function * Backup features Buzzer Multilingual support Snapshot Web-based management Security algorithms Reset button | NAS Large Enterprise Business Cloud, iSCSI LUN 256-bit AES, HTTPS, SSH, SSL/TLS |
| Processor boost frequency Processor cores Processor threads | 4.4 GHz 8 16 | On/off switch Browser supported | Internet Explorer 10+, Chrome, Safari 7+, Firefox |
| Memory | | System log Hot spare | √ |
| Internal memory type Maximum RAM supported | DDR4 128 GB | S.M.A.R.T. support Universal Plug and Play (UPnP) | * |
| Memory slots | 4 | Software | |
| Internal memory * Memory form factor Flash memory | 32 GB UDIMM 5000 MB | Operating system installed * Operating system version Windows operating systems | QuTS hero 4.5 |
| Network | | supported | Windows 10, Windows 7, Windows 8 |
| Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) | 1000,10000 Mbit/s 10000 Mbit/s | Linux operating systems supported | ✓ |

| Network | | Software | |
|--|-------------------------------------|---|---|
| DHCP client DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready Supported network protocols | ✓ ✓ ✓ FTP/FTPS, HTTP/HTTPS | Mac operating systems supported | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur Windows Server 2008 R2, Windows Server 2012 |
| Link aggregation Load balancing system | 1 | Server operating systems supported | R2, Windows Server 2016, Windows Server 2019 |
| Dynamic DNS (DDNS) | V | Power | |
| WLAN adapter supported Ports & interfaces | √ | Power supply location Power supply unit (PSU) capacity | Built-in 800 W |
| USB port * | 1 | Number of power supply units | 2 |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4 | AC input voltage Fan voltage | 100-240 V 12 V |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 1 | Weight & dimensions | |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity | 1 | Width * Depth * | 481 mm 672 mm |
| Fiber ports quantity | 2 | Height * Weight | 176.2 mm 22.7 kg |
| | | Packaging content | |
| | | Cables included Power cables quantity Number of screws | AC, LAN (RJ-45) 2 192 |
| | | Operational conditions | |
| | | Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) | 0 - 40 °C 5 - 95% -20 - 70 °C |

