

QNAP TVS-472XT-I3-4G/48TB-REDPLUS NAS/storage server Tower Ethernet LAN Black i3-8100T





Brand: QNAP

Product code: TVS-472XT-I3-4G/48TB-REDPLUS

×

Product name: TVS-472XT-I3-4G/48TB-REDPLUS

- High-speed Thunderbolt 3 with SMB protocol, allowing Mac and Windows users to collaborate on media editing
- $\hbox{-} 5\hbox{-speed 10GBASE-T RJ45 connectivity accelerates virtualization applications and file sharing across teams and devices}\\$
- PCIe expandability allows for graphics cards or $40\text{GbE}/\ 25\text{GbE}/\ 10\text{GbE}$ adapters to increase application performance
- Install M.2 PCIe (Gen 3 x2, 2 GB/s) NVMe SSDs (sold separately) to set up caching or storage pools, improving file access efficiency
- 4K media playback and real-time transcoding; directly view creative works on an HDTV via HDMI 2.0 (4K @60Hz) output
- Snapshots fully record system status and data, allowing you to protect files and data from accidental deletion and malware attacks

Intel Core i3-8100T, 4 GB DDR4, 4x 3.5", 2x M.2, RJ-45, Thunderbolt, PCIe, USB 3.2, HDMI, $188.2\times199.3\times279.6$ mm

Storage		Design	
Supported storage drive interfaces Storage drive size Storage drive sizes supported Number of system drives installed System drive capacity	Serial ATA II, Serial ATA III Serial ATA II, Serial ATA III 2.5/3.5" 2.5,3.5" 1 5 GB	Fan diameter 2 LED indicators Built-in display Display type Cable lock slot Cable lock slot type	6 cm HDD, LAN, Status, USB ✓ LCD ✓ Kensington
Number of M.2 (M & B) slots	2	Performance	
RAID support * RAID levels Online RAID migration Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives installed * Number of storage drives supported * Installed storage drive type * Supported storage drive type *	Type * Device Backup Backup Buzzer Multilin Noise le Securit 48 TB Access Reset b 4 HDD Type * Device Backup Buzzer Multilin Noise le Securit Access Reset b Built-in	Device class * Backup function * Backup features	NAS Small & Medium Business Cloud, iSCSI LUN 21.2 dB 256-bit AES, HTTPS, SSL/TLS Mozilla Firefox, Microsoft Edge,
Processor		System log	Google Chrome, Apple Safari
Processor manufacturer * Intel Processor generation 8th gen Intel® Core™ i3 Processor family * Intel® Core™ i3 Processor model * i3-8100T	Hot spare S.M.A.R.T. support Share folder USB copy function	✓ ✓ CIFS/SMB	
Processor frequency * Processor cores	3.1 GHz 4	Software	
Processor cores Processor threads Processor cache Bus type Configurable TDP-down frequency CPU configuration (max) Number of processors supported On-board graphics card model	threads 4 cache 6 MB DMI3 ble TDP-down frequency 2.4 GHz guration (max) 1 f processors supported 1	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported	QNAP Turbo System 4.4.0 Windows 10, Windows 7, Windows 8
Memory			
Internal memory type	DDR4		

Momory		Software	
Memory	C4 CD	SULWATE	M 00 V 10 10 V
Maximum RAM supported	64 GB		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Memory slots	2 4 CP		Sierra, Mac OS X 10.13 High Sierra,
Internal memory *	4 GB	Mag apparating quetamag gunnarted	Mac OS X 10.14 Mojave, Mac OS X
Memory form factor	SO-DIMM 5000 MB	Mac operating systems supported	10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac
Flash memory Network	3000 MB		OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big
Ethernet LAN *	✓		Sur
Ethernet LAN data rates	10,100,1000,2500,5000,10000 Mbit/s	Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2,
Ethernet LAN data rate supported (max)	10000 Mbit/s		Windows Server 2016
DHCP client	✓	Power	
DHCP server	✓	Power supply location	Built-in
Jumbo frames support	✓	Power supply unit (PSU) capacity	250 W
iSCSI support	✓	Number of power supply units	1
Wake-on-LAN ready	✓	Power consumption (typical)	37.32 W
Link aggregation	✓	Power consumption (sleep)	24.14 W
Load balancing system	✓	AC input voltage	100-240 V
Dynamic DNS (DDNS)	✓	Fan voltage	12 V
WLAN adapter supported	✓	Weight & dimensions	
Ports & interfaces		Width *	199.3 mm
USB port *	√	Depth *	279.6 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	1	Height *	188.2 mm
ports quantity	1	Weight	5.4 kg
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Packaging content	
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Cables included Power cables quantity	AC, LAN (RJ-45) 1
HDMI ports quantity	1	Processor special features	
HDMI version	2.0	Embedded options available	✓
Ethernet LAN (RJ-45) ports *	3	Enhanced Intel SpeedStep	1
Thunderbolt 3 ports quantity	2	Technology	*
PCI Express x4 (Gen 3.x) slots	1	Execute Disable Bit	✓
Design		Idle States	V
Chassis type *	Tower	Intel 64	V
Cooling type *	Active	Intel Clear Video Technology	V
Product colour	Black	Intel Enhanced Halt State	✓
Number of fans Fan diameter	3 fan(s) 12 cm	Intel Identity Protection Technology version	1.00
		Intel Secure Key Technology version	
		Intel Stable Image Platform Program (SIPP)	
		Intel Stable Image Platform Program (SIPP) version	0.00
		Intel Trusted Execution Technology	X
		Intel TSX-NI	X
		Intel TSX-NI version	0.00
		Intel Virtualization Technology (VT-x)	1
		Intel Virtualization Technology for Directed I/O (VT-d)	1
		Intel VT-x with Extended Page Tables (EPT)	✓
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	5 - 95%
		Storage temperature (T-T)	-20 - 70 °C

