

QNAP TS-H886 NAS Tower Ethernet LAN Black, Grey D-1622





Brand: QNAP Product code: TS-H886-D1622-16G/36TB-GOLD

Product name: TS-H886

- Four 2.5GbE ports accelerate file sharing across teams and devices, virtual machine applications or multimedia transmission
- DDR4 ECC memory detects and corrects single-bit memory errors, demonstrating high reliability for crucial applications
- Two M.2 NVMe Gen 3 x4 SSD slots (each slot providing up to 3.2 GB/s bandwidth) enable SSD caching to boost random read/write performance
- Two PCIe slots allow for 5GbE/10GbE/25GbE/40GbE adapters, QM2 cards, or entry-level graphics cards to increase application performance
- Scalable storage supporting virtual machines, containerized apps, centralized storage, backup, sharing, and disaster recovery
- QuTS hero combines ZFS advantages with the QTS App Center ecosystem to empower your business Xeon D-1622 2.6 GHz, 16 GB DDR4, 5GB, 6x 3.5" + 2x 2.5", 2x M.2, 4x 2.5G LAN, 3x USB 3.2, 231.9x292.9x319.8 mm

Storage		Performance	
Supported storage drive interfaces	Serial ATA II, Serial ATA III	Buzzer	✓
Storage drive sizes supported	2.5,3.5"	Multilingual support	✓
Number of M.2 (M & B) slots	2	Noise level	20.4 dB
RAID support *	✓	Snapshot	✓
RAID levels	0, 1, 5, 6, 10, 50, 60	Web-based management	✓
Online RAID migration Online RAID expansion	1	Security algorithms	256-bit AES, AES, FIPS 140-2, HTTPS, SSH, SSL/TLS
RAID rebuild	1	Access Control List (ACL)	✓
Hot-swap drive bays	1	Reset button	✓
Supported file systems	FAT32, HFS+, NTFS, ZFS, ext3, ext4	On/off switch	✓
Storage drives installed *	✓	Built-in FTP server	✓
Total installed storage capacity * Number of storage drives installed *	36 TB	Browser supported	Apple Safari 7+, Google Chrome, Microsoft Internet Explorer 10+,
Number of storage drives supported		Calcula	Mozilla Firefox
*	8	System log	√
Installed storage drive type *	HDD	Hot spare	√
Supported storage drive types *	HDD & SSD	S.M.A.R.T. support	✓ CIEC/CMD
Bad block scan	✓	Share folder	CIFS/SMB
Disk roaming	✓	Universal Plug and Play (UPnP)	V
Processor		USB copy function	1
Processor manufacturer *	Intel	Software	
Processor family *	Intel® Xeon® D	Operating system installed *	QNAP Turbo System
Processor model *	D-1622	Operating system version	4.5.0
Processor frequency *	2.6 GHz	Windows operating systems	Windows 10, Windows 7, Windows 8
Processor boost frequency	3.2 GHz	supported	
Processor cores	4	Linux operating systems supported	V
Processor threads Processor cache	8 6 MB	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra,
	O I I IB		,
CPU configuration (max)	1		Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
PCI Express slots version			Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
•	1	Server operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012
PCI Express slots version	1 2.0, 3.0	Server operating systems supported	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
PCI Express slots version Processor lithography	1 2.0, 3.0 14 nm		Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012
PCI Express slots version Processor lithography Processor operating modes	1 2.0, 3.0 14 nm 64-bit 37.5 x 37.5 mm 15	Server operating systems supported Power	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
PCI Express slots version Processor lithography Processor operating modes Processor package size	1 2.0, 3.0 14 nm 64-bit 37.5 x 37.5 mm		Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
PCI Express slots version Processor lithography Processor operating modes Processor package size Scalability	1 2.0, 3.0 14 nm 64-bit 37.5 x 37.5 mm 15	Power	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
PCI Express slots version Processor lithography Processor operating modes Processor package size Scalability Tcase	1 2.0, 3.0 14 nm 64-bit 37.5 x 37.5 mm 1S 83 °C	Power Power supply location	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
PCI Express slots version Processor lithography Processor operating modes Processor package size Scalability Tcase Tjunction	1 2.0, 3.0 14 nm 64-bit 37.5 x 37.5 mm 1S 83 °C 105 °C	Power Power supply location Power supply unit (PSU) capacity	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 Built-in 250 W
PCI Express slots version Processor lithography Processor operating modes Processor package size Scalability Tcase Tjunction Thermal Design Power (TDP)	1 2.0, 3.0 14 nm 64-bit 37.5 x 37.5 mm 1S 83 °C 105 °C 40 W	Power Power supply location Power supply unit (PSU) capacity Number of power supply units	Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2019 Built-in 250 W 1

Memory		Weight & dimensions	
Internal memory type	DDR4	Width *	292.9 mm
Maximum RAM supported	128 GB	Depth *	319.8 mm
Internal memory *	16 GB	Height *	231.9 mm
Memory form factor	UDIMM	Weight	8.5 kg
Flash memory	5000 MB	Packaging content	
Network		Cables included	AC, LAN (RJ-45)
Ethernet LAN *	1	Number of screws	32
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Processor special features	
DHCP client	✓		_
DHCP server	✓	Embedded options available	×
Jumbo frames support	✓	Enhanced Intel SpeedStep Technology	✓
Supported network protocols	TCP/IP, HTTP/HTTPS	Execute Disable Bit	1
Ports & interfaces		Idle States	1
USB port *	1	Intel 64	√
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	•	Intel QuickAssist Technology	×
ports quantity	3	Intel Trusted Execution Technology	✓
Ethernet LAN (RJ-45) ports *	4	Intel TSX-NI	✓
PCI Express x8 (Gen 3.x) slots	2	Intel Virtualization Technology (VT-x)	✓
Design		Intel Virtualization Technology for	
Chassis type *	Tower	Directed I/O (VT-d)	✓
Cooling type *	Active	Intel VT-x with Extended Page	1
Product colour	Black, Grey	Tables (EPT)	•
Number of fans	3 fan(s)	Intel® AES New Instructions (Intel® AES-NI)	✓
Fan diameter Fan diameter 2	8 cm 9.7 cm	Intel® Hyper Threading Technology (Intel® HT Technology)	√
LED indicators	HDD, SSD, Status	Intel® OS Guard	1
Built-in display	✓	Intel® Secure Key	1
Cable lock slot	✓	Intel® Turbo Boost Technology	2.0
Cable lock slot type	Kensington	Maximum number of PCI Express lanes	32
Performance		Thermal Monitoring Technologies	1
Type *	NAS	Memory types supported by	
Device class *	Large Enterprise Business	processor	DDR3-SDRAM, DDR4-SDRAM
Backup function *	Cloud iscelling	Operational conditions	
Backup features	Cloud, iSCSI LUN	Operating temperature (T-T)	0 - 35 °C
		Operating relative humidity (H-H)	5 - 95%
		Other features	
		Processor ARK ID	193687

